# Statement of Basis
# Automotive Coating Operations General Permit

**Permit to Construct P-2009.0147**
**Project No. 61723**

**EPSCO Powder & Industrial Coatings, LLC**
**Boise, Idaho**

**Facility ID No. 001-00155**

**Final**

**August 16, 2016**
**Darrin Pampaian, P.E.**
**Permit Writer**

The purpose of this Statement of Basis is to satisfy the requirements of IDAPA 58.01.01.et seq, Rules for the Control of Air Pollution in Idaho, for issuing air permits.

**ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE** ..... **3**
**FACILITY INFORMATION** ..... **4**
Description ..... 4
Permitting History ..... 4
Application Scope ..... 4
Application Chronology ..... 4
**TECHNICAL ANALYSIS** ..... **4**
Emissions Units and Control Devices ..... 5
Emissions Inventories ..... 5
Ambient Air Quality Impact Analyses ..... 8
**REGULATORY ANALYSIS** ..... **9**
Attainment Designation (40 CFR 81.313) ..... 9
Facility Classification AIRS/AFS ..... 9
PTC Permit to Construct (IDAPA 58.01.01.201) ..... 10
Tier II Operating Permit (IDAPA 58.01.01.401) ..... 11
Visible Emissions (IDAPA 58.01.01.625) ..... 11
Rules for the Control of Odors (IDAPA 58.01.01.775-776) ..... 11
Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70) ..... 11
PSD Classification (40 CFR 52.21) ..... 13
NSPS Applicability (40 CFR 60) ..... 13
NESHAP Applicability (40 CFR 61) ..... 13
MACT Applicability (40 CFR 63) ..... 13
Permit Conditions Review ..... 16
**PUBLIC REVIEW** ..... **17**
Public Comment Opportunity ..... 17
Public Comment Period ..... 17
**APPENDIX A – EMISSIONS INVENTORIES**

## ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE

| | |
|---|---|
| AQCR | Air Quality Control Region |
| Btu | British thermal units |
| CAS No. | Chemical Abstracts Service registry number |
| CE | Control Efficiency |
| CFR | Code of Federal Regulations |
| CO | carbon monoxide |
| DEQ | Department of Environmental Quality |
| EL | screening emission levels |
| EPA | U.S. Environmental Protection Agency |
| gal/day | gallons per calendar day |
| gal/hr | gallons per hour |
| gal/yr | gallons per consecutive 12 calendar month period |
| gr | grain (1 lb = 7,000 grains) |
| HAP | hazardous air pollutants |
| HDI | hexamethylene diisocyanate |
| hr/yr | hours per year |
| HVLP | high volume, low pressure (applies to paint guns) |
| IDAPA | a numbering designation for all administrative rules in Idaho promulgated in accordance with the Idaho Administrative Procedures Act |
| lb/gal | pounds per gallon |
| lb/hr | pounds per hour |
| LPG | Liquefied Petroleum Gas |
| MDI | methylene diisocyanate |
| MMBtu | million British thermal units |
| MSDS | Material Safety Data Sheet |
| NAICS | North American Industry Classification System |
| NESHAP | National Emission Standards for Hazardous Air Pollutants |
| $NO_2$ | nitrogen dioxide |
| $NO_X$ | nitrogen oxides |
| NSPS | New Source Performance Standards |
| PC | permit condition |
| $PM_{10}$ | particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers |
| ppm | parts per million |
| PTC | permit to construct |
| PTE | potential to emit |
| Rules | Rules for the Control of Air Pollution in Idaho |
| scf | standard cubic feet |
| SIC | Standard Industrial Classification |
| SM80 | synthetic minor facility with emissions greater than or equal to 80% of a major source threshold |
| $SO_2$ | sulfur dioxide |
| $SO_X$ | sulfur oxides |
| T/yr | tons per consecutive 12-calendar month period |
| T2 | Tier II operating permit |
| TAP | toxic air pollutants |
| TE | Transfer Efficiency |
| UTM | Universal Transverse Mercator |
| VOC | volatile organic compounds |

## FACILITY INFORMATION

### *Description*

EPSCO Powder & Industrial Coatings, LLC is a bed-lining and abrasive blasting facility with paint spray booth(s) and an abrasive blasting booth. The paint booth(s) is a pressurized rear filter wall booth(s) with glass fiber filtration media for control of particulate emissions. The abrasive blasting booth is a pressurized filter booth(s) with glass fiber filtration media for control of particulate emissions. Drying and paint curing is done in the paint booth(s). The process includes application of coatings via a HVLP (or equivalent) paint gun and an abrasive blasting operation using sand, coal slag, smelter slag, and mineral, metallic, and synthetic abrasives. In this case "or equivalent" means a paint gun that has a minimum 65% transfer efficiency as documented by the spray gun manufacturer.

### *Permitting History*

The following information was derived from a review of the permit files available to DEQ. Permit status is noted as active and in effect (A) or superseded (S).

| | |
|---|---|
| February 19, 2010 | P-2009.0147, Facility name change from EPSCO Corporation to EPSCO Powder & Industrial Coatings, LLC, Permit status (A, will become S as a result of this project) |
| February 2, 2007 | P-060057, Conversion of the existing Tier II permit to a Permit to Construct, Permit status (S) |
| August 3, 2000 | Tier II Permit No. 001-00155, Initial permit for an abrasive blasting and HVLP coating operation, Permit status (S) |

### *Application Scope*

The facility has proposed the following modifications to the equipment at the facility:

- Remove the HVLP spray paint booth from the current permit
- Include a bed lining operation in the new permit using the Automotive Coatings General Permit template

### *Application Chronology*

| | |
|---|---|
| May 25, 2016 | DEQ received an application and an application fee and a processing fee. |
| June 6 – June 21, 2016 | DEQ provided an opportunity to request a public comment period on the application and proposed permitting action. |
| June 7, 2016 | DEQ determined that the application was complete. |
| July 6 – August 5, 2016 | DEQ provided a public comment period on the proposed action. |
| August 16, 2016 | DEQ issued the final permit and statement of basis. |

## TECHNICAL ANALYSIS

The facility utilizes glass fiber filtration media for control of particulate matter emissions from the automotive coating operation as well as the abrasive blasting operation. In addition, HVLP paint guns (or equivalent) are used to minimize $PM_{10}$ and VOC emissions from painting. The HVLP (or equivalent) spray equipment will control $PM_{10}$ and VOC emissions by having more paint transfer to the desired surfaces than traditional painting equipment.

## Emissions Units and Control Devices

**Table 1 EMISSIONS UNIT AND CONTROL DEVICE INFORMATION**

| ID No. | Source Description | Control Equipment Description | Emissions Point ID No. and Description |
|---|---|---|---|
| Automotive Coating Operation | Paint spray booth(s):<br>Manufacturer(s): Colmet or equivalent<br>Model(s): IB-16-12-20-00 or equivalent<br>Note: The number of booths installed at the facility is not limited by this permit. | Paint spray booth(s) and/or preparation station filter system:<br>Booth Type(s): Rear booth filter wall<br>Particulate filtration method: Dry Filters<br>Manufacturer(s): Colmet or equivalent<br>Model(s): IB-16-12-20-00 or equivalent<br>$PM/PM_{10}$ Efficiency: 98% or greater<br><br>Coating spray gun(s):<br>Manufacturer: Graco or equivalent<br>Model: E-XP2 or equivalent<br>Type: HVLP or equivalent<br>Transfer Efficiency: 65% or greater | Paint booth exhaust stack and/or preparation station exhaust stack |
| Abrasive Blasting Operation | Abrasive Blasting Booth | Air filters | Abrasive blasting booth exhaust stack |

## Emissions Inventories

### Potential to Emit

IDAPA 58.01.01.006 defines Potential to Emit as the maximum capacity of a facility or stationary source to emit an air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the facility or source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is state or federally enforceable. Secondary emissions do not count in determining the potential to emit of a facility or stationary source.

Using this definition of Potential to Emit an emission inventory was developed for the automotive coating operation associated with this proposed project (see Appendix A for detailed potential to emit calculations). Criteria pollutant and HAPs PTE were based on the worst-case VOC, $PM_{10}$, and HAPs content for coatings as taken from the DEQ Automotive Coating EI spreadsheet (see the DEQ website).

### Uncontrolled Potential to Emit

Using the definition of Potential to Emit, uncontrolled Potential to Emit is then defined as the maximum capacity of a facility or stationary source to emit an air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the facility or source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall **not** be treated as part of its design **since** the limitation or the effect it would have on emissions **is not** state or federally enforceable.

The uncontrolled Potential to Emit is used to determine if a facility is a "Synthetic Minor" source of emissions. Synthetic Minor sources are facilities that have an uncontrolled Potential to Emit for criteria pollutants or HAPs above the applicable Major Source threshold without permit limits.

The following table presents the uncontrolled Potential to Emit for criteria pollutants as determined by DEQ staff. See Appendix A for a detailed presentation of the calculations and the assumptions used to determine emissions for each emissions unit. For this automotive coating operation uncontrolled Potential to Emit is based upon a worst-case for operation of the facility of 2,080 hrs/yr (8 hrs/day x 260 days/yr) with all coating operations occurring during this time. Since there is prep time (the time spent preparing the automobile for the application of coating) and paint drying time (the time the automobile spends in the booth with the burner operating to facilitate hardening of the coating) associated with applying coatings, this was considered to be the worst-case maximum for which emissions would occur.

Table 2 UNCONTROLLED POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS

| Emissions Unit | $PM_{10}/PM_{2.5}$ T/yr | $SO_2$ T/yr | $NO_X$ T/yr | CO T/yr | VOC T/yr | Lead lb/quarter |
|---|---|---|---|---|---|---|
| **Point Sources** | | | | | | |
| Paint spray booth(s) and/or preparation station(s) | 8.55 | 0.0 | 0.0 | 0.0 | 24.47 | 0.0 |
| **Total, Point Sources** | **8.55** | **0.00** | **0.00** | **0.00** | **24.47** | **0.00** |

The following table presents the uncontrolled Potential to Emit for HAP pollutants as determined by DEQ staff. For this automotive coating operation uncontrolled HAP emissions were calculated by using the DEQ Automotive Coating EI spreadsheet (see the DEQ website) and setting paint use to 4.0 gallons per day (as limited by the permit). Then, the worst-case maximum HAPs Potential to Emit was determined for all paints listed in the spreadsheet. As discussed previously, HAP emissions were assumed to occur during the worst-case for operation of the facility of 2,080 hrs/yr.

Table 3 UNCONTROLLED POTENTIAL TO EMIT FOR HAPs

| HAP Pollutants | PTE (T/yr) |
|---|---|
| Ethyl benzene | 0.61 |
| Methyl Isobutyl Ketone (MIBK) | 1.25 |
| Naphthalene | 2.32 |
| Toluene | 1.90 |
| Styrene | 2.49 |
| Xylene (o-, m-, p-isomers) | 2.36 |
| **Total** | **10.93** |

## Pre-Project Potential to Emit

The following table presents the pre-project Potential to Emit for criteria pollutants from all emissions units at the facility as listed in the current permit (taken from P-060057, issued 2/2/2007). See Appendix A for a detailed presentation of the calculations of these emissions for each emissions unit.

Table 4 PRE-PROJECT POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS

| Emissions Unit | $PM_{10}/PM_{2.5}$ | | $SO_2$ | | $NO_X$ | | CO | | VOC | | Lead | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr | T/yr |
| **Point Sources** | | | | | | | | | | | | |
| Abrasive blasting booth | 0.60 | 0.11 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0 |
| HVLP Spray Painting Booth (being removed) | 0.03 | 0.11 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0 |
| **Pre-Project Totals** | **0.63** | **0.22** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** |

a) Controlled average emission rate in pounds per hour is a daily average, based on the proposed daily operating schedule and daily limits.
b) Controlled average emission rate in tons per year is an annual average, based on the proposed annual operating schedule and annual limits.

## Post Project Potential to Emit

Post project Potential to Emit is used to establish the change in emissions at a facility and to determine the facility's classification as a result of this project. Post project Potential to Emit includes all permit limits resulting from this project.

The following table presents the post project Potential to Emit for criteria pollutants from all emissions units at the facility as determined by DEQ staff. See Appendix A for a detailed presentation of the calculations of these emissions for each emissions unit.

**Table 5 POST PROJECT POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS**

| Emissions Unit | $PM_{10}/PM_{2.5}$ | | $SO_2$ | | $NO_X$ | | CO | | VOC | | Lead | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr[a] | T/yr[b] | lb/hr | T/yr |
| **Point Sources** | | | | | | | | | | | | |
| Paint spray booth(s) and/or preparation station(s) | 0.04 | 0.171 | 0.000 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 5.59 | 24.47 | 0 | 0 |
| Abrasive blasting booth | 0.60 | 0.11 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0 |
| **Post-Project Totals** | **0.64** | **0.28** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **5.59** | **24.47** | **0.00** | **0.00** |

a) Controlled average emission rate in pounds per hour is a daily average, based on the proposed daily operating schedule and daily limits.
b) Controlled average emission rate in tons per year is an annual average, based on the proposed annual operating schedule and annual limits.

The following table presents the post project Potential to Emit for HAP pollutants from all emissions units at the facility as determined by DEQ staff. The DEQ Automotive Coating EI spreadsheet (see the DEQ website) was used to determine post project Potential to Emit for HAP pollutants.

**Table 6 POST PROJECT POTENTIAL TO EMIT FOR HAPs**

| HAP Pollutants | PTE (T/yr) |
|---|---|
| Ethyl benzene | 0.61 |
| Methyl Isobutyl Ketone (MIBK) | 1.25 |
| Naphthalene | 2.32 |
| Toluene | 1.90 |
| Styrene | 2.49 |
| Xylene (o-, m-, p-isomers) | 2.36 |
| **Total** | **10.93** |

**Change in Potential to Emit**

The project's change in Potential to Emit is used to determine if a public comment period may be required or if emissions modeling may be required, and to determine the processing fee per IDAPA 58.01.01.225.

The following table presents the change in the Potential to Emit for criteria pollutants as a result of this project.

**Table 7 CHANGES IN POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS**

| | $PM_{10}/PM_{2.5}$ | | $SO_2$ | | $NO_X$ | | CO | | VOC | | Lead | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | lb/hr | T/yr | lb/hr | T/yr | lb/hr | T/yr | lb/hr | T/yr | lb/hr | T/yr | lb/hr | T/yr |
| **Point Sources** | | | | | | | | | | | | |
| Pre-Project Potential to Emit | 0.63 | 0.22 | 0.0. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Post Project Potential to Emit | 0.64 | 0.28 | 0.000 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 5.59 | 24.47 | 0.00 | 0.00 |
| **Changes in Potential to Emit** | **0.01** | **0.06** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **0.00** | **5.59** | **24.47** | **0.00** | **0.00** |

**Non-Carcinogenic and Carcinogenic TAPs Potential to Emit**

Because of the daily coating material use limits imposed by DEQ, and agreed to by the facility in applying for this Automotive Coating "General Permit", no ELs specified in IDAPA 58.01.01.585 or 586 are expected to be exceeded by the facility (see Appendix A).

## *Ambient Air Quality Impact Analyses*

It needs to be determined if the PTE for the automotive coating operation and abrasive blasting operation combined triggers the requirement to perform an air impact analysis. Per DEQ policy if the PTE of a source would qualify for a Category I, Below Regulatory Concern (BRC) exemption, then DEQ is not required to assert NAAQS compliance for those pollutants under IDAPA 58.01.01.203.02. The following table compares the facility-wide annual PTE to the BRC Category I thresholds.

**Table 8 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE BRC CATEGORY I EXEMPTION THRESHOLDS**

| Pollutant | PTE (T/yr) | DEQ BRC Category I Thresholds (T/yr) | Exceeds Modeling Guideline Threshold? |
|---|---|---|---|
| $PM_{10}$ | 0.28 | 1.5 | No |
| $PM_{2.5}$ | 0.28 | 1.0 | No |
| $SO_2$ | 0.00 | 4.0 | No |
| $NO_X$ | 0.00 | 4.0 | No |
| CO | 0.00 | 10.0 | No |
| Lead | 0.00 | 0.06 | No |

Therefore, the automotive coating operation and abrasive blasting operation does not require an air impact analyses demonstrating compliance with NAAQS.

As presented previously in the DEQ Automotive Coatings EI Spreadsheet (see the DEQ website) there are no TAPs that required facility modeling for exceeding the pounds per hour screening levels provided in IDAPA 58.01.01.585 and .586. Therefore, the automotive coating operation and abrasive blasting operation does not require TAPs modeling.

## REGULATORY ANALYSIS

### *Attainment Designation (40 CFR 81.313)*

EPSCO Powder & Industrial Coatings, LLC is located in Ada County, which is designated as attainment or unclassifiable for $PM_{2.5}$, $PM_{10}$, $SO_2$, $NO_2$, CO, and Ozone. Refer to 40 CFR 81.313 for additional information.

### *Facility Classification AIRS/AFS*

"Synthetic Minor" for AIRS/AFS classification for criteria pollutants is defined as the uncontrolled Potential to Emit for criteria pollutants are above the applicable major source thresholds and the Potential to Emit for criteria pollutants fall below the applicable major source thresholds. Therefore, the following table compares the uncontrolled Potential to Emit and the Potential to Emit for criteria pollutants to the Major Source thresholds to determine if the facility will be "Synthetic Minor."

**Table 9 UNCONTROLLED PTE AND PTE FOR CRITERIA POLLUTANTS COMPARED TO THE MAJOR SOURCE THRESHOLDS**

| Pollutant | Uncontrolled PTE (T/yr) | PTE (T/yr) | Major Source Thresholds (T/yr) | Uncontrolled PTE Exceeds the Major Source Threshold and PTE Exceeds the Major Source Threshold? |
|---|---|---|---|---|
| $PM_{10}$ | 8.55 | 0.28 | 100 | No |
| $PM_{2.5}$ | 8.55 | 0.28 | 100 | No |
| $SO_2$ | 0.00 | 0.00 | 100 | No |
| $NO_X$ | 0.00 | 0.00 | 100 | No |
| CO | 0.00 | 0.00 | 100 | No |
| VOC | 24.47 | 24.47 | 100 | No |

"Synthetic Minor" for AIRS/AFS classification for HAP pollutants is defined as the uncontrolled Potential to Emit for HAP pollutants are above the applicable major source thresholds and the Potential to Emit for HAPs pollutants fall below the applicable major source thresholds. Therefore, the following table compares the uncontrolled Potential to Emit and the Potential to Emit for HAP pollutants to the Major Source thresholds to determine if the facility will be "Synthetic Minor."

**Table 10 UNCONTROLED PTE AND PTE FOR HAPs POLLUTANTS COMPARED TO THE MAJOR SOURCE THRESHOLDS**

| HAP Pollutant | Uncontrolled PTE (T/yr) | PTE (T/yr) | Major Source Thresholds (T/yr) | Uncontrolled PTE Exceeds the Major Source Threshold and PTE Exceeds the Major Source Threshold? |
|---|---|---|---|---|
| Ethyl benzene | 0.61 | 0.61 | 10 | No |
| Methyl Isobutyl Ketone (MIBK) | 1.25 | 1.25 | 10 | No |
| Naphthalene | 2.32 | 2.32 | 10 | No |
| Toluene | 1.90 | 1.90 | 10 | No |
| Styrene | 2.49 | 2.49 | 10 | No |
| Xylene (o-, m-, p-isomers) | 2.36 | 2.36 | 10 | No |
| **Total** | **10.93** | **10.93** | 25 | No |

As demonstrated in Table 9 the facility has an uncontrolled potential to emit for $PM_{10}$, $SO_2$, $NO_X$, CO, and VOC emissions are less than the Major Source thresholds of 100 T/yr for each pollutant. In addition, as demonstrated in Table 10 the facility has an uncontrolled potential for each HAP less than the Major Source threshold of 10 T/yr and for all HAPs combined less than the Major Source threshold of 25 T/yr. Therefore, this facility is not designated as a Synthetic Minor facility.

## *PTC Permit to Construct (IDAPA 58.01.01.201)*

IDAPA 58.01.01.201 Permit to Construct Required

The PTC rules under IDAPA 58.01.01.201 require that "No owner or operator may commence construction or modification of any stationary source, facility, major facility, or major modification without first obtaining a permit to construct from the Department which satisfies the requirements of Sections 200 through 228 unless the source is exempted in any of Sections 220 through 223." Therefore, DEQ staff analyzed the data from the permit application for the installation of this automotive coating operation to determine if it is exempt from obtaining a PTC according to Sections 220 through 223.

IDAPA 58.01.01.220 General Exemption Criteria for Permit to Construct Exemptions

In accordance with IDAPA 58.01.01.220.01.a, the maximum capacity of the source to emit an air pollutant under its physical and operational design without consideration of limitations on emissions such as air pollution control equipment, restrictions on hours of operation and restrictions on the type and amount of material combusted, stored, or processed shall not equal or exceed 100 tons/yr for all regulated air pollutants. As previously presented in Table 2, the proposed project results in uncontrolled potential emissions of less than 100 tons/yr for all regulated air pollutants. Therefore, the project meets the criteria set forth in Section 220 and may be exempt from PTC requirements. In addition, the criteria set forth in Section 221, 222, or 223 must be met to be exempt from PTC requirements.

IDAPA 58.01.01.221 Category I Exemption Criteria

In accordance with IDAPA 58.01.01.221.01, the maximum capacity of a source to emit an air pollutant under its physical and operational design considering limitations on emissions such as air pollution control equipment, restrictions on hours of operation and restrictions on the type and amount of material combusted, stored or processed shall be less than ten percent (10%) of the significant emission rates set out in the definition of significant at Section 006. The following table compares the post-project facility-wide annual PTE to 10% of the significance threshold listed in IDAPA 58.01.01.006.104 in order to determine if the project may qualify for a Category I exemption.

**Table 11 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE SIGNIFICANCE THRESHOLDS**

| Pollutant | PTE (T/yr) | 10% of the Significance Threshold (T/yr) | Exceeds 10% of the Significance Threshold? |
|---|---|---|---|
| $PM_{10}$ | 0.28 | 1.5 | No |
| $PM_{2.5}$ | 0.28 | 1.0 | No |
| $SO_2$ | 0.00 | 4.0 | No |
| $NO_X$ | 0.00 | 4.0 | No |
| CO | 0.00 | 10.0 | No |
| VOC | 24.47 | 4.0 | Yes |

The potential VOC emission rate of the proposed project is indicated in Table 10 above, which is above 10% of the significant emission rate listed in IDAPA 58.01.01.006.104. Therefore, the permitting of an existing automotive coating operation does not qualify for a Category I exemption.

## *Tier II Operating Permit (IDAPA 58.01.01.401)*

IDAPA 58.01.01.401 Tier II Operating Permit

The application was submitted for a permit to construct (refer to the Permit to Construct section), and an optional Tier II operating permit has not been requested. Therefore, the procedures of IDAPA 58.01.01.400–410 were not applicable to this permitting action.

## *Visible Emissions (IDAPA 58.01.01.625)*

IDAPA 58.01.01.625 Visible Emissions

The emissions from the automotive coating and abrasive blasting processes are subject to the State of Idaho visible emissions standard of 20% opacity. This requirement is assured by Permit Condition 8 and 26.

## *Rules for the Control of Odors (IDAPA 58.01.01.775-776)*

IDAPA 58.01.01.775-776 Rules for the Control of Odors

The facility is subject to the general restrictions for the control of odors from the facility. This requirement is assured by Permit Conditions 9 and 14.

## *Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70)*

IDAPA 58.01.01.301 Requirement to Obtain Tier I Operating Permit

IDAPA 58.01.01.006 defines a Tier I source as "Any source located at a major facility as defined in Section 008." IDAPA 58.01.01.008 defines a Major Facility as either:

- For HAPS a facility with the potential to emit ten (10) tons per year (T/yr) or more of any hazardous air pollutant, other than radionuclides, or

- The facility emits or has the potential to emit twenty-five (25) T/yr or more of any combination of any hazardous air pollutants, other than radionuclides.

Or, for non-attainment areas:

- The facility is located in a "serious" particulate matter ($PM_{10}$) nonattainment area and the facility has the potential to emit seventy (70) T/yr or more of $PM_{10}$, or
- The facility is located in a "serious" carbon monoxide nonattainment area in which stationary sources are significant contributors to carbon monoxide levels and the facility has the potential to emit fifty (50) T/yr or more of carbon monoxide, or
- The facility is located in an ozone transport region established pursuant to 42 U.S.C. Section 7511c and the facility has the potential to emit fifty (50) T/yr or more of volatile organic compounds, or
- The facility is located in an ozone nonattainment area and, depending upon the classification of the nonattainment area, the facility has the potential to emit the following amounts of volatile organic compounds or oxides of nitrogen; provided that oxides of nitrogen shall not be included if the facility has been identified in accordance with 42 U.S.C. Section 7411a(f)(1) or (2) if the area is "marginal" or "moderate," one hundred (100) T/yr or more, if the area is "serious," fifty (50) T/yr or more, if the area is "severe," twenty-five (25) T/yr or more, and if the area is "extreme," ten (10) T/yr or more.
- The facility emits or has the potential to emit one hundred (100) T/yr or more of any regulated air pollutant. The fugitive emissions shall not be considered in determining whether the facility is major unless the facility is a "Designated Facility":

Uncontrolled HAP emissions were calculated by using the DEQ Automotive Coating EI spreadsheet (see the DEQ website) and setting paint use to 4.0 gallons per day (as limited by the permit). Then worst-case HAP emissions were determined for all paints listed in the spreadsheet. Then emissions were assumed to occur 2,080 hours per year as a worst-case assumption.

The following table compares the post-project facility-wide annual worst-case uncontrolled emission rate for all HAPs emitted by the source to the HAPS Major Source thresholds in order to determine if the facility is a HAPs Major Source.

**Table 12 PTE FOR HAPs POLLUTANTS COMPARED TO THE HAPs MAJOR SOURCE THRESHOLDS**

| HAP Pollutants | PTE (T/yr) | Major Source Threshold (T/yr) | Exceeds the Major Source Threshold? |
|---|---|---|---|
| Ethyl benzene | 0.61 | 10 | No |
| Methyl Isobutyl Ketone (MIBK) | 1.25 | 10 | No |
| Naphthalene | 2.32 | 10 | No |
| Toluene | 1.90 | 10 | No |
| Styrene | 2.49 | 10 | No |
| Xylene (o-, m-, p-isomers) | 2.36 | 10 | No |
| **Total** | **10.93** | 25 | No |

As presented in the preceding table the PTE for each HAP is less than 10 T/yr and the PTE for all HAPs combined is less than 25 T/yr. Therefore, this facility is not a HAPs Major Source subject to Tier I permitting requirements.

As discussed previously the Business Name facility is located in XXX County (AQCR 6X), which is designated as unclassifiable/attainment for $PM_{2.5}$, $PM_{10}$, $SO_2$, $NO_X$, CO, and Ozone for federal and state criteria air pollutants. Therefore, the following table compares the post-project facility-wide annual PTE for all criteria pollutants emitted by the source to the applicable criteria pollutant Major Source thresholds in order to determine if the facility is a criteria pollutant Major Source.

**Table 13 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE CRITERIA POLLUTANT MAJOR SOURCE THRESHOLDS**

| Criteria Pollutants | PTE (T/yr) | Major Source Threshold (T/yr) | Exceeds the Major Source Threshold? |
|---|---|---|---|
| $PM_{10}$ | 0.28 | 100 | No |
| $PM_{2.5}$ | 0.28 | 100 | No |
| $SO_2$ | 0.00 | 100 | No |
| $NO_X$ | 0.00 | 100 | No |
| CO | 0.00 | 100 | No |
| VOC | 24.47 | 100 | No |

As presented in the preceding table the PTE for each criteria pollutant is less than 100 T/yr. Therefore, this facility is not a criteria pollutant Major Source subject to Tier I permitting requirements.

## *PSD Classification (40 CFR 52.21)*

40 CFR 52.21 Prevention of Significant Deterioration of Air Quality

The facility is not a major stationary source as defined in 40 CFR 52.21(b)(1), nor is it undergoing any physical change at a stationary source, not otherwise qualifying under paragraph 40 CFR 52.21(b)(1) as a major stationary source, that would constitute a major stationary source by itself as defined in 40 CFR 52. Therefore, in accordance with 40 CFR 52.21(a)(2), the PSD requirements do not apply.

## *NSPS Applicability (40 CFR 60)*

The facility is not subject to any NSPS requirements.

## *NESHAP Applicability (40 CFR 61)*

The facility is not subject to any NESHAP requirements in 40 CFR 61.

## *MACT Applicability (40 CFR 63)*

**40 CFR 63, Subpart HHHHHH** **National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources**

§ 63.11169 What is the purpose of this subpart?

In accordance with §63.11169, subpart HHHHHH establishes national emission standards for hazardous air pollutants (HAP) for area sources involved in auto body refinishing operations that encompass motor vehicle and mobile equipment spray-applied surface coating operations.

§ 63.11170 Am I subject to this subpart?

In accordance with §63.11170(a), this automotive coating operation is subject to this subpart because the facility will be operated as an area source of HAP. The facility is a source of HAP that is not a major source of HAP, is not located at a major source, and is not part of a major source of HAP emissions. In addition, the facility will perform one or more activities listed in this section, including spray application of coatings, as defined in §63.11180, to motor vehicles and mobile equipment including operations that are located in stationary structures at fixed locations.

§ 63.11171 How do I know if my source is considered a new source or an existing source?

In accordance with §63.11171(b), the automotive coating operation is the collection of mixing rooms and equipment; spray booths, curing ovens, and associated equipment; spray guns and associated equipment; spray gun cleaning equipment; and equipment used for storage, handling, recovery, or recycling of cleaning solvent or waste paint. Paint stripping was not proposed as a business activity.

In accordance with §63.11171(c), this automotive coating operation is an existing source because it commenced construction prior to September 17, 2007, by installing new paint stripping or surface coating equipment, and the new surface coating equipment will be used at a source that was actively engaged in paint stripping and/or miscellaneous surface coating prior to September 17, 2007.

§ 63.11172 When do I have to comply with this subpart?

In accordance with §63.11172(a)(2), because the initial startup of the facility occurred prior to January 9, 2008, the compliance date is January 10, 2011.

§ 63.11173 What are my general requirements for complying with this subpart?

Because the facility has not proposed paint-stripping activities, the requirements of §63.11173(a) through (f) are not applicable. Because the facility is an automotive coating operation, in accordance with §63.11173(e), the permittee must meet the requirements of in paragraphs (e)(1) through (e)(5) of this section.

In accordance with §63.11173(f), each owner or operator of an affected automotive coating operation must ensure and certify that all new and existing personnel, including contract personnel, who spray apply surface coatings, as defined in §63.11180, are trained in the proper application of surface coatings as required by paragraph (e)(1) of this section. The training program must include, at a minimum, the items listed in paragraphs (f)(1) through (f)(3) of this section.

In accordance with §63.11173(g), as required by paragraph (e)(1) of this section, all new and existing personnel at an affected motor vehicle and mobile equipment or miscellaneous surface coating source, including contract personnel, who spray apply surface coatings, as defined in §63.11180, must be trained by the dates specified in paragraphs (g)(1) and (2) of this section. Employees who transfer within a company to a position as a painter are subject to the same requirements as a new hire.

Compliance with these requirements is assured by permit condition 19.

§ 63.11174 What parts of the General Provisions apply to me?

In accordance with §63.11174(a), Table 1 of this subpart shows which parts of the General Provisions in subpart A apply. Compliance with these requirements is assured by permit condition 18.

In accordance with §63.11174(b), an owner or operator of an area source subject to this subpart is exempt from the obligation to obtain a permit under 40 CFR part 70 or 71 provided that a permit under 40 CFR 70.3(a) or 71.3(a) is not required for a reason other than becoming area source subject to this subpart. This permit application and permitting action involve a Permit to Construct, and will not utilize the requirements and procedures in IDAPA 58.01.01.300-399 for the issuance of Tier I operating permits.

§ 63.11175 What notifications must I submit?

In accordance with §63.11175(a), because the facility is a surface coating operation subject to this subpart, the initial notification required by §63.9(b) must be submitted. For this existing operation, the Initial Notification must be submitted no later than on or before March 11, 2011.

In accordance with §63.11175(b), because the facility is an existing source, the permittee is not required to submit a separate notification of compliance status in addition to the initial notification specified in paragraph (a) of this subpart provided the permittee was able to certify compliance on the date of the initial notification, as part of the initial notification, and the permittee's compliance status has not since changed. The permittee must submit a Notification of Compliance Status on or before March 11, 2011. The permittee is required to submit the information specified in paragraphs (b)(1) through (4) of this section with the Notification of Compliance Status.

Compliance with these requirements is assured by permit condition 20.

§ 63.11176 What reports must I submit?

In accordance with §63.11176(a), because the permittee is an owner or operator of a paint stripping, motor vehicle or mobile equipment, or miscellaneous surface coating affected source, the permittee is required to submit a report in each calendar year in which information previously submitted in either the initial notification required by §63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted under this paragraph, has changed. Deviations from the relevant requirements in §63.11173(a) through (d) or §63.11173(e) through (g) on the date of the report will be deemed to be a change. The annual notification of changes report must be submitted prior to March 1 of each calendar year when reportable changes have occurred and must include the information specified in paragraphs (a)(1) through (2) of this section.

Compliance with these requirements is assured by permit condition 21.

Because the facility has not proposed to conduct paint stripping operations, the MeCl minimization plan requirements are not applicable (see permit condition 10).

§ 63.11177 What records must I keep?

In accordance with §63.11177, because the permittee is the owner or operator of a surface coating operation, the permittee must keep the records specified in paragraphs (a) through (d) and (g) of this section. Because the permittee has not proposed to conduct paint stripping operations, the requirements of paragraphs (e) and (f) of this section are not applicable. Compliance with these requirements is assured by permit condition 19.

§ 63.11178 In what form and for how long must I keep my records?

In accordance with 40 CFR 63.11178(a) because the permittee is the owner or operator of an affected source, the permittee must maintain copies of the records specified in §63.11177 for a period of at least five years after the date of each record. Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period. Compliance with these requirements is assured by permit condition 19.

§ 63.11179 Who implements and enforces this subpart?

In accordance with §63.11179(a), this subpart can be implemented and enforced by the U.S. Environmental Protection Agency (EPA), or a delegated authority. At the time of this permitting action, the EPA has not delegated authority to the State of Idaho. However, IDAPA 58.01.01.107.03.i incorporates by reference all Federal Clean Air Act requirements including 40 CFR 63, Subpart HHHHHH. Therefore, the requirements of this subpart have been placed in the permit.

§ 63.11180 What definitions do I need to know?

Terms used in this subpart are defined in accordance with §63.11180.

### *Permit Conditions Review*

This section describes the permit conditions for this initial permit or only those permit conditions that have been added, revised, modified or deleted as a result of this permitting action.

Permit condition 1 establishes the permit to construct scope.

Permit condition 4 provides a description of the purpose of the permit and the regulated sources, the process, and the control devices used at the facility.

Permit condition 5 provides a process description of the automotive coating operation at the facility.

Permit condition 6 provides a description of the control devices used for the automotive coating operation at the facility.

Permit condition 7 establishes hourly and annual emissions limits for $PM_{10}$ and VOC emissions from the automotive coating operation.

As mentioned previously, Permit Condition 8 establishes a 20% opacity limit for the paint booth stacks, vents, or functionally equivalent openings associated with the automotive coating operation.

As mentioned previously, Permit Condition 9 establishes that the permittee shall not allow, suffer, cause, or permit the emission of odorous gasses, liquids, or solids to the atmosphere in such quantities as to cause air pollution.

Permit condition 10 establishes that the facility will not use MeCl to remove paint from vehicles at the facility. This was done because MeCl was not proposed to be used at this facility by the Applicant and the emissions were not included in the DEQ Automotive Coating EI Spreadsheet (see the DEQ website). In addition, Subpart HHHHHH has additional requirements for facilities that use MeCl to remove paint as mentioned previously in the discussion of Subpart HHHHHH in the MACT Applicability Section.

Permit condition 11 establishes a daily use limit for all coating materials used in the automotive coating process as proposed by the Applicant. This limit was established because it was the easiest way for the Applicant to demonstrate compliance with the $PM_{10}$ and VOC emissions limit specified in permit condition 5 and the TAPs emissions limits specified in the DEQ Automotive Coating EI Spreadsheet (see the DEQ website).

Permit Condition 12 excludes bed liner component B coatings from each daily usage total. For those bed liner coatings analyzed, component B coatings did not contain substances which would result in emissions of regulated TAP. (Use of component B coatings did result in additional VOC emissions which were included in the emission inventories; see Appendix A.) Component A coatings (also referred to as the "iso" component) are counted toward the daily usage limit in Permit Condition 11 because these coatings contain isocyanates (including HDI and/or MDI) which result in the emissions of regulated TAP.

Permit condition 13 establishes that the permittee conduct all automotive coating operations in the paint booth or preparation station with the filters in place, exhaust fan(s) operating, and door(s) or curtain(s) closed, that the operation shall use a HVLP spray gun, and that the permittee shall maintain and operate the paint booth and preparation station exhaust filter system in accordance with the manufacturer's specifications. This condition also defines what a booth and preparation station used for applying coating is.

Permit condition 14 establishes that the permittee shall maintain records of all odor complaints received, perform appropriate corrective actions, and maintain records of corrective actions taken at the facility for the automotive coating process. This was required because automotive operation operations are expected to have odors that might be offensive to their immediate neighbors.

Permit condition 15 establishes that the permittee shall maintain material purchase records and Material Safety Data Sheets (MSDS) for the automotive coating process. This condition was placed in the permit to ensure compliance with the Coating Materials Use Limit Permit Condition.

Permit condition 16 establishes that the permittee shall maintain daily usage records of pre-treatment wash primer, primer, topcoat, clear coat, thinner/reducer, and undercoating, and isocyanate-containing bed liner component materials used for the automotive coating process. This condition was placed in the permit to ensure compliance with the Coating Materials Use Limit permit condition.

Permit condition 17 establishes that the permittee shall maintain records as required by the General Provision recordkeeping requirements.

Permit condition 18 establishes parameters that will allow the facility to comply with the general operating requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 19 establishes parameters that will allow the facility to comply with the monitoring and recordkeeping requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 20 establishes parameters that will allow the facility to comply with the initial notification and reporting requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 21 establishes parameters that will allow the facility to comply with the annual notification and reporting requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 22 establishes that the federal requirements of 40 CFR Part 63 are incorporated by reference into the requirements of this permit per current DEQ guidance.

Permit conditions 23 through 31 were taken from the previous operating permit for the abrasive blasting operation.

## PUBLIC REVIEW

### *Public Comment Opportunity*

An opportunity for public comment period on the application was provided in accordance with IDAPA 58.01.01.209.01.c or IDAPA 58.01.01.404.01.c. During this time, there were comments on the application and there was a request for a public comment period on DEQ's proposed action. Refer to the chronology for public comment opportunity dates.

### *Public Comment Period*

A public comment period was made available to the public in accordance with IDAPA 58.01.01.209.01.c. During this time, comments were not submitted in response to DEQ's proposed action. Refer to the chronology for public comment period dates.

# APPENDIX A – EMISSIONS INVENTORIES

Coating Operation Emissions Calculations:

A daily coatings material use limit needs to be established for Automotive Coating operations that demonstrates compliance with State Law. Specifically, compliance with IDAPA 58.01.01.585 and .586 for toxic air pollutants (TAPs) needs to be determined. Therefore, DEQ staff created the DEQ Automotive Coating EI spreadsheet (see the DEQ website). This spreadsheet contains paints from two different manufacturers of paints used in the automotive coating industry and multiple paint systems for each brand. The paint brands chosen were based upon discussions with a national paint distributor with several stores throughout the state of Idaho. The TAPs data entered in the spreadsheet was taken from the MSDSs for the paints listed. Included in the calculations was a safety factor of 19% since all paints available were not analyzed. With this safety factor it is reasonably presumed that the data represents all available automotive coatings. The spreadsheet was then used to demonstrate that with 4.0 gallons per day of coating use, the ELs listed in IDAPA 58.01.01.585 and .586 would not be exceeded for any of the coatings listed in the spreadsheet. The 4.0 gallons per day of coating was then used to determine worst-case $PM_{10}$ and VOC emissions from Automotive Coating operations (see the calculations as follows):

**Table A.1 POST PROJECT HOURLY AND ANNUAL $PM_{10}$ POTENTIAL TO EMIT FOR THE AUTOMOTIVE COATING OPERATION**

| Coating Material | Daily Coating Use[1] (gal/day) | Annual Coating Use[2] (gal/yr) | Density[3] (lb/gal) | Paint Spray Gun TE[4] (%) | Booth Particulate Filters CE[5] (%) | Hourly $PM_{10}$ Emissions (lb-$PM_{10}$/hr) | Annual $PM_{10}$ Emissions (T-$PM_{10}$/yr) |
|---|---|---|---|---|---|---|---|
| Pre-treatment wash primer, primer, topcoat, clear, reducer, and hardener combined | 8.0 | 2,920 | 16.76 | 65 | 98 | 0.04 | 0.171 |

[1] – Daily coating use was determined using the DEQ Automotive Coatings EI spreadsheet (see the DEQ website) and the allowance to use an additional 4.0 gal/day of "Component B" in the bed lining operation.
[2] – Annual coating use is assumed to be daily coating use multiplied by 365 days per year.
[3] – The density of the paint was assumed to be the highest available using the DEQ Automotive Coatings EI spreadsheet (DEQ assumption for worst-case emissions).
[4] – The permit requires a minimum paint gun transfer efficiency of 65%. Therefore, $PM_{10}$ emissions are based up this minimum transfer efficiency.
[5] – The permit requires a minimum $PM_{10}$ control efficiency of 98%. Therefore, $PM_{10}$ emissions are based up this minimum control efficiency.

**Table A.2 POST PROJECT HOURLY AND ANNUAL VOC POTENTIAL TO EMIT FOR THE AUTOMOTIVE COATING OPERATION**

| Coating Material | Daily Coating Use[1] (gal/day) | Annual Coating Use[2] (gal/yr) | VOC Content[3] (lb-VOC/gal) | Hourly VOC Emissions (lb-VOC/hr) | Annual VOC Emissions[3] (T-VOC/yr) |
|---|---|---|---|---|---|
| Pre-treatment wash primer, primer, topcoat, clear, reducer, and hardener combined | 8.0 | 2,920 | 16.76 | 5.59 | 24.47 |

[1] – Daily coating use was determined using the DEQ Automotive Coatings EI spreadsheet (see the DEQ website) and the allowance to use an additional 4.0 gal/day of "Component B" in the bed lining operation.
[2] – Annual coating use is assumed to be daily coating use multiplied by 365 days per year.
[3] – The VOC content of the paint is assumed to be 100% VOC (DEQ assumption for worst-case emissions).

Spray booth emissions of methylene diisocyanate (MDI) resulting from the application of the "iso" component coating during bed lining coating operations were estimated using the equation and assumptions from Section 19.0 of the MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry.[1] In this equation it was assumed that 100% of the "iso" component sprayed was MDI ($k_{MDI}$ = 1.0), that the combined spray and dry

[1] MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry, Alliance for the Polyurethanes Industry (API), 2004.

time to apply up to 4 gallons of MDI-based "iso" component was 4 hours or less per day, that "iso" spray coatings were applied 365 days per year, and that "iso" spray coatings were applied at less than 95°F. Although spray booth filtration is required, no additional removal or reduction of MDI emissions was assumed (0% control efficiency).

Uncontrolled emissions are based upon normal operation of the facility of 2,080 hrs/yr (8 hrs/day x 260 days/yr, normal business hours) with all coating operation occurring during this time. Since there is inherent prep time (the time spent preparing the automobile for the application of coating) and paint drying time (the time the automobile spends in the booth with the burner operating to facilitate hardening of the coating) this was considered to be the worst-case maximum for which emissions could occur.

Therefore, uncontrolled annual PM emissions are calculated using the annual PTE as calculated and backing out the 98% control efficiency of the filter system.

Uncontrolled annual $PM_{10}$ emissions from the coating operation are calculated as:

Uncontrolled Annual $PM_{10}$ emissions = $PM_{10}$ PTE (T-$PM_{10}$/yr) ÷ (1 – Filter CE)

Uncontrolled Annual $PM_{10}$ emissions = 0.171 T-$PM_{10}$/yr ÷ (1 – 0.98) = 8.55 T-$PM_{10}$/yr

Therefore, uncontrolled annual VOC emissions are calculated using the annual PTE as calculated.

Uncontrolled annual VOC emissions are equal to annual PTE as calculated.

Uncontrolled Annual VOC emissions = VOC PTE (T-VOC/yr)

Uncontrolled Annual VOC emissions = 24.47 T-VOC/yr

## Coating: Nason Primers, Primer Surfacers, and Sealers

**Content Weight %**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aromatic Hydrocarbon | Barium Sulfate | Butyl Acetate |
|---|---|---|---|---|---|---|---|---|
| 421-05 | | 49.01% | | | 1.00% | | | 1.00% |
| 421-08 | | 56.62% | | | | | | 1.00% |
| 421-09 | | 54.07% | | | 1.00% | | | 1.00% |
| 421-15 | | 52.89% | | | 1.00% | 1.00% | | 1.00% |
| 421-17 | | 62.36% | | | | | 1.00% | 1.00% |
| 421-18 | | 67.04% | | | 1.00% | | | |
| 421-19 | | 63.65% | | | | | 1.00% | 1.00% |
| 421-20 | | 61.62% | | | | | | 1.00% |
| 421-21 | | 51.56% | | | 1.00% | | 1.00% | 1.00% |
| 421-23 | | 58.92% | | | | | 1.00% | |
| 421-30 | | 64.77% | | | 1.00% | | | |
| 421-40 | | 53.78% | | | 1.00% | | | 1.00% |

**Content lb/gal**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aromatic Hydrocarbon | Barium Sulfate | Butyl Acetate |
|---|---|---|---|---|---|---|---|---|
| 421-05 | 9.52 | 4.67 | 0.74 | 0.38 | 0.10 | 0.00 | 0.00 | 0.10 |
| 421-08 | 10.28 | 5.82 | 0.82 | 0.82 | 0.00 | 0.00 | 0.00 | 0.10 |
| 421-09 | 9.94 | 5.37 | 0.99 | 0.89 | 0.10 | 0.00 | 0.00 | 0.10 |
| 421-15 | 9.94 | 5.26 | 0.55 | 0.20 | 0.10 | 0.10 | 0.00 | 0.10 |
| 421-17 | 11.88 | 7.41 | 3.43 | 2.49 | 0.00 | 0.00 | 0.12 | 0.12 |
| 421-18 | 13.83 | 9.27 | 1.22 | 0.97 | 0.14 | 0.00 | 0.00 | 0.00 |
| 421-19 | 12.08 | 7.69 | 2.54 | 2.54 | 0.00 | 0.00 | 0.12 | 0.12 |
| 421-20 | 11.62 | 7.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.12 |
| 421-21 | 12.32 | 6.35 | 0.00 | 0.00 | 0.12 | 0.00 | 0.12 | 0.12 |
| 421-23 | 11.15 | 6.57 | 3.20 | 1.78 | 0.00 | 0.00 | 0.11 | 0.00 |
| 421-30 | 10.91 | 7.07 | 0.15 | 0.11 | 0.11 | 0.00 | 0.00 | 0.00 |
| 421-40 | 10.24 | 5.51 | 3.07 | 2.87 | 0.10 | 0.00 | 0.00 | 0.10 |
| **Maximum (lb/gal)** | **13.83** | **9.27** | **3.43** | **2.87** | **0.14** | **0.10** | **0.12** | **0.12** |
| **Emission Rate (lb/hr)** | | **1.3E-02** | **6.9E-01** | **5.7E-01** | **2.8E-02** | **2.0E-02** | **2.5E-02** | **2.5E-02** |

# Coating: Nason Primers, Primer Surfacers, and Sealers

| | | |
|---|---|---|
| **IDAPA TAP EL (lb/hr)** | 1.19E+02 | 4.73E+01 |
| **Below EL?** | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Primers, Primer Surfacers, and Sealers

**Content Weight %**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | n-Butyl Alcohol | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate |
|---|---|---|---|---|---|---|---|---|
| 421-05 | | 49.01% | | | 5.00% | 1.00% | 0.80% | |
| 421-08 | | 56.62% | | | | 0.60% | | |
| 421-09 | | 54.07% | | | | 0.50% | | |
| 421-15 | | 52.89% | | | | 0.30% | 0.50% | 1.00% |
| 421-17 | | 62.36% | | | | | 5.90% | |
| 421-18 | | 67.04% | | | | | 1.80% | |
| 421-19 | | 63.65% | | | | | | |
| 421-20 | | 61.62% | | | | 0.20% | | |
| 421-21 | | 51.56% | | | | 0.20% | | |
| 421-23 | | 58.92% | | | | 0.20% | 2.70% | |
| 421-30 | | 64.77% | | | 2.00% | 0.20% | 0.40% | 1.00% |
| 421-40 | | 53.78% | | | | | | |

**Content lb/gal**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | n-Butyl Alcohol | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate |
|---|---|---|---|---|---|---|---|---|
| 421-05 | 9.52 | 4.67 | 0.74 | 0.38 | 0.48 | 0.10 | 0.08 | 0.00 |
| 421-08 | 10.28 | 5.82 | 0.82 | 0.82 | 0.00 | 0.06 | 0.00 | 0.00 |
| 421-09 | 9.94 | 5.37 | 0.99 | 0.89 | 0.00 | 0.05 | 0.00 | 0.00 |
| 421-15 | 9.94 | 5.26 | 0.55 | 0.20 | 0.00 | 0.03 | 0.05 | 0.10 |
| 421-17 | 11.88 | 7.41 | 3.43 | 2.49 | 0.00 | 0.00 | 0.70 | 0.00 |
| 421-18 | 13.83 | 9.27 | 1.22 | 0.97 | 0.00 | 0.00 | 0.25 | 0.00 |
| 421-19 | 12.08 | 7.69 | 2.54 | 2.54 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-20 | 11.62 | 7.16 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 |
| 421-21 | 12.32 | 6.35 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 |
| 421-23 | 11.15 | 6.57 | 3.20 | 1.78 | 0.00 | 0.02 | 0.30 | 0.00 |
| 421-30 | 10.91 | 7.07 | 0.15 | 0.11 | 0.22 | 0.02 | 0.04 | 0.11 |
| 421-40 | 10.24 | 5.51 | 3.07 | 2.87 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **13.83** | **9.27** | **3.43** | **2.87** | **0.48** | **0.10** | **0.70** | **0.11** |
| **Emission Rate (lb/hr)** | | **1.3E-02** | **6.9E-01** | **5.7E-01** | **9.5E-02** | **1.3E-04** | **1.4E-01** | **2.2E-02** |

# Coating: Nason Primers, Primer Surfacers, and Sealers

| | | | |
|---|---|---|---|
| **IDAPA TAP EL (lb/hr)** | 1.00E+01 | 2.3E-01 | 2.90E+01 |
| **Below EL?** | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Primers, Primer Surfacers, and Sealers

**Content Weight %**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Ethyl Alcohol | Ethylene Glycol Monobutyl Ether | Heptane | Isopropyl Alcohol (IPA) |
|---|---|---|---|---|---|---|---|---|
| 421-05 | | 49.01% | | | 1.00% | | | |
| 421-08 | | 56.62% | | | | | | |
| 421-09 | | 54.07% | | | | | | 1.00% |
| 421-15 | | 52.89% | | | | | 1.00% | |
| 421-17 | | 62.36% | | | | | | |
| 421-18 | | 67.04% | | | | | | |
| 421-19 | | 63.65% | | | | 6.00% | | |
| 421-20 | | 61.62% | | | | | | |
| 421-21 | | 51.56% | | | | | | |
| 421-23 | | 58.92% | | | | | | 1.00% |
| 421-30 | | 64.77% | | | | | | 1.00% |
| 421-40 | | 53.78% | | | | | | |

**Content lb/gal**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Ethyl Alcohol | Ethylene Glycol Monobutyl Ether | Heptane | Isopropyl Alcohol (IPA) |
|---|---|---|---|---|---|---|---|---|
| 421-05 | 9.52 | 4.67 | 0.74 | 0.38 | 0.10 | 0.00 | 0.00 | 0.00 |
| 421-08 | 10.28 | 5.82 | 0.82 | 0.82 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-09 | 9.94 | 5.37 | 0.99 | 0.89 | 0.00 | 0.00 | 0.00 | 0.10 |
| 421-15 | 9.94 | 5.26 | 0.55 | 0.20 | 0.00 | 0.00 | 0.10 | 0.00 |
| 421-17 | 11.88 | 7.41 | 3.43 | 2.49 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-18 | 13.83 | 9.27 | 1.22 | 0.97 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-19 | 12.08 | 7.69 | 2.54 | 2.54 | 0.00 | 0.72 | 0.00 | 0.00 |
| 421-20 | 11.62 | 7.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-21 | 12.32 | 6.35 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-23 | 11.15 | 6.57 | 3.20 | 1.78 | 0.00 | 0.00 | 0.00 | 0.11 |
| 421-30 | 10.91 | 7.07 | 0.15 | 0.11 | 0.00 | 0.00 | 0.00 | 0.11 |
| 421-40 | 10.24 | 5.51 | 3.07 | 2.87 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **13.83** | **9.27** | **3.43** | **2.87** | **0.10** | **0.72** | **0.10** | **0.11** |
| **Emission Rate (lb/hr)** | | **1.3E-02** | **6.9E-01** | **5.7E-01** | **1.9E-02** | **1.4E-01** | **2.0E-02** | **2.2E-02** |

# Coating: Nason Primers, Primer Surfacers, and Sealers

| | | | |
|---|---|---|---|
| **IDAPA TAP EL (lb/hr)** | 1.25E+02 | 1.09E+02 | 6.53E+01 |
| **Below EL?** | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Primers, Primer Surfacers, and Sealers

**Content Weight %**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isobutyl Ketone (MIBK)(HAP) | Phosphoric Acid Aluminum Salt (particulate) |
|---|---|---|---|---|---|---|---|---|
| 421-05 | | 49.01% | | | | | | |
| 421-08 | | 56.62% | | | | | | |
| 421-09 | | 54.07% | | | | 1.00% | | |
| 421-15 | | 52.89% | | | | 1.00% | | |
| 421-17 | | 62.36% | | | | | | |
| 421-18 | | 67.04% | | | | | | 1.00% |
| 421-19 | | 63.65% | | | 1.00% | | | |
| 421-20 | | 61.62% | | | | | | |
| 421-21 | | 51.56% | | | 1.00% | | | |
| 421-23 | | 58.92% | | | | | | |
| 421-30 | | 64.77% | | | | | | |
| 421-40 | | 53.78% | | | | 1.00% | 1.00% | |

**Content lb/gal**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isobutyl Ketone (MIBK)(HAP) | Phosphoric Acid Aluminum Salt (particulate) |
|---|---|---|---|---|---|---|---|---|
| 421-05 | 9.52 | 4.67 | 0.74 | 0.38 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-08 | 10.28 | 5.82 | 0.82 | 0.82 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-09 | 9.94 | 5.37 | 0.99 | 0.89 | 0.00 | 0.10 | 0.00 | 0.00 |
| 421-15 | 9.94 | 5.26 | 0.55 | 0.20 | 0.00 | 0.10 | 0.00 | 0.00 |
| 421-17 | 11.88 | 7.41 | 3.43 | 2.49 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-18 | 13.83 | 9.27 | 1.22 | 0.97 | 0.00 | 0.00 | 0.00 | 0.14 |
| 421-19 | 12.08 | 7.69 | 2.54 | 2.54 | 0.12 | 0.00 | 0.00 | 0.00 |
| 421-20 | 11.62 | 7.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-21 | 12.32 | 6.35 | 0.00 | 0.00 | 0.12 | 0.00 | 0.00 | 0.00 |
| 421-23 | 11.15 | 6.57 | 3.20 | 1.78 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-30 | 10.91 | 7.07 | 0.15 | 0.11 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-40 | 10.24 | 5.51 | 3.07 | 2.87 | 0.00 | 0.10 | 0.10 | 0.00 |
| **Maximum (lb/gal)** | **13.83** | **9.27** | **3.43** | **2.87** | **0.12** | **0.10** | **0.10** | **0.14** |
| **Emission Rate (lb/hr)** | | **1.3E-02** | **6.9E-01** | **5.7E-01** | **2.5E-02** | **2.0E-02** | **2.0E-02** | **1.9E-04** |

## Coating: Nason Primers, Primer Surfacers, and Sealers

| | | | | |
|---|---|---|---|---|
| **IDAPA TAP EL (lb/hr)** | 1.57E+01 | 3.93E+01 | 1.37E+01 | 6.70E-02 |
| **Below EL?** | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Primers, Primer Surfacers, and Sealers

**Content Weight %**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Silicon Dioxide (particulate) | Styrene (HAP) | Toluene (HAP) | VM&P Naphtha |
|---|---|---|---|---|---|---|---|---|
| 421-05 | | 49.01% | | | 1.00% | | 4.00% | |
| 421-08 | | 56.62% | | | | | 8.00% | |
| 421-09 | | 54.07% | | | | | 9.00% | |
| 421-15 | | 52.89% | | | 6.50% | | 2.00% | |
| 421-17 | | 62.36% | | | | | 2.00% | |
| 421-18 | | 67.04% | | | 0.20% | | | |
| 421-19 | | 63.65% | | | | | | |
| 421-20 | | 61.62% | | | 0.30% | | | |
| 421-21 | | 51.56% | | | 0.10% | | | |
| 421-23 | | 58.92% | | | | | 16.00% | |
| 421-30 | | 64.77% | | | | | | |
| 421-40 | | 53.78% | | | | 28.00% | | 1.00% |

**Content lb/gal**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Silicon Dioxide (particulate) | Styrene (HAP) | Toluene (HAP) | VM&P Naphtha |
|---|---|---|---|---|---|---|---|---|
| 421-05 | 9.52 | 4.67 | 0.74 | 0.38 | 0.10 | 0.00 | 0.38 | 0.00 |
| 421-08 | 10.28 | 5.82 | 0.82 | 0.82 | 0.00 | 0.00 | 0.82 | 0.00 |
| 421-09 | 9.94 | 5.37 | 0.99 | 0.89 | 0.00 | 0.00 | 0.89 | 0.00 |
| 421-15 | 9.94 | 5.26 | 0.55 | 0.20 | 0.65 | 0.00 | 0.20 | 0.00 |
| 421-17 | 11.88 | 7.41 | 3.43 | 2.49 | 0.00 | 0.00 | 0.24 | 0.00 |
| 421-18 | 13.83 | 9.27 | 1.22 | 0.97 | 0.03 | 0.00 | 0.00 | 0.00 |
| 421-19 | 12.08 | 7.69 | 2.54 | 2.54 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-20 | 11.62 | 7.16 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 |
| 421-21 | 12.32 | 6.35 | 0.00 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 |
| 421-23 | 11.15 | 6.57 | 3.20 | 1.78 | 0.00 | 0.00 | 1.78 | 0.00 |
| 421-30 | 10.91 | 7.07 | 0.15 | 0.11 | 0.00 | 0.00 | 0.00 | 0.00 |
| 421-40 | 10.24 | 5.51 | 3.07 | 2.87 | 0.00 | 2.87 | 0.00 | 0.10 |
| **Maximum (lb/gal)** | **13.83** | **9.27** | **3.43** | **2.87** | **0.65** | **2.87** | **1.78** | **0.10** |
| **Emission Rate (lb/hr)** | | **1.3E-02** | **6.9E-01** | **5.7E-01** | **9.0E-04** | **5.7E-01** | **3.6E-01** | **2.0E-02** |

## Coating: Nason Primers, Primer Surfacers, and Sealers

| | | | | |
|---|---|---|---|---|
| **IDAPA TAP EL (lb/hr)** | 6.70E-03 | 6.67E+00 | 2.50E+01 | 9.13E+01 |
| **Below EL?** | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

# Coating: Nason Primers, Primer Surfacers, and Sealers

**Content Weight %**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Xylene (HAP) |
|---|---|---|---|---|---|
| 421-05 | | 49.01% | | | 3.00% |
| 421-08 | | 56.62% | | | |
| 421-09 | | 54.07% | | | |
| 421-15 | | 52.89% | | | 2.00% |
| 421-17 | | 62.36% | | | 21.00% |
| 421-18 | | 67.04% | | | 7.00% |
| 421-19 | | 63.65% | | | 21.00% |
| 421-20 | | 61.62% | | | |
| 421-21 | | 51.56% | | | |
| 421-23 | | 58.92% | | | 10.00% |
| 421-30 | | 64.77% | | | 1.00% |
| 421-40 | | 53.78% | | | |

**Content lb/gal**

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Xylene (HAP) |
|---|---|---|---|---|---|
| 421-05 | 9.52 | 4.67 | 0.74 | 0.38 | 0.29 |
| 421-08 | 10.28 | 5.82 | 0.82 | 0.82 | 0.00 |
| 421-09 | 9.94 | 5.37 | 0.99 | 0.89 | 0.00 |
| 421-15 | 9.94 | 5.26 | 0.55 | 0.20 | 0.20 |
| 421-17 | 11.88 | 7.41 | 3.43 | 2.49 | 2.49 |
| 421-18 | 13.83 | 9.27 | 1.22 | 0.97 | 0.97 |
| 421-19 | 12.08 | 7.69 | 2.54 | 2.54 | 2.54 |
| 421-20 | 11.62 | 7.16 | 0.00 | 0.00 | 0.00 |
| 421-21 | 12.32 | 6.35 | 0.00 | 0.00 | 0.00 |
| 421-23 | 11.15 | 6.57 | 3.20 | 1.78 | 1.12 |
| 421-30 | 10.91 | 7.07 | 0.15 | 0.11 | 0.11 |
| 421-40 | 10.24 | 5.51 | 3.07 | 2.87 | 0.00 |
| **Maximum (lb/gal)** | **13.83** | **9.27** | **3.43** | **2.87** | **2.54** |
| **Emission Rate (lb/hr)** | | **1.3E-02** | **6.9E-01** | **5.7E-01** | **5.1E-01** |

# Coating: Nason Primers, Primer Surfacers, and Sealers

**IDAPA TAP EL (lb/hr)** 2.90E+01

**Below EL?** Yes

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Factory Packaged Colors

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aromatic Hydrocarbon | Barium Sulfate | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Proplonate | Ethylene Glycol Monobutyl Ether | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isobutyl Ketone (MIBK)(HAP) | Naphthalene (HAP) | Silica Silicon Dioxide (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 422-23 | | 33.61% | | | 1.00% | 1.00% | | 1.00% | 0.60% | 0.80% | 1.00% | | 1.00% | | | | 2.30% | | 3.00% | | 3.00% |
| 422-28 | | 72.31% | | | 1.00% | 1.00% | | | 2.20% | 0.30% | | | 1.00% | | 9.00% | 0.30% | | | 1.00% | | 1.00% |
| 422-33 | | 76.92% | | | | | | | 2.10% | 1.00% | | | | | 12.00% | | | | | | 4.00% |
| 422-46 | | 64.87% | | | | | | 1.00% | 1.40% | 0.40% | | 1.00% | | | | | | 1.00% | 4.00% | 1.00% | 1.00% |
| 422-48 | | 61.17% | | | | | 1.00% | 1.00% | | 5.10% | | | 1.00% | 1.00% | | | | | 1.00% | | 18.00% |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aromatic Hydrocarbon | Barium Sulfate | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Proplonate | Ethylene Glycol Monobutyl Ether | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isobutyl Ketone (MIBK)(HAP) | Naphthalene (HAP) | Silica Silicon Dioxide (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 422-23 | 8.24 | 2.77 | 0.56 | 0.25 | 0.08 | 0.08 | 0.00 | 0.08 | 0.05 | 0.07 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.19 | 0.00 | 0.25 | 0.00 | 0.25 |
| 422-28 | 10.57 | 7.64 | 1.23 | 0.95 | 0.11 | 0.11 | 0.00 | 0.00 | 0.23 | 0.03 | 0.00 | 0.00 | 0.11 | 0.00 | 0.95 | 0.03 | 0.00 | 0.00 | 0.11 | 0.00 | 0.11 |
| 422-33 | 11.47 | 8.82 | 1.95 | 1.38 | 0.00 | 0.00 | 0.00 | 0.00 | 0.24 | 0.11 | 0.00 | 0.00 | 0.00 | 0.00 | 1.38 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.46 |
| 422-46 | 10.30 | 6.68 | 0.56 | 0.41 | 0.00 | 0.00 | 0.00 | 0.10 | 0.14 | 0.04 | 0.00 | 0.10 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 | 0.41 | 0.10 | 0.10 |
| 422-48 | 10.82 | 6.62 | 2.72 | 1.95 | 0.00 | 0.00 | 0.11 | 0.11 | 0.00 | 0.55 | 0.00 | 0.00 | 0.11 | 0.11 | 0.00 | 0.00 | 0.00 | 0.00 | 0.11 | 0.00 | 1.95 |
| **Maximum (lb/gal)** | **11.47** | **8.82** | **2.72** | **1.95** | **0.11** | **0.11** | **0.11** | **0.11** | **0.24** | **0.55** | **0.08** | **0.10** | **0.11** | **0.11** | **1.38** | **0.03** | **0.19** | **0.10** | **0.41** | **0.10** | **1.95** |
| **Emission Rate (lb/hr)** | | **1.2E-02** | **5.4E-01** | **3.9E-01** | **2.1E-02** | **2.1E-02** | **2.2E-02** | **2.2E-02** | **3.4E-04** | **1.1E-01** | **1.6E-02** | **2.1E-02** | **2.2E-02** | **2.2E-02** | **2.8E-01** | **6.3E-03** | **2.7E-04** | **2.1E-02** | **8.2E-02** | **2.1E-02** | **3.9E-01** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | | | 4.73E+01 | 2.3E-01 | 2.90E+01 | | | 1.57E+01 | 3.93E+01 | 1.37E+01 | 3.33E+00 | 6.70E-03 | 3.50E+01 | 2.50E+01 | 9.13E+01 | 2.90E+01 |
| Below EL? | | | | | Yes | | | Yes | Yes | Yes | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Tints, Toners, and Binders

Content
Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Aromatic Hydrocarbon | Barium Sulfate | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethylene Glycol Monobutyl Ether | Heptane | Naphthalene (HAP) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 430-01 | | 44.25% | | | 1.00% | | 1.00% | 6.60% | 0.60% | | | | 0.40% | | 4.00% | | 1.00% | 2.00% |
| 430-02 | | 40.95% | | | 1.00% | | 1.00% | 1.30% | 0.50% | | | 1.00% | 0.50% | | 5.00% | | 1.00% | 2.00% |
| 430-03 | | 74.89% | | | | | 1.00% | | 0.70% | | | | | | | | | 2.00% |
| 430-04 | | 60.77% | | | | | 1.00% | | 0.60% | | | 1.00% | | | 2.00% | | 1% | 2.00% |
| 430-05 | | 46.64% | | | 1.00% | | 1.00% | | 5.80% | | | 1.00% | 0.40% | | 3.00% | | 1% | 21.00% |
| 430-06 | | 44.34% | | | 1.00% | | 1.00% | | 3.30% | | | 1.00% | 0.40% | | 4.00% | | 1% | 12.00% |
| 430-07 | | 51.19% | | | 1.00% | | 1.00% | | 1.10% | | | | 0.20% | | | | 1% | 4.00% |
| 430-08 | | 49.09% | | | 1.00% | | 1.00% | | 1.40% | | | 1.00% | 0.40% | | 5.00% | | 1% | 5.00% |
| 430-09 | | 51.31% | | | | | 1.00% | | 4.90% | | | | | | | | 1% | 18.00% |
| 430-10 | | 49.80% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-11 | | 43.37% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-12 | | 52.71% | | | 1.00% | | 1.00% | | 0.60% | | | | 0.30% | | | | 1% | 2.00% |
| 430-13 | | 46.56% | | | 1.00% | | 1.00% | | 0.60% | | | 1.00% | 0.30% | | 4.00% | | 1% | 2.00% |
| 430-14 | | 40.53% | | | 1.00% | | 1.00% | | 0.60% | | | 1.00% | 0.40% | | 5.00% | | 1% | 2.00% |
| 430-15 | | 42.39% | | | 1.00% | | 1.00% | | 0.70% | | | 1.00% | 0.50% | | 5.00% | | 1% | 3.00% |
| 430-16 | | 48.65% | | | 1.00% | | 1.00% | | 0.70% | | | 1.00% | 0.40% | | 4.00% | | 1% | 2.00% |
| 430-17 | | 50.93% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.30% | | | | 1% | 2.00% |
| 430-18 | | 53.26% | | | 1.00% | | 1.00% | | 0.60% | | | | 0.30% | | | | 1% | 2.00% |
| 430-19 | | 54.70% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.30% | | 2.00% | | 1% | 2.00% |
| 430-20 | | 51.75% | | | 1.00% | | 1.00% | | 0.60% | | | 1.00% | 0.30% | | 2.00% | | 1% | 2.00% |
| 430-21 | | 44.90% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-22 | | 51.24% | | | 1.00% | 1.00% | 1.00% | | 0.60% | | | | 0.30% | | 2.00% | | 1% | 2.00% |
| 430-23 | | 50.94% | | | 1.00% | 1.00% | 1.00% | | 0.70% | | | 1.00% | 0.40% | | 4.00% | | 1% | 3.00% |
| 430-24 | | 51.17% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.20% | | | | 1% | 2.00% |
| 430-25 | | 48.38% | | | 1.00% | | 1.00% | | 0.60% | | | 1.00% | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-26 | | 56.66% | | | | | 1.00% | | 0.50% | | | | | | | | 1% | 2.00% |
| 430-27 | | 53.83% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-28 | | 53.31% | | | 1.00% | | 1.00% | | 0.50% | | 2.00% | | | | 5.00% | | 1% | 2.00% |
| 430-29 | | 53.11% | | | 1.00% | | 1.00% | | 0.50% | | 0.20% | | 0.20% | | 5.00% | | 1% | 2.00% |
| 430-30 | | 43.95% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | | 1.00% | 4.00% | | 1% | 2.00% |
| 430-31 | | 44.96% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | | 1.00% | 4.00% | | 1% | 2.00% |
| 430-32 | | 45.72% | | | | | 1.00% | | 0.40% | | | 1.00% | | | 3.00% | | 1% | 2.00% |
| 430-33 | | 46.88% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | | | 4.00% | | 1% | 2.00% |
| 430-34 | | 45.57% | | | 1.00% | | 1.00% | | 1.00% | | | 1.00% | | | 4.00% | 1.00% | 1% | 4.00% |
| 430-35 | | 47.16% | | | | | 1.00% | | 1.00% | | | 1.00% | | | 4.00% | | 1% | 4.00% |
| 430-36 | | 52.81% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-37 | | 46.95% | | | 1.00% | | 1.00% | | 0.60% | | | 1.00% | 0.30% | | 4.00% | | 1% | 2.00% |
| 430-38 | | 45.07% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-39 | | 41.25% | | | 1.00% | | 1.00% | | 0.50% | | | 1.00% | 0.20% | | 1.00% | | 1% | 2.00% |
| 430-40 | | 40.98% | | | 1.00% | | 1.00% | | 0.40% | 1.00% | | 1.00% | 0.20% | | 7.00% | | 1% | 2.00% |
| 430-41 | | 47.84% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.20% | | | | 1% | 2.00% |
| 430-42 | | 50.12% | | | 1.00% | | 1.00% | | 1.20% | | | | 0.40% | | | | 1% | 4.00% |
| 430-43 | | 42.85% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.40% | | 2.00% | | 1% | 2.00% |
| 430-44 | | 45.36% | | | 1.00% | | 1.00% | | 0.50% | | | | 0.40% | | 3.00% | | 1% | 2.00% |
| 430-45 | | 46.84% | | | | 1.00% | 1.00% | | 0.30% | | | | | | | | 1% | 1.00% |
| 430-46 | | 48.85% | | | 1.00% | | 1.00% | | 1.30% | | | | 0.40% | | 3.00% | | 1% | 5.00% |
| 430-47 | | 49.62% | | | 1.00% | | 1.00% | | 0.40% | | 1.00% | | 0.30% | | 7.00% | | 1% | 2.00% |
| 430-48 | | 45.30% | | | | | 1.00% | | 1.00% | | | 1.00% | | 1.00% | 4.00% | | 1% | 4.00% |
| 430-49 | | 44.68% | | | | | 1.00% | | 0.50% | | | 1.00% | | 1.00% | 3.00% | | 1% | 2.00% |
| 430-50 | | 56.01% | | | 1.00% | | 1.00% | | 0.50% | | 2.00% | 1.00% | 0.20% | 1.00% | 6.00% | | 1% | 2.00% |
| 430-51 | | 51.59% | | | 1.00% | | 1.00% | | 0.40% | | 1.00% | | 0.30% | | 8.00% | | 1% | 2.00% |
| 430-52 | | 34.84% | | | | | 1.00% | | 7.90% | | | | | | | | 1% | 28.00% |
| 430-53 | | 55.78% | | | | | 1.00% | | 0.80% | | | | | | | | 1% | 3.00% |
| 430-54 | | 54.11% | | | 1.00% | | 1.00% | | 0.50% | | 2.00% | | 0.20% | | | | 1% | 2.00% |
| 430-55 | | 47.70% | | | 1.00% | | 1.00% | | 0.80% | | | 1.00% | | | 3.00% | | 1% | 3.00% |
| 430-56 | | 52.74% | | | 1.00% | | 1.00% | | 0.60% | | | | 0.30% | | | | 1% | 2.00% |

## Coating: Nason Tints, Toners, and Binders

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Aromatic Hydrocarbon | Barium Sulfate | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethylene Glycol Monobutyl Ether | Heptane | Naphthalene (HAP) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 430-01 | 8.14 | 3.60 | 0.57 | 0.33 | 0.08 | 0.00 | 0.08 | 0.54 | 0.05 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.33 | 0.00 | 0.08 | 0.16 |
| 430-02 | 7.94 | 3.25 | 0.64 | 0.40 | 0.08 | 0.00 | 0.08 | 0.10 | 0.04 | 0.00 | 0.00 | 0.08 | 0.04 | 0.00 | 0.40 | 0.00 | 0.08 | 0.16 |
| 430-03 | 13.30 | 9.96 | 0.36 | 0.27 | 0.00 | 0.00 | 0.13 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.27 |
| 430-04 | 10.47 | 6.36 | 0.48 | 0.21 | 0.00 | 0.00 | 0.10 | 0.00 | 0.06 | 0.00 | 0.00 | 0.10 | 0.00 | 0.00 | 0.21 | 0.00 | 0.10 | 0.21 |
| 430-05 | 8.85 | 4.30 | 2.67 | 1.86 | 0.09 | 0.00 | 0.09 | 0.00 | 0.51 | 0.00 | 0.00 | 0.09 | 0.04 | 0.00 | 0.27 | 0.00 | 0.09 | 1.86 |
| 430-06 | 8.35 | 3.70 | 1.64 | 1.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.28 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.33 | 0.00 | 0.08 | 1.00 |
| 430-07 | 9.10 | 4.66 | 0.48 | 0.36 | 0.09 | 0.00 | 0.09 | 0.00 | 0.10 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 | 0.00 | 0.09 | 0.36 |
| 430-08 | 8.81 | 4.32 | 1.04 | 0.44 | 0.09 | 0.00 | 0.09 | 0.00 | 0.12 | 0.00 | 0.00 | 0.09 | 0.04 | 0.00 | 0.44 | 0.00 | 0.09 | 0.44 |
| 430-09 | 9.20 | 4.72 | 2.11 | 1.66 | 0.00 | 0.00 | 0.09 | 0.00 | 0.45 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 1.66 |
| 430-10 | 8.43 | 4.20 | 0.41 | 0.17 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.17 | 0.00 | 0.08 | 0.17 |
| 430-11 | 8.19 | 3.55 | 0.40 | 0.16 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.16 | 0.00 | 0.08 | 0.16 |
| 430-12 | 8.50 | 4.48 | 0.25 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.09 | 0.17 |
| 430-13 | 8.30 | 3.86 | 0.57 | 0.33 | 0.08 | 0.00 | 0.08 | 0.00 | 0.05 | 0.00 | 0.00 | 0.08 | 0.02 | 0.00 | 0.33 | 0.00 | 0.08 | 0.17 |
| 430-14 | 7.95 | 3.22 | 0.64 | 0.40 | 0.08 | 0.00 | 0.08 | 0.00 | 0.05 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.40 | 0.00 | 0.08 | 0.16 |
| 430-15 | 7.97 | 3.38 | 0.73 | 0.40 | 0.08 | 0.00 | 0.08 | 0.00 | 0.06 | 0.00 | 0.00 | 0.08 | 0.04 | 0.00 | 0.40 | 0.00 | 0.08 | 0.24 |
| 430-16 | 8.66 | 4.21 | 0.81 | 0.35 | 0.09 | 0.00 | 0.09 | 0.00 | 0.06 | 0.00 | 0.00 | 0.09 | 0.03 | 0.00 | 0.35 | 0.00 | 0.09 | 0.17 |
| 430-17 | 8.62 | 4.39 | 0.24 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.09 | 0.17 |
| 430-18 | 8.60 | 4.58 | 0.25 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.09 | 0.17 |
| 430-19 | 8.65 | 4.73 | 0.42 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.17 | 0.00 | 0.09 | 0.17 |
| 430-20 | 8.55 | 4.42 | 0.42 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.00 | 0.09 | 0.03 | 0.00 | 0.17 | 0.00 | 0.09 | 0.17 |
| 430-21 | 8.16 | 3.66 | 0.40 | 0.16 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.16 | 0.00 | 0.08 | 0.16 |
| 430-22 | 8.54 | 4.38 | 0.42 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.17 | 0.00 | 0.09 | 0.17 |
| 430-23 | 8.48 | 4.32 | 0.69 | 0.34 | 0.08 | 0.08 | 0.08 | 0.00 | 0.06 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.34 | 0.00 | 0.08 | 0.25 |
| 430-24 | 8.44 | 4.32 | 0.23 | 0.17 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 | 0.00 | 0.08 | 0.17 |
| 430-25 | 8.35 | 4.04 | 0.42 | 0.17 | 0.08 | 0.00 | 0.08 | 0.00 | 0.05 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.17 | 0.00 | 0.08 | 0.17 |
| 430-26 | 8.62 | 5.00 | 0.22 | 0.18 | 0.00 | 0.00 | 0.09 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.18 |
| 430-27 | 8.78 | 4.73 | 0.43 | 0.18 | 0.09 | 0.00 | 0.09 | 0.00 | 0.04 | 0.00 | 0.00 | 0.09 | 0.04 | 0.00 | 0.18 | 0.00 | 0.09 | 0.18 |
| 430-28 | 9.22 | 4.92 | 0.69 | 0.46 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.18 | 0.00 | 0.00 | 0.00 | 0.46 | 0.00 | 0.09 | 0.18 |
| 430-29 | 9.26 | 4.92 | 0.71 | 0.46 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.02 | 0.00 | 0.02 | 0.00 | 0.46 | 0.00 | 0.09 | 0.19 |
| 430-30 | 8.07 | 3.55 | 0.52 | 0.32 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.32 | 0.00 | 0.08 | 0.16 |
| 430-31 | 8.10 | 3.64 | 0.53 | 0.32 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.32 | 0.00 | 0.08 | 0.16 |
| 430-32 | 8.21 | 3.75 | 0.44 | 0.25 | 0.00 | 0.00 | 0.08 | 0.00 | 0.03 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.08 | 0.16 |
| 430-33 | 8.32 | 3.90 | 0.54 | 0.33 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.33 | 0.00 | 0.08 | 0.17 |
| 430-34 | 8.35 | 3.81 | 0.75 | 0.33 | 0.08 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.33 | 0.08 | 0.08 | 0.33 |
| 430-35 | 8.42 | 3.97 | 0.76 | 0.34 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.34 | 0.00 | 0.08 | 0.34 |
| 430-36 | 8.51 | 4.49 | 0.42 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.17 | 0.00 | 0.09 | 0.17 |
| 430-37 | 8.25 | 3.87 | 0.57 | 0.33 | 0.08 | 0.00 | 0.08 | 0.00 | 0.05 | 0.00 | 0.00 | 0.08 | 0.02 | 0.00 | 0.33 | 0.00 | 0.08 | 0.17 |
| 430-38 | 8.12 | 3.66 | 0.40 | 0.16 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.03 | 0.00 | 0.16 | 0.00 | 0.08 | 0.16 |
| 430-39 | 8.00 | 3.30 | 0.30 | 0.16 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.02 | 0.00 | 0.08 | 0.00 | 0.08 | 0.16 |
| 430-40 | 7.87 | 3.23 | 0.76 | 0.55 | 0.08 | 0.00 | 0.08 | 0.00 | 0.03 | 0.08 | 0.00 | 0.08 | 0.02 | 0.00 | 0.55 | 0.00 | 0.08 | 0.16 |
| 430-41 | 8.37 | 4.00 | 0.23 | 0.17 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 | 0.00 | 0.08 | 0.17 |
| 430-42 | 8.44 | 4.23 | 0.47 | 0.34 | 0.08 | 0.00 | 0.08 | 0.00 | 0.10 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.08 | 0.34 |
| 430-43 | 8.15 | 3.49 | 0.40 | 0.16 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.16 | 0.00 | 0.08 | 0.16 |
| 430-44 | 8.23 | 3.73 | 0.49 | 0.25 | 0.08 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.25 | 0.00 | 0.08 | 0.16 |
| 430-45 | 8.37 | 3.92 | 0.11 | 0.08 | 0.00 | 0.08 | 0.08 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 |
| 430-46 | 8.39 | 4.10 | 0.81 | 0.42 | 0.08 | 0.00 | 0.08 | 0.00 | 0.11 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.25 | 0.00 | 0.08 | 0.42 |
| 430-47 | 8.72 | 4.33 | 0.85 | 0.61 | 0.09 | 0.00 | 0.09 | 0.00 | 0.03 | 0.00 | 0.09 | 0.00 | 0.03 | 0.00 | 0.61 | 0.00 | 0.09 | 0.17 |
| 430-48 | 8.34 | 3.78 | 0.75 | 0.33 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.33 | 0.00 | 0.08 | 0.33 |
| 430-49 | 8.13 | 3.63 | 0.45 | 0.24 | 0.00 | 0.00 | 0.08 | 0.00 | 0.04 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.24 | 0.00 | 0.08 | 0.16 |
| 430-50 | 9.52 | 5.33 | 0.83 | 0.57 | 0.10 | 0.00 | 0.10 | 0.00 | 0.05 | 0.00 | 0.19 | 0.10 | 0.02 | 0.10 | 0.57 | 0.00 | 0.10 | 0.19 |
| 430-51 | 8.92 | 4.60 | 0.95 | 0.71 | 0.09 | 0.00 | 0.09 | 0.00 | 0.04 | 0.00 | 0.09 | 0.00 | 0.03 | 0.00 | 0.71 | 0.00 | 0.09 | 0.18 |
| 430-52 | 7.96 | 2.77 | 2.86 | 2.23 | 0.00 | 0.00 | 0.08 | 0.00 | 0.63 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 2.23 |
| 430-53 | 10.51 | 5.86 | 0.40 | 0.32 | 0.00 | 0.00 | 0.11 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.11 | 0.32 |
| 430-54 | 9.32 | 5.04 | 0.25 | 0.19 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.19 | 0.00 | 0.02 | 0.00 | 0.00 | 0.00 | 0.09 | 0.19 |
| 430-55 | 8.79 | 4.19 | 0.60 | 0.26 | 0.09 | 0.00 | 0.09 | 0.00 | 0.07 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.09 | 0.26 |
| 430-56 | 8.54 | 4.50 | 0.25 | 0.17 | 0.09 | 0.00 | 0.09 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.09 | 0.17 |
| **Maximum (lb/gal)** | **13.30** | **9.96** | **2.86** | **2.23** | **0.10** | **0.09** | **0.13** | **0.54** | **0.63** | **0.08** | **0.19** | **0.10** | **0.04** | **0.10** | **0.71** | **0.08** | **0.11** | **2.23** |
| **Emission Rate (lb/hr)** | | **1.4E-02** | **5.7E-01** | **4.5E-01** | **1.9E-02** | **1.7E-02** | **2.7E-02** | **7.5E-04** | **1.3E-01** | **1.6E-02** | **3.8E-02** | **2.1E-02** | **8.0E-03** | **1.9E-02** | **1.4E-01** | **1.7E-02** | **2.1E-02** | **4.5E-01** |
| IDAPA TAP EL (lb/hr) | | | | | | | 4.73E+01 | 2.3E-01 | 2.90E+01 | | | 1.09E+02 | 3.33E+00 | 3.50E+01 | 2.50E+01 | 8.20E+00 | 9.13E+01 | 2.90E+01 |
| Below EL? | | | | | | | Yes | Yes | Yes | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Activators, Reducers, Solvents, and Additives

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aromatic Hydrocarbon | Butyl Acetate | n-Butyl Alcohol | Cyclohexane | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethyl Alcohol | Ethylene Glycol Monobutyl Ether | Heptane | n-Hexane (HAP) | Isopropyl Alcohol (IPA) | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Naphthalene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 441-00 | | 0.00% | | | | 1.00% | | | | 1.00% | | | | 1.00% | 1.00% | 1.00% | | | 0.60% |
| 441-01 | | 0.00% | | | | 2.00% | | | | 0.20% | | | 2.00% | | | 1.00% | | | 40.00% |
| 441-02 | | 0.00% | | | | 1.00% | | | 1.00% | | | | | 1.00% | 2.00% | 1.00% | | | 0.50% |
| 441-05 | | 0.00% | | | | 1.00% | | | | 0.40% | | | | 1.00% | | | | | 0.20% |
| 441-20 | | 0.00% | | | 1.00% | | | | | 0.60% | 1.00% | | | 1.00% | 1.00% | | | | |
| 441-21 | | 0.00% | | | 1.00% | | 1.00% | | | 1.30% | 1.00% | | | 1.00% | 1.00% | | | | |
| 441-22 | | 0.00% | | | 1.00% | 1.00% | 1.00% | | | | | | 8.00% | 1.00% | 1.00% | | | | |
| 441-29 | | 0.00% | | | | | 1.00% | | | 1.30% | 1.00% | | 12.00% | | | | | 1.00% | |
| 441-43 | | 2.23% | | | | | | 80.00% | | | | 1.00% | | | | | | | |
| 441-49 | | 0.00% | | | | | | | | | 1.00% | | 20.00% | | | | | | |
| 441-60 | | 0.00% | | | 1.00% | | | | | | | | | | | | | | |
| 441-62 | | 0.00% | | | 1.00% | | 1.00% | | | | | | | | | | 1.00% | | |
| 441-66 | | 0.00% | | | 1.00% | | | | | | | | | | | | | | |
| 441-72 | | 0.00% | | | 1.00% | | | | 1.00% | | | | | 1.00% | | | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aromatic Hydrocarbon | Butyl Acetate | n-Butyl Alcohol | Cyclohexane | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethyl Alcohol | Ethylene Glycol Monobutyl Ether | Heptane | n-Hexane (HAP) | Isopropyl Alcohol (IPA) | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Naphthalene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 441-00 | 6.42 | 0.00 | 1.00 | 0.83 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.06 | 0.06 | 0.06 | 0.00 | 0.00 | 0.04 |
| 441-01 | 6.68 | 0.00 | 3.49 | 2.67 | 0.00 | 0.13 | 0.00 | 0.00 | 0.00 | 0.01 | 0.00 | 0.00 | 0.13 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 2.67 |
| 441-02 | 6.28 | 0.00 | 1.10 | 0.94 | 0.00 | 0.06 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.06 | 0.13 | 0.06 | 0.00 | 0.00 | 0.03 |
| 441-05 | 6.49 | 0.00 | 0.49 | 0.45 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 |
| 441-20 | 6.63 | 0.00 | 1.70 | 1.46 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.04 | 0.07 | 0.00 | 0.00 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-21 | 6.71 | 0.00 | 1.56 | 1.07 | 0.07 | 0.00 | 0.07 | 0.00 | 0.00 | 0.09 | 0.07 | 0.00 | 0.00 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-22 | 6.91 | 0.00 | 1.11 | 1.04 | 0.07 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.55 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-29 | 7.40 | 0.00 | 1.21 | 0.67 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.10 | 0.07 | 0.00 | 0.89 | 0.00 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 |
| 441-43 | 6.86 | 0.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 5.49 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-49 | 7.97 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 1.59 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-60 | 6.61 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-62 | 6.67 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 |
| 441-66 | 8.75 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-72 | 6.44 | 0.00 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **8.75** | **0.15** | **3.49** | **2.67** | **0.09** | **0.13** | **0.07** | **5.49** | **0.06** | **0.10** | **0.08** | **0.07** | **1.59** | **0.07** | **0.13** | **0.07** | **0.07** | **0.07** | **2.67** |
| **Emission Rate (lb/hr)** | | **2.1E-04** | **7.0E-01** | **5.3E-01** | **1.8E-02** | **2.7E-02** | **1.5E-02** | **1.1E+00** | **1.3E-02** | **1.9E-02** | **1.6E-02** | **1.4E-02** | **3.2E-01** | **1.4E-02** | **2.5E-02** | **1.3E-02** | **1.3E-02** | **1.5E-02** | **5.3E-01** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | | 4.73E+01 | 1.00E+01 | 7.00E+01 | 2.90E+01 | | 1.25E+02 | | 1.09E+02 | 1.20E+01 | 6.53E+01 | 1.57E+01 | 3.93E+01 | 3.33E+00 |
| Below EL? | | | | | Yes | | Yes | Yes | Yes | Yes | | Yes | | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Nason Activators, Reducers, Solvents, and Additives

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Phosphoric Acid Aluminum Salt (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|
| 441-00 | | 0.00% | | | | 1.00% | 13.00% | | | |
| 441-01 | | 0.00% | | | | 1.00% | 12.00% | 1.00% | | |
| 441-02 | | 0.00% | | | | 1.00% | 15.00% | | 1% | |
| 441-05 | | 0.00% | | | | 1.00% | 7.00% | 0.20% | | |
| 441-20 | | 0.00% | | | | | 22.00% | | | 2.00% |
| 441-21 | | 0.00% | | | | | 16.00% | | | 5.00% |
| 441-22 | | 0.00% | | | | | 15.00% | 2.00% | | |
| 441-29 | | 0.00% | | | | | 9.00% | | 1.00% | 5.00% |
| 441-43 | | 2.23% | | | 1.00% | | | | | |
| 441-49 | | 0.00% | | | | | | | | |
| 441-60 | | 0.00% | | | | | | | | |
| 441-62 | | 0.00% | | | | | | | | |
| 441-66 | | 0.00% | | | | | | | | |
| 441-72 | | 0.00% | | | | | | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Phosphoric Acid Aluminum Salt (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|
| 441-00 | 6.42 | 0.00 | 1.00 | 0.83 | 0.00 | 0.06 | 0.83 | 0.00 | 0.00 | 0.00 |
| 441-01 | 6.68 | 0.00 | 3.49 | 2.67 | 0.00 | 0.07 | 0.80 | 0.07 | 0.00 | 0.00 |
| 441-02 | 6.28 | 0.00 | 1.10 | 0.94 | 0.00 | 0.06 | 0.94 | 0.00 | 0.06 | 0.00 |
| 441-05 | 6.49 | 0.00 | 0.49 | 0.45 | 0.00 | 0.06 | 0.45 | 0.01 | 0.00 | 0.00 |
| 441-20 | 6.63 | 0.00 | 1.70 | 1.46 | 0.00 | 0.00 | 1.46 | 0.00 | 0.00 | 0.13 |
| 441-21 | 6.71 | 0.00 | 1.56 | 1.07 | 0.00 | 0.00 | 1.07 | 0.00 | 0.00 | 0.34 |
| 441-22 | 6.91 | 0.00 | 1.11 | 1.04 | 0.00 | 0.00 | 1.04 | 0.14 | 0.00 | 0.00 |
| 441-29 | 7.40 | 0.00 | 1.21 | 0.67 | 0.00 | 0.00 | 0.67 | 0.00 | 0.07 | 0.37 |
| 441-43 | 6.86 | 0.15 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-49 | 7.97 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-60 | 6.61 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-62 | 6.67 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-66 | 8.75 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 441-72 | 6.44 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **8.75** | **0.15** | **3.49** | **2.67** | **0.07** | **0.07** | **1.46** | **0.14** | **0.07** | **0.37** |
| **Emission Rate (lb/hr)** | | **2.1E-04** | **7.0E-01** | **5.3E-01** | **9.6E-05** | **1.3E-02** | **2.9E-01** | **2.8E-02** | **1.5E-02** | **7.4E-02** |
| IDAPA TAP EL (lb/hr) | | | | | 6.70E-02 | 3.50E+01 | 2.50E+01 | 8.20E+00 | 9.13E+01 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Imron® Activators, Reducers, Solvents, and Additives

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aluminum | Antimony & Compounds (particulate) (HAP) | Aromatic Hydrocarbon | Barium (soluble) (particulate) | Butyl Acetate | n-Butyl Alcohol | Carbon Black (particulate) | Chromium III (particulate) (HAP) | Ethyl Benzene (HAP) | Ethyl Acetate | Methyl Amyl Ketone | Propylene Glycol Monomethyl Ether Acetate | Silica Amorphous (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 500S (clear) | | 31.60% | | | 1.00% | | | | | | | | | 0.20% | | | 1.00% | | | 3.00% | | |
| 520U | | 47.75% | | | | 10.00% | | 1.00% | | | 3.00% | | | 1.10% | | | 1.00% | | 1.00% | | | |
| 521U | | 49.43% | | | | 14.00% | | | | 1.00% | 3.00% | | | 1.10% | | | 1.00% | | 1.00% | | | |
| 522U | | 51.08% | | | | 25.00% | | 1.00% | | 1.00% | 2.00% | | | | | | 1.00% | | | | 4.00% | |
| 523U | | 46.94% | | | | 11.00% | | 1.00% | | | 3.00% | | | 1.10% | | | 1.00% | | 1.00% | | | |
| 531U | | 35.15% | | | | | | | | | | 0.10% | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 532U | | 57.19% | | | | | 5.00% | | | | | | | 0.10% | 1.00% | | 1.00% | | | 3.00% | | |
| 533U | | 38.86% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 4.00% | | |
| 534U | | 42.63% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 11.00% | | |
| 535U | | 37.08% | | | | | | | | 1.00% | | 1.50% | | 0.90% | 1.00% | | 1.00% | | | 3.00% | | |
| 536U | | 43.26% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 537U | | 49.16% | | | | | 9.00% | | | | | | 4.00% | 2.00% | 1.00% | | 1.00% | | | 4.00% | | |
| 539U | | 42.81% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 4.00% | | |
| 540U | | 42.62% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 4.00% | | |
| 541U | | 43.60% | | | | | | | 1.00% | | | | | 0.30% | 1.00% | | 1.00% | | | 4.00% | | |
| 543U | | 42.47% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 4.00% | | |
| 544U | | 41.77% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 7.00% | | |
| 547U | | 57.18% | | | | | 0.90% | | 1.00% | | | | | 0.10% | 1.00% | | 1.00% | | | 2.00% | | |
| 548U | | 49.64% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 2.00% | | |
| 550U | | 37.06% | | | | 2.00% | | | | | | | | | 1.00% | | 1.00% | | | 3.00% | | 1.00% |
| 553U | | 37.91% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 554U | | 52.95% | | | | | | | | | | | | 0.10% | 1.00% | | 1.00% | 1.00% | | 3.00% | | |
| 555U | | 54.20% | | | | | | | | | | | | 0.10% | 1.00% | | 1.00% | 1.00% | | 3.00% | | |
| 556U | | 47.54% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 557U | | 38.14% | | | | | | | | | | | | 0.40% | 1.00% | | 1.00% | | | 3.00% | | |
| 558U | | 36.48% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 559U | | 38.01% | | | | | | | | | | | | 0.50% | 1.00% | 1.00% | 1.00% | | | 3.00% | | |
| 560U | | 46.33% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 561U | | 38.52% | | | | | | | | 1.00% | | | | 0.80% | 1.00% | | 1.00% | | | 3.00% | | |
| 563U | | 38.03% | | | | | | | | 1.00% | | | | 1.30% | 1.00% | | 1.00% | | | 2.00% | | 1.00% |
| 564U | | 39.59% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | 1.00% |
| 565U | | 36.42% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 567U | | 35.81% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 568U | | 37.82% | | | | | | | | | | | | 0.20% | 1.00% | | 1.00% | | | 3.00% | | |
| 570U | | 55.47% | | | | | | | | 1.00% | | | | 0.20% | 1.00% | 1.00% | 1.00% | | | 3.00% | | |
| 571U | | 35.00% | | | | | | | | | | | | 0.10% | 1.00% | | 1.00% | | | 3.00% | | 1.00% |
| 572U | | 35.44% | | | | | | | | | | | | | 1.00% | | 1.00% | | | 5.00% | | 1.00% |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aluminum | Antimony & Compounds (particulate) (HAP) | Aromatic Hydrocarbon | Barium (soluble) (particulate) | Butyl Acetate | n-Butyl Alcohol | Carbon Black (particulate) | Chromium III (particulate) (HAP) | Ethyl Benzene (HAP) | Ethyl Acetate | Methyl Amyl Ketone | Propylene Glycol Monomethyl Ether Acetate | Silica Amorphous (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 500S (clear) | 8.25 | 2.61 | 0.26 | 0.25 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 |
| 520U | 8.64 | 4.13 | 0.44 | 0.35 | 0.00 | 0.86 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 | 0.10 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 |
| 521U | 8.74 | 4.32 | 0.45 | 0.35 | 0.00 | 1.22 | 0.00 | 0.00 | 0.00 | 0.09 | 0.26 | 0.00 | 0.00 | 0.10 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 |
| 522U | 9.32 | 4.76 | 0.00 | 0.00 | 0.00 | 2.33 | 0.00 | 0.09 | 0.00 | 0.09 | 0.19 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.37 | 0.00 |
| 523U | 8.62 | 4.05 | 0.44 | 0.34 | 0.00 | 0.95 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 |
| 531U | 8.36 | 2.94 | 0.27 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.00 | 0.02 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 |
| 532U | 11.18 | 6.39 | 0.91 | 0.56 | 0.00 | 0.00 | 0.56 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.11 | 0.00 | 0.11 | 0.00 | 0.00 | 0.34 | 0.00 | 0.00 |
| 533U | 8.60 | 3.34 | 0.36 | 0.34 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.34 | 0.00 | 0.00 |
| 534U | 8.69 | 3.70 | 0.97 | 0.86 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.96 | 0.00 | 0.00 |
| 535U | 8.32 | 3.09 | 0.57 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.12 | 0.00 | 0.07 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 |
| 536U | 9.29 | 4.02 | 0.30 | 0.28 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.28 | 0.00 | 0.00 |
| 537U | 10.06 | 4.95 | 1.91 | 0.91 | 0.00 | 0.00 | 0.91 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.40 | 0.20 | 0.10 | 0.00 | 0.10 | 0.00 | 0.00 | 0.40 | 0.00 | 0.00 |
| 539U | 8.77 | 3.75 | 0.37 | 0.35 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.35 | 0.00 | 0.00 |
| 540U | 8.71 | 3.71 | 0.37 | 0.35 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.35 | 0.00 | 0.00 |
| 541U | 8.93 | 3.89 | 0.47 | 0.36 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.03 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.36 | 0.00 | 0.00 |
| 543U | 8.84 | 3.75 | 0.37 | 0.35 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.35 | 0.00 | 0.00 |
| 544U | 8.60 | 3.59 | 0.62 | 0.60 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.60 | 0.00 | 0.00 |
| 547U | 11.50 | 6.58 | 0.35 | 0.23 | 0.00 | 0.00 | 0.10 | 0.00 | 0.12 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.12 | 0.00 | 0.12 | 0.00 | 0.00 | 0.23 | 0.00 | 0.00 |
| 548U | 10.32 | 5.12 | 0.23 | 0.21 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.10 | 0.00 | 0.10 | 0.00 | 0.00 | 0.21 | 0.00 | 0.00 |
| 550U | 8.28 | 3.07 | 0.25 | 0.25 | 0.00 | 0.17 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.08 |
| 553U | 8.54 | 3.24 | 0.27 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 |
| 554U | 10.42 | 5.52 | 0.32 | 0.31 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.10 | 0.00 | 0.10 | 0.10 | 0.00 | 0.31 | 0.00 | 0.00 |
| 555U | 10.58 | 5.73 | 0.33 | 0.32 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.11 | 0.00 | 0.11 | 0.11 | 0.00 | 0.32 | 0.00 | 0.00 |
| 556U | 9.77 | 4.64 | 0.31 | 0.29 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.10 | 0.00 | 0.10 | 0.00 | 0.00 | 0.29 | 0.00 | 0.00 |
| 557U | 8.56 | 3.26 | 0.38 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.03 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 |
| 558U | 8.46 | 3.09 | 0.27 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 |
| 559U | 8.50 | 3.23 | 0.47 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.04 | 0.09 | 0.09 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 |
| 560U | 9.63 | 4.48 | 0.31 | 0.29 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.10 | 0.00 | 0.10 | 0.00 | 0.00 | 0.29 | 0.00 | 0.00 |
| 561U | 8.59 | 3.31 | 0.58 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.07 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 |
| 563U | 8.44 | 3.21 | 0.70 | 0.42 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.11 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.17 | 0.00 | 0.08 |
| 564U | 8.66 | 3.43 | 0.28 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.09 |
| 565U | 8.54 | 3.11 | 0.27 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 |
| 567U | 8.39 | 3.00 | 0.27 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 |
| 568U | 8.61 | 3.26 | 0.28 | 0.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.26 | 0.00 | 0.00 |
| 570U | 8.18 | 4.54 | 0.26 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.02 | 0.08 | 0.08 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 |
| 571U | 8.14 | 2.85 | 0.25 | 0.24 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.24 | 0.00 | 0.08 |
| 572U | 8.16 | 2.89 | 0.41 | 0.41 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.41 | 0.00 | 0.08 |
| Maximum (lb/gal) | 11.50 | 6.58 | 1.91 | 0.96 | 0.08 | 2.33 | 0.91 | 0.09 | 0.12 | 0.09 | 0.26 | 0.12 | 0.40 | 0.20 | 0.12 | 0.09 | 0.12 | 0.11 | 0.09 | 0.96 | 0.37 | 0.09 |
| Emission Rate (lb/hr) | | 9.2E-03 | 3.8E-01 | 1.9E-01 | 1.7E-02 | 4.7E-01 | 1.3E-03 | 1.9E-02 | 1.6E-04 | 1.9E-02 | 5.2E-02 | 1.7E-04 | 5.6E-04 | 4.0E-02 | 2.3E-02 | 1.7E-02 | 2.3E-02 | 1.5E-04 | 1.7E-02 | 1.9E-01 | 7.5E-02 | 1.7E-02 |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 6.67E-01 | 3.30E-02 | | 3.30E-02 | 4.73E+01 | 1.00E+01 | 2.3E-01 | 3.30E-02 | 2.90E+01 | 9.33E+01 | 1.57E+01 | | 6.67E-01 | 3.50E+01 | 2.50E+01 | 8.20E+00 | 9.13E+01 |
| Below EL? | | | | | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Imron® Activators, Reducers, Solvents, and Additives

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Xylene (HAP) |
|---|---|---|---|---|---|
| 500S (clear) | | 31.60% | | | |
| 520U | | 47.75% | | | 4.00% |
| 521U | | 49.43% | | | 4.00% |
| 522U | | 51.06% | | | |
| 523U | | 46.94% | | | 4.00% |
| 531U | | 35.15% | | | |
| 532U | | 57.19% | | | |
| 533U | | 38.86% | | | |
| 534U | | 42.63% | | | |
| 535U | | 37.08% | | | 3.00% |
| 536U | | 43.26% | | | |
| 537U | | 49.16% | | | |
| 539U | | 42.81% | | | |
| 540U | | 42.62% | | | |
| 541U | | 43.60% | | | 1.00% |
| 543U | | 42.47% | | | |
| 544U | | 41.77% | | | |
| 547U | | 57.18% | | | |
| 548U | | 49.64% | | | |
| 550U | | 37.08% | | | |
| 553U | | 37.91% | | | |
| 554U | | 52.95% | | | |
| 555U | | 54.20% | | | |
| 556U | | 47.54% | | | |
| 557U | | 38.14% | | | 1.00% |
| 558U | | 36.48% | | | |
| 559U | | 38.01% | | | 2.00% |
| 560U | | 46.33% | | | |
| 561U | | 38.52% | | | 3.00% |
| 563U | | 38.03% | | | 5.00% |
| 564U | | 39.59% | | | |
| 565U | | 36.42% | | | |
| 567U | | 35.81% | | | |
| 568U | | 37.82% | | | |
| 570U | | 55.47% | | | |
| 571U | | 35.00% | | | |
| 572U | | 35.44% | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Xylene (HAP) |
|---|---|---|---|---|---|
| 500S (clear) | 8.25 | 2.61 | 0.26 | 0.25 | 0.00 |
| 520U | 8.64 | 4.13 | 0.44 | 0.35 | 0.35 |
| 521U | 8.74 | 4.32 | 0.45 | 0.35 | 0.35 |
| 522U | 9.32 | 4.76 | 0.00 | 0.00 | 0.00 |
| 523U | 8.62 | 4.05 | 0.44 | 0.34 | 0.34 |
| 531U | 8.36 | 2.94 | 0.27 | 0.25 | 0.00 |
| 532U | 11.18 | 6.39 | 0.91 | 0.56 | 0.00 |
| 533U | 8.60 | 3.34 | 0.36 | 0.34 | 0.00 |
| 534U | 8.89 | 3.70 | 0.97 | 0.96 | 0.00 |
| 535U | 8.32 | 3.09 | 0.57 | 0.25 | 0.25 |
| 536U | 9.29 | 4.02 | 0.30 | 0.28 | 0.00 |
| 537U | 10.06 | 4.95 | 1.91 | 0.91 | 0.00 |
| 539U | 8.77 | 3.75 | 0.37 | 0.35 | 0.00 |
| 540U | 8.71 | 3.71 | 0.37 | 0.35 | 0.00 |
| 541U | 8.93 | 3.89 | 0.47 | 0.36 | 0.09 |
| 543U | 8.84 | 3.75 | 0.37 | 0.35 | 0.00 |
| 544U | 8.60 | 3.59 | 0.62 | 0.60 | 0.00 |
| 547U | 11.50 | 6.58 | 0.35 | 0.23 | 0.00 |
| 548U | 10.32 | 5.12 | 0.23 | 0.21 | 0.00 |
| 550U | 8.28 | 3.07 | 0.25 | 0.25 | 0.00 |
| 553U | 8.54 | 3.24 | 0.27 | 0.26 | 0.00 |
| 554U | 10.42 | 5.52 | 0.32 | 0.31 | 0.00 |
| 555U | 10.58 | 5.73 | 0.33 | 0.32 | 0.00 |
| 556U | 9.77 | 4.64 | 0.31 | 0.29 | 0.00 |
| 557U | 8.56 | 3.26 | 0.38 | 0.26 | 0.09 |
| 558U | 8.46 | 3.09 | 0.27 | 0.25 | 0.00 |
| 559U | 8.59 | 3.23 | 0.47 | 0.26 | 0.17 |
| 560U | 9.83 | 4.46 | 0.31 | 0.29 | 0.00 |
| 561U | 8.59 | 3.31 | 0.58 | 0.26 | 0.26 |
| 563U | 8.44 | 3.21 | 0.70 | 0.42 | 0.42 |
| 564U | 8.66 | 3.43 | 0.28 | 0.26 | 0.00 |
| 565U | 8.54 | 3.11 | 0.27 | 0.26 | 0.00 |
| 567U | 8.39 | 3.00 | 0.27 | 0.25 | 0.00 |
| 568U | 8.61 | 3.26 | 0.28 | 0.26 | 0.00 |
| 570U | 8.18 | 4.54 | 0.26 | 0.25 | 0.00 |
| 571U | 8.14 | 2.85 | 0.25 | 0.24 | 0.00 |
| 572U | 8.18 | 2.89 | 0.41 | 0.41 | 0.00 |
| Maximum (lb/gal) | 11.50 | 6.58 | 1.91 | 0.96 | 0.42 |
| Emission Rate (lb/hr) | | 9.2E-03 | 3.8E-01 | 1.9E-01 | 8.4E-02 |
| IDAPA TAP EL (lb/hr) | | | | | 2.90E+01 |
| Below EL? | | | | | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 99.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: ChromaBase® Clears



Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Amyl Acetate | Aromatic Hydrocarbon | Butyl Acetate | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethyl Acetate | Ethylene Glycol Monobutyl Ether | Hexamethylene Diisocyanate (HDI)(HAP) | Isophorone Diisocyanate Polymer | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isobutyl Ketone (MIBK)(HAP) | Propionic Acid |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7480S | | 30.95% | | | 1.00% | | | 1.00% | 1.20% | | | | | | 1.00% | | | 1.00% |
| 7565S | | 58.18% | | | | | | | | | 1.00% | | 0.10% | | 1.00% | | | |
| 7601S | | 3.72% | | | | | 1.00% | 1.00% | 3.30% | | | | | | 1.00% | | | |
| 7655S | | 39.12% | | | | | 1.00% | 1.00% | | | | | | | | | | |
| 7675S | | 37.62% | | | | | 1.00% | 1.00% | | | | | | | | | | |
| 7695S | | 37.76% | | | | | 1.00% | 1.00% | | 1.00% | | | | | | | | |
| 7699S | | 38.10% | | | | | | 1.00% | | 1.00% | | | | | | | | |
| 7765S | | 47.03% | | | | 1.00% | | 1.00% | | | | | | 1.00% | | | | |
| 7775S | | 47.01% | | | | 1.00% | | 1.00% | 1.30% | 1.00% | | | | 1.00% | | | | |
| 7785S | | 46.97% | | | | | | 1.00% | 1.30% | 1.00% | 1.00% | | | 1.00% | | | | |
| 7795S | | 46.97% | | | | | | 1.00% | | 1.00% | | | | 1.00% | | | | |
| 7875S | | 71.33% | | | | | | | | | 1.00% | | 0.10% | | | | | |
| 7895S | | 69.18% | | | | | | | | 1.00% | | 5.00% | 0.10% | | | | | |
| G2-4500S | | 48.67% | | | 1.00% | | | 1.00% | 5.90% | | | | | | 1.00% | 1.00% | 1.00% | |
| G2-4700S | | 50.52% | | | | | | | | | | | | | | | | |
| G2-7779S | | 38.23% | | | 1.00% | | 1.00% | | 3.00% | | | | | | 1.00% | 1.00% | | |
| HC-4500S | | 52.25% | | | | | | 1.00% | 4.90% | | | | | | 1.00% | 1.00% | | |
| HC-4700S | | 51.46% | | | | | | 1.00% | 5.60% | | | | | | 1.00% | 1.00% | 1.00% | |
| HC-7776S | | 34.90% | | | 1.00 | | | | 3.80% | | | | | | 1.00% | 1.00% | 8.00% | |
| LH7775 | | 47.00% | | | | 1.00 | | 1.00% | | 1.00% | | | | 1.00% | | 1.00% | | |
| LH7779 | | 39.00% | | | 1.00 | | | 1.00% | | 1.00% | | | | | 1.00% | | | |
| LH7785 | | 47.00% | | | | | | 1.00% | | 1.00% | | | | 1.00% | | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Amyl Acetate | Aromatic Hydrocarbon | Butyl Acetate | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethyl Acetate | Ethylene Glycol Monobutyl Ether | Hexamethylene Diisocyanate (HDI)(HAP) | Isophorone Diisocyanate Polymer | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isobutyl Ketone (MIBK)(HAP) | Propionic Acid |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7480S | 7.55 | 2.34 | 0.47 | 0.38 | 0.08 | 0.00 | 0.00 | 0.08 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.08 |
| 7565S | 8.48 | 4.93 | 1.11 | 1.10 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.01 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 |
| 7601S | 7.18 | 0.27 | 3.18 | 2.01 | 0.00 | 0.00 | 0.07 | 0.07 | 0.24 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 |
| 7655S | 8.11 | 3.17 | 2.19 | 2.19 | 0.00 | 0.00 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7675S | 8.33 | 3.13 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7695S | 8.39 | 3.17 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7699S | 8.25 | 3.14 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7765S | 8.29 | 3.90 | 1.08 | 1.08 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7775S | 8.32 | 3.91 | 1.11 | 0.58 | 0.00 | 0.08 | 0.00 | 0.08 | 0.11 | 0.08 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7785S | 8.34 | 3.92 | 0.53 | 0.42 | 0.00 | 0.00 | 0.00 | 0.08 | 0.11 | 0.08 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7795S | 8.33 | 3.91 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7875S | 8.90 | 6.35 | 0.72 | 0.71 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7895S | 9.04 | 6.25 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.45 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| G2-4500S | 7.97 | 3.88 | 2.54 | 1.91 | 0.08 | 0.00 | 0.00 | 0.08 | 0.47 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.08 | 0.00 |
| G2-4700S | 8.04 | 4.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| G2-7779S | 7.63 | 2.92 | 1.22 | 0.92 | 0.08 | 0.00 | 0.08 | 0.00 | 0.23 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.00 | 0.00 |
| HC-4500S | 8.10 | 4.23 | 2.10 | 1.62 | 0.00 | 0.00 | 0.00 | 0.08 | 0.40 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.00 | 0.00 |
| HC-4700S | 8.04 | 4.14 | 2.38 | 1.77 | 0.00 | 0.00 | 0.00 | 0.08 | 0.45 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.08 | 0.00 |
| HC-7776S | 7.55 | 2.63 | 2.25 | 1.13 | 7.55 | 0.00 | 0.00 | 0.00 | 0.29 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.08 | 0.60 | 0.00 |
| LH7775 | 8.24 | 3.87 | 0.08 | 0.08 | 0.00 | 8.24 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 |
| LH7779 | 7.80 | 3.04 | 0.00 | 0.00 | 7.80 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 |
| LH7785 | 8.32 | 3.91 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **9.04** | **6.35** | **3.18** | **2.19** | **7.80** | **8.24** | **0.08** | **0.08** | **0.47** | **0.09** | **0.09** | **0.45** | **0.01** | **0.08** | **0.08** | **0.08** | **0.60** | **0.08** |
| **Emission Rate (lb/hr)** | | **8.9E-03** | **6.4E-01** | **4.4E-01** | **1.6E+00** | **1.6E+00** | **1.7E-02** | **1.7E-02** | **9.4E-02** | **1.8E-02** | **1.8E-02** | **9.0E-02** | **2.7E-04** | **2.5E-03** | **1.7E-02** | **1.6E-02** | **1.2E-01** | **1.5E-02** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | | | 4.73E+01 | 2.90E+01 | | 9.33E+01 | | 2.0E-03 | 6.0E-03 | 1.57E+01 | 3.93E+01 | 1.37E+01 | 2.00E+00 |
| Below EL? | | | | | Yes | | | Yes | Yes | | Yes | | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: ChromaBase® Clears

## ; Type: ChromaBase® Clears

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Propylene Glycol Monomethyl Ether Acetate | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|
| 7480S | | 30.95% | | | | | | 5.00% |
| 7565S | | 58.18% | | | | 13.00% | | |
| 7601S | | 3.72% | | | 1.00% | 28.00% | 2.00% | 13.00% |
| 7655S | | 39.12% | | | | 27.00% | | |
| 7675S | | 37.62% | | | 1.00% | | | |
| 7695S | | 37.76% | | | | | 6.00% | |
| 7699S | | 38.10% | | | | | | |
| 7765S | | 47.03% | | | | 13.00% | | |
| 7775S | | 47.01% | | | | 7.00% | | 5.00% |
| 7785S | | 46.97% | | | | | | 5.00% |
| 7795S | | 46.97% | | | | | | |
| 7875S | | 71.33% | | | | 8.00% | | |
| 7895S | | 69.18% | | | | | | |
| G2-4500S | | 48.67% | | | | | | 24.00% |
| G2-4700S | | 50.52% | | | | | | |
| G2-7779S | | 38.23% | | | | | 2.00% | 12.00% |
| HC-4500S | | 52.25% | | | | | | 20.00% |
| HC-4700S | | 51.46% | | | | | | 22.00% |
| HC-7776S | | 34.90% | | | | 2.00% | | 15.00% |
| LH7775 | | 47.00% | | | | | | |
| LH7779 | | 39.00% | | | | | | |
| LH7785 | | 47.00% | | | | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Propylene Glycol Monomethyl Ether Acetate | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|
| 7480S | 7.55 | 2.34 | 0.47 | 0.38 | 0.00 | 0.00 | 0.00 | 0.38 |
| 7565S | 8.48 | 4.93 | 1.11 | 1.10 | 0.00 | 1.10 | 0.00 | 0.00 |
| 7601S | 7.18 | 0.27 | 3.18 | 2.01 | 0.07 | 2.01 | 0.14 | 0.93 |
| 7655S | 8.11 | 3.17 | 2.19 | 2.19 | 0.00 | 2.19 | 0.00 | 0.00 |
| 7675S | 8.33 | 3.13 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 |
| 7695S | 8.39 | 3.17 | 0.00 | 0.00 | 0.00 | 0.00 | 0.50 | 0.00 |
| 7699S | 8.25 | 3.14 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7765S | 8.29 | 3.90 | 1.08 | 1.08 | 0.00 | 1.08 | 0.00 | 0.00 |
| 7775S | 8.32 | 3.91 | 1.11 | 0.58 | 0.00 | 0.58 | 0.00 | 0.42 |
| 7785S | 8.34 | 3.92 | 0.53 | 0.42 | 0.00 | 0.00 | 0.00 | 0.42 |
| 7795S | 8.33 | 3.91 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7875S | 8.90 | 6.35 | 0.72 | 0.71 | 0.00 | 0.71 | 0.00 | 0.00 |
| 7895S | 9.04 | 6.25 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 |
| G2-4500S | 7.97 | 3.88 | 2.54 | 1.91 | 0.00 | 0.00 | 0.00 | 1.91 |
| G2-4700S | 8.04 | 4.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| G2-7779S | 7.63 | 2.92 | 1.22 | 0.92 | 0.00 | 0.00 | 0.15 | 0.92 |
| HC-4500S | 8.10 | 4.23 | 2.10 | 1.62 | 0.00 | 0.00 | 0.00 | 1.62 |
| HC-4700S | 8.04 | 4.14 | 2.38 | 1.77 | 0.00 | 0.00 | 0.00 | 1.77 |
| HC-7776S | 7.55 | 2.63 | 2.25 | 1.13 | 0.00 | 0.15 | 0.00 | 1.13 |
| LH7775 | 8.24 | 3.87 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 |
| LH7779 | 7.80 | 3.04 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| LH7785 | 8.32 | 3.91 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Maximum (lb/gal) | 9.04 | 6.35 | 3.18 | 2.19 | 0.08 | 2.19 | 0.50 | 1.91 |
| Emission Rate (lb/hr) | | 8.9E-03 | 6.4E-01 | 4.4E-01 | 1.7E-02 | 4.4E-01 | 1.0E-01 | 3.8E-01 |
| IDAPA TAP EL (lb/hr) | | | | | | 2.50E+01 | 8.20E+00 | 2.90E+01 |
| Below EL? | | | | | | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: ChromaBase® Factory Packaged Colors

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aluminum | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Isobutanol | Methyl Ethyl Ketone (MEK)(HAP) | Mica (particulate) | Silica Silicon Dioxide (particulate) | Toluene (HAP) | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 99K | | 32.28% | | | | | 1.00% | 2.40% | 2.70% | | 1.00% | | | 24.00% | 7.00% |
| 100990K | | 24.15% | | | 1.00% | | 1.00% | | 5.50% | 1.00% | | | | | 20.00% |
| 101756K | | 25.12% | | | 1.00% | 1.00% | 1.00% | 0.40% | 5.30% | 1.00% | | | | | 19.00% |
| 736625K | | 25.40% | | | 1.00% | 1.00% | 1.00% | | 5.50% | 1.00% | | | | | 19.00% |
| 738766K | | 29.55% | | | 1.00% | | 1.00% | | 5.70% | 1.00% | | | 1.00% | | 19.00% |
| 745101K | | 23.80% | | | 1.00% | | 1.00% | | 5.60% | 1.00% | | | | | 20.00% |
| 747402K | | 26.41% | | | 1.00% | | 1.00% | | 6.30% | | | | | | 24.00% |
| B8424K | | 40.45% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 1.00% |
| B8469K | | 40.44% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 18.00% |
| B8550K | | 38.65% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 18.00% |
| B8713K | | 27.13% | | | 1.00% | | 1.00% | | 7.30% | | | | | | 27.00% |
| B8833K | | 40.57% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 18.00% |
| B9025K | | 25.74% | | | 1.00% | | 1.00% | 0.10% | 5.90% | | | | | | 22.00% |
| B9031K | | 25.37% | | | 1.00% | | 1.00% | | 6.80% | | | | | | 26.00% |
| B9118K | | 51.86% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 17.00% |
| B9145K | | 40.48% | | | 1.00% | | 1.00% | | 5.70% | | | | 1.00% | | 20.00% |
| B9326K | | 30.05% | | | 1.00% | | 1.00% | | 7.00% | | | | | | 26.00% |
| B9444K | | 40.63% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 18.00% |
| D8590K | | 28.17% | | | 1.00% | 6.00% | 1.00% | | 5.60% | | | | | | 20.00% |
| F7996K | | 25.81% | | | 1.00% | | 1.00% | | 6.70% | | | 1.00% | | | 25.00% |
| M5150K | | 26.45% | | | 1.00% | 1.00% | 1.00% | | 6.00% | 1.00% | | | | | 20.00% |
| M8744K | | 26.49% | | | 1.00% | | 1.00% | | 6.10% | 1.00% | | | | | 20.00% |
| M8757K | | 31.90% | | | 1.00% | | 1.00% | 0.10% | 5.70% | | | | | | 21.00% |
| M9318K | | 25.89% | | | 1.00% | 4.00% | 1.00% | 0.10% | 5.10% | 1.00% | | | | | 19.00% |
| M9369K | | 26.69% | | | 1.00% | 1.00% | 1.00% | | 6.00% | 1.00% | | | | | 20.00% |
| P0931K | | 25.16% | | | 1.00% | | 1.00% | 0.40% | 5.70% | 1.00% | | | | | 20.00% |
| P0932K | | 25.90% | | | 1.00% | 1.00% | 1.00% | 0.30% | 5.50% | | | | | | 20.00% |
| P0960K | | 24.55% | | | 1.00% | | 1.00% | 0.60% | 5.50% | 1.00% | | | | | 19.00% |
| P2236K | | 22.06% | | | 1.00% | | 1.00% | | 5.30% | 1.00% | | | | | 20.00% |
| P4040K | | 23.93% | | | 1.00% | | 1.00% | 0.30% | 5.50% | 1.00% | | | | | 19.00% |
| P4577K | | 24.84% | | | 1.00% | | 1.00% | | 6.10% | 1.00% | | | | | 21.00% |
| P4846K | | 25.92% | | | 1.00% | | 1.00% | | 6.10% | 1.00% | | | | | 20.00% |
| P4927K | | 24.18% | | | 1.00% | | 1.00% | 0.30% | 5.60% | 1.00% | | | | | 20.00% |
| P6640K | | 26.71% | | | 1.00% | | 1.00% | | 5.60% | 1.00% | | | | | 18.00% |
| P6647K | | 29.75% | | | 1.00% | | 1.00% | | 6.30% | 1.00% | | | | | 22.00% |
| P6755K | | 25.11% | | | 1.00% | 1.00% | 1.00% | | 5.30% | 1.00% | | | | | 20.00% |
| P6834K | | 27.98% | | | 1.00% | | 1.00% | | 5.10% | 1.00% | | | | | 18.00% |
| P7105K | | 27.49% | | | 1.00% | | 1.00% | | 6.00% | 1.00% | | | 1.00% | | 19.00% |
| P7304K | | 24.11% | | | 1.00% | | 1.00% | | 5.30% | 1.00% | | | | | 19.00% |
| P7333K | | 24.06% | | | 1.00% | 1.00% | 1.00% | 0.10% | 5.70% | 1.00% | | | | | 22.00% |
| W8430K | | 40.67% | | | 1.00% | | 1.00% | | 4.60% | | | | 1.00% | | 18.00% |

## Coating: ChromaBase® Factory Packaged Colors

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Aluminum | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Isobutanol | Methyl Ethyl Ketone (MEK)(HAP) | Mica (particulate) | Silica Silicon Dioxide (particulate) | Toluene (HAP) | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 99K | 7.81 | 2.52 | 2.71 | 1.87 | 0.00 | 0.00 | 0.08 | 0.19 | 0.21 | 0.00 | 0.08 | 0.00 | 0.00 | 1.87 | 0.55 |
| 100990K | 7.68 | 1.85 | 1.96 | 1.54 | 0.08 | 0.00 | 0.08 | 0.00 | 0.42 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.54 |
| 101756K | 7.76 | 1.95 | 1.89 | 1.47 | 0.08 | 0.08 | 0.08 | 0.03 | 0.41 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.47 |
| 736625K | 7.76 | 1.97 | 1.90 | 1.47 | 0.08 | 0.08 | 0.08 | 0.00 | 0.43 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.47 |
| 738766K | 7.82 | 2.31 | 1.93 | 1.49 | 0.08 | 0.00 | 0.08 | 0.00 | 0.45 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 1.49 |
| 745101K | 7.69 | 1.83 | 1.97 | 1.54 | 0.08 | 0.00 | 0.08 | 0.00 | 0.43 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.54 |
| 747402K | 7.83 | 2.07 | 2.37 | 1.88 | 0.08 | 0.00 | 0.08 | 0.00 | 0.49 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.88 |
| B8424K | 9.17 | 3.71 | 0.51 | 0.42 | 0.09 | 0.00 | 0.09 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 |
| B8469K | 9.17 | 3.71 | 2.07 | 1.65 | 0.09 | 0.00 | 0.09 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 1.65 |
| B8550K | 9.00 | 3.48 | 2.03 | 1.62 | 0.09 | 0.00 | 0.09 | 0.00 | 0.41 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 1.62 |
| B8713K | 7.80 | 2.12 | 2.68 | 2.11 | 0.08 | 0.00 | 0.08 | 0.00 | 0.57 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 2.11 |
| B8833K | 9.18 | 3.72 | 2.07 | 1.65 | 0.09 | 0.00 | 0.09 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 1.65 |
| B9025K | 7.84 | 2.02 | 2.19 | 1.72 | 0.08 | 0.00 | 0.08 | 0.01 | 0.46 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.72 |
| B9031K | 7.79 | 1.98 | 2.56 | 2.03 | 0.08 | 0.00 | 0.08 | 0.00 | 0.53 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 2.03 |
| B9118K | 10.40 | 5.39 | 2.25 | 1.77 | 0.10 | 0.00 | 0.10 | 0.00 | 0.48 | 0.00 | 0.00 | 0.00 | 0.10 | 0.00 | 1.77 |
| B9145K | 9.17 | 3.71 | 2.36 | 1.83 | 0.09 | 0.00 | 0.09 | 0.00 | 0.52 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 1.83 |
| B9326K | 7.86 | 2.36 | 2.59 | 2.04 | 0.08 | 0.00 | 0.08 | 0.00 | 0.55 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 2.04 |
| B9444K | 9.18 | 3.73 | 2.07 | 1.65 | 0.09 | 0.00 | 0.09 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 1.65 |
| D8590K | 7.98 | 2.25 | 2.04 | 1.60 | 0.08 | 0.48 | 0.08 | 0.00 | 0.45 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.60 |
| F7996K | 7.81 | 2.02 | 2.48 | 1.95 | 0.08 | 0.00 | 0.08 | 0.00 | 0.52 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 1.95 |
| M5150K | 7.75 | 2.05 | 2.02 | 1.55 | 0.08 | 0.08 | 0.08 | 0.00 | 0.47 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.55 |
| M8744K | 7.71 | 2.04 | 2.01 | 1.54 | 0.08 | 0.00 | 0.08 | 0.00 | 0.47 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.54 |
| M8757K | 8.00 | 2.55 | 2.14 | 1.68 | 0.08 | 0.00 | 0.08 | 0.01 | 0.46 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.68 |
| M9318K | 7.86 | 2.03 | 1.89 | 1.49 | 0.08 | 0.31 | 0.08 | 0.01 | 0.40 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.49 |
| M9369K | 7.75 | 2.07 | 2.02 | 1.55 | 0.08 | 0.08 | 0.08 | 0.00 | 0.47 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.55 |
| P0931K | 7.72 | 1.94 | 1.98 | 1.54 | 0.08 | 0.00 | 0.08 | 0.03 | 0.44 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.54 |
| P0932K | 7.80 | 2.02 | 1.99 | 1.56 | 0.08 | 0.08 | 0.08 | 0.02 | 0.43 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.56 |
| P0960K | 7.69 | 1.89 | 1.88 | 1.46 | 0.08 | 0.00 | 0.08 | 0.05 | 0.42 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.46 |
| P2236K | 7.65 | 1.69 | 1.94 | 1.53 | 0.08 | 0.00 | 0.08 | 0.00 | 0.41 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.53 |
| P4040K | 7.67 | 1.84 | 1.88 | 1.46 | 0.08 | 0.00 | 0.08 | 0.02 | 0.42 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.46 |
| P4577K | 7.66 | 1.90 | 2.08 | 1.61 | 0.08 | 0.00 | 0.08 | 0.00 | 0.47 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.61 |
| P4846K | 7.69 | 1.99 | 2.01 | 1.54 | 0.08 | 0.00 | 0.08 | 0.00 | 0.47 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.54 |
| P4927K | 7.68 | 1.86 | 1.97 | 1.54 | 0.08 | 0.00 | 0.08 | 0.02 | 0.43 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.54 |
| P6640K | 7.68 | 2.05 | 1.81 | 1.38 | 0.08 | 0.00 | 0.08 | 0.00 | 0.43 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.38 |
| P6647K | 7.88 | 2.34 | 2.23 | 1.73 | 0.08 | 0.00 | 0.08 | 0.00 | 0.50 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.73 |
| P6755K | 7.78 | 1.95 | 1.97 | 1.56 | 0.08 | 0.08 | 0.08 | 0.00 | 0.41 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.56 |
| P6834K | 7.92 | 2.22 | 1.83 | 1.43 | 0.08 | 0.00 | 0.08 | 0.00 | 0.40 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.43 |
| P7105K | 7.74 | 2.13 | 1.94 | 1.47 | 0.08 | 0.00 | 0.08 | 0.00 | 0.46 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 1.47 |
| P7304K | 7.67 | 1.85 | 1.86 | 1.46 | 0.08 | 0.00 | 0.08 | 0.00 | 0.41 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.46 |
| P7333K | 7.74 | 1.86 | 2.14 | 1.70 | 0.08 | 0.08 | 0.08 | 0.01 | 0.44 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 1.70 |
| W8430K | 9.18 | 3.73 | 2.07 | 1.65 | 0.09 | 0.00 | 0.09 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 1.65 |
| **Maximum (lb/gal)** | **10.40** | **5.39** | **2.71** | **2.11** | **0.10** | **0.48** | **0.10** | **0.19** | **0.57** | **0.08** | **0.08** | **0.08** | **0.10** | **1.87** | **2.11** |
| **Emission Rate (lb/hr)** | | **7.6E-03** | **5.4E-01** | **4.2E-01** | **2.1E-02** | **9.6E-02** | **2.1E-02** | **2.6E-04** | **1.1E-01** | **1.6E-02** | **1.6E-02** | **1.1E-04** | **1.5E-04** | **3.7E-01** | **4.2E-01** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 6.67E-01 | 4.73E+01 | 2.3E-01 | 2.90E+01 | 1.0E+01 | 3.93E+01 | 2.00E-01 | 6.70E-03 | 2.50E+01 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Centari® 5000 Acylic Urethane

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Aluminum | Antimony & Compounds (particulate) (HAP) | Aromatic Hydrocarbon | Barium (soluble) (particulate) | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethyl Acetate | Ethylene Glycol Monobutyl Ether | Hexamethylene Diisocyanate (HDI)(HAP) | Kaolin (particulate) | Methyl Amyl Ketone |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 359S | | 25.01% | | | | | 1.00% | | 1.00% | | | | | | | | |
| 389S | | 1.00% | | | | | | | | | | | | | | | |
| 501H | | 52.26% | | | | | | | 1.00% | 0.60% | 0.20% | | | | | | 1.00% |
| 502H | | 71.79% | | | | | | | 1.00% | | | | | | | | |
| 503H | | 77.54% | | | | | | | | | 0.30% | | | | | | 1.00% |
| 504H | | 49.95% | | | | | 1.00% | | 1.00% | | 0.20% | | | | | | 1.00% |
| 505H | | 48.82% | | | | | | | 1.00% | 4.10% | 1.40% | | | | | | 1.00% |
| 506H | | 44.39% | | | | | | | 1.00% | | | | | | | | 1.00% |
| 507H | | 48.62% | | | | | 1.00% | | 1.00% | | | | | | | | 1.00% |
| 509H | | 53.24% | | | | | | | 1.00% | | | | | | | | 1.00% |
| 510H | | 76.30% | | | | | | | 1.00% | | | | | | | | 1.00% |
| 512H | | 75.76% | | | | 1.50% | 1.00% | 1.00% | 1.00% | | | | | | | | 1.00% |
| 513H | | 42.59% | | | | | 1.00% | 1.00% | 1.00% | | | | | | | | 1.00% |
| 514H | | 47.13% | | | | | | | 1.00% | | | | | | | | 1.00% |
| 515H | | 66.39% | | | | | | | | | | | | | | | 1.00% |
| 516H | | 77.59% | | | 1.00% | | | | 1.00% | | | | | | | | 1.00% |
| 518H | | 52.93% | | | | | 1.00% | | 1.00% | | 0.40% | | | | | | 1.00% |
| 519H | | 48.58% | | | | | 1.00% | | 1.00% | | | | | | | | 1.00% |
| 522H | | 51.06% | | | 25.00% | | 1.00% | | 1.00% | | | | | | | | |
| 525H | | 52.70% | | | | | 1.00% | | 1.00% | | | | | | | | 1.00% |
| 527H | | 44.06% | | | | | | 1.00% | 1.00% | | | | | | | | 1.00% |
| 528H | | 48.94% | | | | | | | 1.00% | | | | | | | | 1.00% |
| 529H | | 51.47% | | | | | | 1.00% | | | | | | | | | 1.00% |
| 538H | | 72.17% | | | | 9.00% | | | 1.00% | | | | | | | | 1.00% |
| 542H | | 48.81% | | | | | 1.00% | | | | | | | | | | 1.00% |
| 545H | | 54.32% | | | | | 1.00% | | 1.00% | | | | | | | | 1.00% |
| 551H | | 52.75% | | | | | | | 1.00% | | 0.20% | | | | | | 1.00% |
| 569H | | 59.60% | | | | | | | 1.00% | | 0.10% | | | | | | 1.00% |
| 577H | | 34.39% | | | | | 1.00% | | 1.00% | | 0.10% | | | | | | 1.00% |
| 590H | | 49.62% | | | 24.00% | | 1.00% | | 1.00% | | | | | | | | |
| 773A | | 75.25% | | | | | | | | | 0.40% | | | 2.00% | | | 1.00% |
| 774A | | 69.54% | | | | | | | | | 0.40% | | 1.00% | 4.00% | | | 1.00% |
| 778A | | 93.59% | | | | | | | | | 0.20% | | 1.00% | | | | |
| 785S | | 90.00% | | | | | | | | | | | | | 0.20% | | 1.00% |
| 795S | | 66.78% | | | | | | | 1.00% | | | | 1.00% | 6.00% | 0.10% | | |
| 8685S | | 0.00% | | | | | | | | | | | 1.00% | 40.00% | | | |
| 8785S | | 0.00% | | | | | | | | | | | | 26.00% | | | 1.00% |
| 8909S | | 95.00% | | | | | | | | | | | | | 0.20% | | |
| 8920S | | 93.67% | | | | | | | | | 0.20% | | 1.00% | | | | |
| 8928S | | 71.90% | | | | | | 1.00% | | | 0.40% | | 1.00% | 10.00% | | 1.00% | |
| 8930S | | 0.00% | | | | | | | | | | | 1.00% | | | | 1.00% |
| 8989S | | 5.00% | | | | | | | | | | | | | | | |
| VGF70050 | | 58.98% | | | | | | | | | | 1.00% | | | | | 1.00% |

## Coating: Centari® 5000 Acylic Urethane

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Aluminum | Antimony & Compounds (particulate) (HAP) | Aromatic Hydrocarbon | Barium (soluble) (particulate) | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Propionate | Ethyl Acetate | Ethylene Glycol Monobutyl Ether | Hexamethylene Diisocyanate (HDI)(HAP) | Kaolin (particulate) | Methyl Amyl Ketone |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 359S | 7.67 | 1.92 | 0.15 | 0.15 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 389S | 8.14 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 501H | 8.22 | 4.30 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.05 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 502H | 14.20 | 10.19 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.14 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 503H | 16.71 | 12.96 | 0.05 | 0.05 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.17 |
| 504H | 8.55 | 4.27 | 0.02 | 0.02 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 505H | 8.24 | 4.02 | 0.28 | 0.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.34 | 0.12 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 506H | 8.20 | 3.64 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 507H | 8.58 | 4.17 | 0.09 | 0.09 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 509H | 9.16 | 4.88 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 510H | 15.82 | 12.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.16 |
| 512H | 15.50 | 11.74 | 0.23 | 0.23 | 0.00 | 0.23 | 0.16 | 0.16 | 0.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.16 |
| 513H | 8.65 | 3.68 | 0.17 | 0.17 | 0.00 | 0.00 | 0.09 | 0.09 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 514H | 8.46 | 3.99 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 515H | 12.47 | 8.28 | 0.25 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.12 |
| 516H | 14.96 | 11.61 | 0.00 | 0.00 | 0.15 | 0.00 | 0.00 | 0.00 | 0.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.15 |
| 518H | 8.41 | 4.45 | 0.12 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.03 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 519H | 8.27 | 4.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 522H | 9.32 | 4.76 | 0.00 | 0.00 | 2.33 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 525H | 9.55 | 5.03 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 | 0.00 | 0.10 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 |
| 527H | 8.81 | 3.88 | 0.26 | 0.26 | 0.00 | 0.00 | 0.00 | 0.09 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 528H | 9.17 | 4.49 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 529H | 9.43 | 4.85 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 538H | 14.80 | 10.68 | 1.48 | 1.33 | 0.00 | 1.33 | 0.00 | 0.00 | 0.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.15 |
| 542H | 8.30 | 4.05 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 545H | 9.32 | 5.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 |
| 551H | 9.57 | 5.05 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 | 0.00 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 |
| 569H | 9.68 | 5.77 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 |
| 577H | 8.09 | 2.78 | 0.09 | 0.08 | 0.00 | 0.00 | 0.08 | 0.00 | 0.08 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| 590H | 9.18 | 4.56 | 0.00 | 0.00 | 2.20 | 0.00 | 0.09 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 773A | 8.93 | 6.72 | 0.21 | 0.18 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.04 | 0.00 | 0.00 | 0.18 | 0.00 | 0.00 | 0.09 |
| 774A | 8.77 | 6.10 | 0.21 | 0.18 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.04 | 0.00 | 0.09 | 0.35 | 0.00 | 0.00 | 0.09 |
| 778A | 9.06 | 8.48 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 |
| 785S | 9.24 | 8.32 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.09 |
| 795S | 8.82 | 5.89 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.09 | 0.53 | 0.01 | 0.00 | 0.00 |
| 8685S | 7.55 | 0.00 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 3.02 | 0.00 | 0.00 | 0.00 |
| 8785S | 6.75 | 0.00 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.76 | 0.00 | 0.00 | 0.07 |
| 8909S | 9.44 | 8.97 | 0.11 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 |
| 8920S | 8.57 | 8.03 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8928S | 13.89 | 9.99 | 0.33 | 0.14 | 0.00 | 0.00 | 0.00 | 0.14 | 0.00 | 0.00 | 0.06 | 0.00 | 0.14 | 1.39 | 0.00 | 0.14 | 0.00 |
| 8930S | 6.57 | 0.00 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 0.07 |
| 8989S | 8.16 | 0.41 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| VGF70050 | 8.26 | 4.87 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.08 |
| **Maximum (lb/gal)** | **16.71** | **12.96** | **1.48** | **1.33** | **2.33** | **1.33** | **0.16** | **0.16** | **0.16** | **0.34** | **0.12** | **0.08** | **0.14** | **3.02** | **0.02** | **0.14** | **0.17** |
| **Emission Rate (lb/hr)** | | **1.8E-02** | **3.0E-01** | **2.7E-01** | **4.7E-01** | **1.9E-03** | **3.1E-02** | **2.2E-04** | **3.2E-02** | **4.7E-04** | **2.3E-02** | **1.7E-02** | **2.8E-02** | **6.0E-01** | **5.7E-04** | **1.9E-04** | **3.3E-02** |
| IDAPA TAP EL (lb/hr) | | | | | 6.67E-01 | 3.30E-02 | | 3.30E-02 | 4.73E+01 | 2.3E-01 | 2.90E+01 | | 9.33E+01 | | 2.0E-03 | 1.3E-01 | 1.57E+01 |
| Below EL? | | | | | Yes | Yes | | Yes | Yes | Yes | Yes | | Yes | | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Centari® 5000 Acylic Urethane

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Methyl Ethyl Ketone (MEK)(HAP) | Propylene Glycol Monomethyl Ether Acetate | Silica Silicon Dioxide (particulate) | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|
| 359S | | 25.01% | | | | | | | 7% | 2.00% |
| 389S | | 1.00% | | | | | | | | |
| 501H | | 52.26% | | | | | | | | |
| 502H | | 71.79% | | | | 1.00% | | | | |
| 503H | | 77.54% | | | | 1.00% | | | | |
| 504H | | 49.95% | | | | 1.00% | | | 2.00% | |
| 505H | | 48.82% | | | | | | 2.00% | | |
| 506H | | 44.39% | | | | | | 1.00% | 2.00% | |
| 507H | | 48.62% | | | | 1.00% | | 1.00% | 1.00% | |
| 509H | | 53.24% | | | | 1.00% | | | | |
| 510H | | 76.30% | | | | 1.00% | | | | |
| 512H | | 75.76% | | | | 1.00% | | | | |
| 513H | | 42.59% | | | | 1.00% | | 2.00% | | |
| 514H | | 47.13% | | | | | | | | |
| 515H | | 66.39% | | | | 1.00% | | 2.00% | | |
| 516H | | 77.59% | | | | 1.00% | 1.00% | | | |
| 518H | | 52.93% | | | | 1.00% | | | 3.00% | 1.00% |
| 519H | | 48.58% | | | | 1.00% | | | 3.00% | |
| 522H | | 51.06% | | | | 1.00% | | | 4.00% | |
| 525H | | 52.70% | | | | | | | 1.00% | |
| 527H | | 44.06% | | | | 1.00% | | 3.00% | | |
| 528H | | 48.94% | | | | 1.00% | | | | |
| 529H | | 51.47% | | | | 1.00% | | | | |
| 538H | | 72.17% | | | | 1.00% | | 1.00% | | |
| 542H | | 48.81% | | | | | | | | |
| 545H | | 54.32% | | | | | | | 2.00% | |
| 551H | | 52.75% | | | | 1.00% | | | | |
| 569H | | 59.60% | | | | 1.00% | | | | |
| 577H | | 34.39% | | | 1.00% | | | | 2.00% | |
| 590H | | 49.62% | | | | 1.00% | | | 2.00% | |
| 773A | | 75.25% | | | | | | | | 2.00% |
| 774A | | 69.54% | | | | | | | | 2.00% |
| 778A | | 93.59% | | | | | | | | |
| 785S | | 90.00% | | | | | | | | |
| 795S | | 66.78% | | | | | | | | |
| 8685S | | 0.00% | | | 1.00% | | | | | |
| 8785S | | 0.00% | | | 1.00% | | | | | |
| 8909S | | 95.00% | | | 1.00% | | | | | |
| 8920S | | 93.67% | | | | | | | | |
| 8928S | | 71.90% | | | 1.00% | | | | | 1.00% |
| 8930S | | 0.00% | | | 1.00% | | | | | |
| 8989S | | 5.00% | | | | | | | | |
| VGF70050 | | 58.98% | | | | | | | | |

## Coating: Centari® 5000 Acylic Urethane

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Methyl Ethyl Ketone (MEK)(HAP) | Propylene Glycol Monomethyl Ether Acetate | Silica Silicon Dioxide (particulate) | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|
| 359S | 7.67 | 1.92 | 0.15 | 0.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.54 | 0.15 |
| 389S | 8.14 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 501H | 8.22 | 4.30 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 502H | 14.20 | 10.19 | 0.00 | 0.00 | 0.00 | 0.14 | 0.00 | 0.00 | 0.00 | 0.00 |
| 503H | 16.71 | 12.96 | 0.05 | 0.05 | 0.00 | 0.17 | 0.00 | 0.00 | 0.00 | 0.00 |
| 504H | 8.55 | 4.27 | 0.02 | 0.02 | 0.00 | 0.09 | 0.00 | 0.00 | 0.17 | 0.00 |
| 505H | 8.24 | 4.02 | 0.28 | 0.16 | 0.00 | 0.00 | 0.00 | 0.16 | 0.00 | 0.00 |
| 506H | 8.20 | 3.64 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.08 | 0.16 | 0.00 |
| 507H | 8.58 | 4.17 | 0.09 | 0.09 | 0.00 | 0.09 | 0.00 | 0.09 | 0.09 | 0.00 |
| 509H | 9.16 | 4.88 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 |
| 510H | 15.82 | 12.07 | 0.00 | 0.00 | 0.00 | 0.16 | 0.00 | 0.00 | 0.00 | 0.00 |
| 512H | 15.50 | 11.74 | 0.23 | 0.23 | 0.00 | 0.16 | 0.00 | 0.00 | 0.00 | 0.00 |
| 513H | 8.65 | 3.68 | 0.17 | 0.17 | 0.00 | 0.09 | 0.00 | 0.17 | 0.00 | 0.00 |
| 514H | 8.46 | 3.99 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 515H | 12.47 | 8.28 | 0.25 | 0.25 | 0.00 | 0.12 | 0.00 | 0.25 | 0.00 | 0.00 |
| 516H | 14.96 | 11.61 | 0.00 | 0.00 | 0.00 | 0.15 | 0.15 | 0.00 | 0.00 | 0.00 |
| 518H | 8.41 | 4.45 | 0.12 | 0.08 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.08 |
| 519H | 8.27 | 4.02 | 0.00 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.25 | 0.00 |
| 522H | 9.32 | 4.76 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.37 | 0.00 |
| 525H | 9.55 | 5.03 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 | 0.00 |
| 527H | 8.81 | 3.88 | 0.26 | 0.26 | 0.00 | 0.09 | 0.00 | 0.26 | 0.00 | 0.00 |
| 528H | 9.17 | 4.49 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 |
| 529H | 9.43 | 4.85 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 |
| 538H | 14.80 | 10.68 | 1.48 | 1.33 | 0.00 | 0.15 | 0.00 | 0.15 | 0.00 | 0.00 |
| 542H | 8.30 | 4.05 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 545H | 9.32 | 5.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.19 | 0.00 |
| 551H | 9.57 | 5.05 | 0.02 | 0.02 | 0.00 | 0.10 | 0.00 | 0.00 | 0.00 | 0.00 |
| 569H | 9.68 | 5.77 | 0.01 | 0.01 | 0.00 | 0.10 | 0.00 | 0.00 | 0.00 | 0.00 |
| 577H | 8.09 | 2.78 | 0.09 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.16 | 0.00 |
| 590H | 9.18 | 4.56 | 0.00 | 0.00 | 0.00 | 0.09 | 0.00 | 0.00 | 0.18 | 0.00 |
| 773A | 8.93 | 6.72 | 0.21 | 0.18 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.18 |
| 774A | 8.77 | 6.10 | 0.21 | 0.18 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.18 |
| 778A | 9.06 | 8.48 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 785S | 9.24 | 8.32 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 795S | 8.82 | 5.89 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8685S | 7.55 | 0.00 | 0.08 | 0.08 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8785S | 6.75 | 0.00 | 0.07 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8909S | 9.44 | 8.97 | 0.11 | 0.09 | 0.09 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8920S | 8.57 | 8.03 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8928S | 13.89 | 9.99 | 0.33 | 0.14 | 0.14 | 0.00 | 0.00 | 0.00 | 0.00 | 0.14 |
| 8930S | 6.57 | 0.00 | 0.07 | 0.07 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8989S | 8.16 | 0.41 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| VGF70050 | 8.26 | 4.87 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **16.71** | **12.96** | **1.48** | **1.33** | **0.14** | **0.17** | **0.15** | **0.26** | **0.54** | **0.18** |
| **Emission Rate (lb/hr)** | | **1.8E-02** | **3.0E-01** | **2.7E-01** | **2.8E-02** | **3.3E-02** | **2.1E-04** | **5.3E-02** | **1.1E-01** | **3.6E-02** |
| **IDAPA TAP EL (lb/hr)** | | | | | 3.93E+01 | | 5.70E-03 | 2.50E+01 | 8.20E+00 | 2.90E+01 |
| **Below EL?** | | | | | Yes | | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: BASF Primers

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Kaolin (particulate) | Magnesium Carbonate | 1-Methoxy-2-Propanol Acetate | Methyl Acetate | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Naphthalene (HAP) | PCBTF | Phosphoric Acid Aluminum Salt (particulate) | Silica Gel (particulate) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DP-20 | | 67% | | | 10.00% | 10.00% | | 1.80% | 15.00% | 5.00% | 10.00% | | | | | | | 5% |
| DP-21 | | 70% | | | | 20.00% | | 1.10% | 20.00% | 5.00% | 5.00% | | | | | | | |
| DP-25 | | 59% | | | 5.00% | 20.00% | | 1.40% | 15.00% | | 5.00% | 5.00% | 5.00% | | | | 5.00% | 5% |
| DP-26 | | 59% | | | 5.00% | 20.00% | 5.00% | 1.40% | 15.00% | | 5.00% | 5.00% | 5.00% | | | | 5.00% | |
| DP-27 | | 59% | | | 5.00% | 20.00% | 5.00% | 1.40% | 20.00% | | 5.00% | 5.00% | 5.00% | | | | | |
| DP-31 | | 66% | | | 5.00% | 15.00% | | 1.50% | 10.00% | 5.00% | 5.00% | | 5.00% | | | | | |
| DP-200 | | 68% | | | 10.00% | | | | 20.00% | 5.00% | | | 10.00% | 5.00% | | | | 5% |
| DP-210 | | 87% | | | | 10.00% | | | | 5.00% | | | 10.00% | | | | | |
| DP-226 | | 67% | | | 5.00% | 5.00% | | 0.20% | 15.00% | 5.00% | 5.00% | 10.00% | | | | | | 5% |
| DP-238 | | 79% | | | | | | | | | 10.00% | | 5.00% | | | | | 5% |
| DP-321 | | 54% | | | 10.00% | | | | 10.00% | 5.00% | | | 10.00% | | | 40.00% | | |
| DP-8330 | | 52% | | | 25.00% | | 5.00% | 0.20% | 5.00% | | | | | 15.00% | 1.00% | | | |
| DP-8335 | | 52% | | | 25.00% | | 5.00% | 0.20% | 5.00% | | | | | 15.00% | 1.00% | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Kaolin (particulate) | Magnesium Carbonate | 1-Methoxy-2-Propanol Acetate | Methyl Acetate | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Naphthalene (HAP) | PCBTF | Phosphoric Acid Aluminum Salt (particulate) | Silica Gel (particulate) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DP-20 | 12.62 | 8.46 | 1.20 | 0.97 | 1.26 | 1.26 | 0.00 | 0.23 | 1.89 | 0.63 | 1.26 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.63 |
| DP-21 | 12.75 | 8.93 | 0.80 | 0.66 | 0.00 | 2.55 | 0.00 | 0.14 | 2.55 | 0.64 | 0.64 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DP-25 | 11.58 | 6.83 | 0.88 | 0.72 | 0.58 | 2.32 | 0.00 | 0.16 | 1.74 | 0.00 | 0.58 | 0.58 | 0.58 | 0.00 | 0.00 | 0.00 | 0.58 | 0.58 |
| DP-26 | 11.56 | 6.82 | 0.88 | 0.72 | 0.58 | 2.31 | 0.58 | 0.16 | 1.73 | 0.00 | 0.58 | 0.58 | 0.58 | 0.00 | 0.00 | 0.00 | 0.58 | 0.00 |
| DP-27 | 11.41 | 6.73 | 0.87 | 0.71 | 0.57 | 2.28 | 0.57 | 0.16 | 2.28 | 0.00 | 0.57 | 0.57 | 0.57 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DP-31 | 10.95 | 7.23 | 0.90 | 0.73 | 0.55 | 1.64 | 0.00 | 0.16 | 1.10 | 0.55 | 0.55 | 0.00 | 0.55 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DP-200 | 14.04 | 9.55 | 0.70 | 0.70 | 1.40 | 0.00 | 0.00 | 0.00 | 2.81 | 0.70 | 0.00 | 0.00 | 1.40 | 0.70 | 0.00 | 0.00 | 0.00 | 0.70 |
| DP-210 | 16.76 | 14.58 | 0.00 | 0.00 | 0.00 | 1.68 | 0.00 | 0.00 | 0.00 | 0.84 | 0.00 | 0.00 | 1.68 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DP-226 | 13.73 | 9.20 | 0.03 | 0.03 | 0.69 | 0.69 | 0.00 | 0.03 | 2.06 | 0.69 | 0.69 | 0.00 | 1.37 | 0.00 | 0.00 | 0.00 | 0.00 | 0.69 |
| DP-238 | 16.04 | 12.67 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.60 | 0.00 | 0.80 | 0.00 | 0.00 | 0.00 | 0.00 | 0.80 |
| DP-321 | 12.06 | 6.51 | 0.00 | 0.00 | 1.21 | 0.00 | 0.00 | 0.00 | 1.21 | 0.60 | 0.00 | 0.00 | 0.00 | 1.21 | 0.00 | 0.00 | 0.00 | 0.00 |
| DP-8330 | 9.19 | 4.78 | 2.41 | 1.38 | 2.30 | 0.00 | 0.46 | 0.02 | 0.46 | 0.00 | 0.00 | 0.00 | 0.00 | 1.38 | 0.09 | 0.00 | 0.00 | 0.00 |
| DP-8335 | 9.19 | 4.78 | 2.41 | 1.38 | 2.30 | 0.00 | 0.46 | 0.02 | 0.46 | 0.00 | 0.00 | 0.00 | 0.00 | 1.38 | 0.09 | 0.00 | 0.00 | 0.00 |
| Maximum (lb/gal) | 16.76 | 14.58 | 2.41 | 1.38 | 2.30 | 2.55 | 0.58 | 0.23 | 2.81 | 0.84 | 1.60 | 1.37 | 1.68 | 1.38 | 0.09 | 4.82 | 0.58 | 0.80 |
| Emission Rate (lb/hr) | | 2.0E-02 | 4.8E-01 | 2.8E-01 | 4.6E-01 | 5.1E-01 | 8.1E-04 | 4.5E-02 | 3.9E-03 | 1.7E-01 | 3.2E-01 | 2.7E-01 | 3.4E-01 | 2.8E-01 | 1.8E-02 | 9.6E-01 | 8.1E-04 | 1.1E-03 |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 4.73E+01 | 2.3E-01 | 2.90E+01 | 1.3E-01 | | 2.40E+01 | 4.1E+01 | 1.57E+01 | 3.93E+01 | 3.33E+00 | | 6.70E-02 | 6.67E-01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: BASF Primers

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Silicon Dioxide (particulate) | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|
| DP-20 | | 67% | | | 5.00% | | | 7.70% |
| DP-21 | | 70% | | | | | | 5.20% |
| DP-25 | | 59% | | | 5.00% | | 2.00% | 6.20% |
| DP-26 | | 59% | | | 5.00% | | 2.00% | 6.20% |
| DP-27 | | 59% | | | 5.00% | | 2.00% | 6.20% |
| DP-31 | | 66% | | | 5.00% | | | 6.70% |
| DP-200 | | 68% | | | 5.00% | | | |
| DP-210 | | 87% | | | 10.00% | | | |
| DP-226 | | 67% | | | 5.00% | | | |
| DP-238 | | 79% | | | | | | |
| DP-321 | | 54% | | | 5.00% | | | |
| DP-8330 | | 52% | | | 10.00% | 10.00% | | |
| DP-8335 | | 52% | | | 10.00% | 10.00% | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Silicon Dioxide (particulate) | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|
| DP-20 | 12.62 | 8.46 | 1.20 | 0.97 | 0.63 | 0.00 | 0.00 | 0.97 |
| DP-21 | 12.75 | 8.93 | 0.80 | 0.66 | 0.00 | 0.00 | 0.00 | 0.66 |
| DP-25 | 11.58 | 6.83 | 0.88 | 0.72 | 0.58 | 0.00 | 0.23 | 0.72 |
| DP-26 | 11.56 | 6.82 | 0.88 | 0.72 | 0.58 | 0.00 | 0.23 | 0.72 |
| DP-27 | 11.41 | 6.73 | 0.87 | 0.71 | 0.57 | 0.00 | 0.23 | 0.71 |
| DP-31 | 10.95 | 7.23 | 0.90 | 0.73 | 0.55 | 0.00 | 0.00 | 0.73 |
| DP-200 | 14.04 | 9.55 | 0.70 | 0.70 | 0.70 | 0.00 | 0.00 | 0.00 |
| DP-210 | 16.76 | 14.58 | 0.00 | 0.00 | 1.68 | 0.00 | 0.00 | 0.00 |
| DP-226 | 13.73 | 9.20 | 0.03 | 0.03 | 0.69 | 0.00 | 0.00 | 0.00 |
| DP-238 | 16.04 | 12.67 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DP-321 | 12.06 | 6.51 | 0.00 | 0.00 | 0.60 | 0.00 | 0.00 | 0.00 |
| DP-8330 | 9.19 | 4.78 | 2.41 | 1.38 | 0.92 | 0.92 | 0.00 | 0.00 |
| DP-8335 | 9.19 | 4.78 | 2.41 | 1.38 | 0.92 | 0.92 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **16.76** | **14.58** | **2.41** | **1.38** | **1.68** | **0.92** | **0.23** | **0.97** |
| **Emission Rate (lb/hr)** | | **2.0E-02** | **4.8E-01** | **2.8E-01** | **2.3E-03** | **1.8E-01** | **4.6E-02** | **1.9E-01** |
| IDAPA TAP EL (lb/hr) | | | | | 6.70E-03 | 2.50E+01 | 8.20E+00 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

Cookie BASF Reduction

| Control Material | Density | Iodine (particulate) | $MP_{air}$ | $MP_{gas}$ | Acetone | Ammonium | Aniline | Carbonyl di(1,2,4-triazole) (particulate) | Ammonium Hydroxide | Decane (vapour) | Xylene (vapour) | Ammonium Chloride | Sodium Acetate | n-Octyl Acetate | Carbon Tetrachloride (particulate) | Carbon Black (particulate) | Chromium III (particulate) (CrCl3) | Cyclohexane | Diethyl Maleate (vapour) | Glycerol Triacetate | Thiophosphoryl Hydrazide Dichloride (vapour) | Ethyl Acetate (DEP) | Ethyl Alcohol | Ethylene Glycol Monomethyl Ether (vapour) | Heptane | Hexamethylene Diisocyanate (HDI) (vapour) | n-Hexane (GHP) | Isobutanol | Isooctyl Acetate | Isopentane (Isopentane Polymer) | Isopropyl Alcohol (IPA) | Kaolin (particulate) | Magnesium Laurate | Methanol | 1-Methoxy-2-Propanol Acetate | Methyl Acetate | Methyl Ethyl Ketone | Methyl Ethyl Ketone (TMG-1123) | Methyl Isobutyl Ketone | Methyl Isobutyl Ketone (TMG-1122) | Methyl Propyl Ketone | Methylene Dichloride (DCM-VP) | Mica (particulate) | Naphthalene (VOP) | PCB77 | Phosphoric Acid Aqueous Soln | Polyether Polyols | Propanol | Propanol Vapour Concentrated | Silica Amorphous (particulate) | Silica Amorphous (particulate) | Silica Volcanic (particulate) | Stabilized Carbon Black (Lot 1) | 1,2,3-Trichloropropane (Vapour) | Whole Peptides |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control (Lot 1) | Density | Iodine (particulate) | $MP_{air}$ | $MP_{gas}$ | Acetone | Ammonium | Aniline | Carbonyl di(1,2,4-triazole) (particulate) | Ammonium Hydroxide | Decane (vapour) | Xylene (vapour) | Ammonium Chloride | Sodium Acetate | n-Octyl Acetate | Carbon Tetrachloride (particulate) | Carbon Black (particulate) | Chromium III (particulate) (CrCl3) | Cyclohexane | Diethyl Maleate (vapour) | Glycerol Triacetate | Thiophosphoryl Hydrazide Dichloride (vapour) | Ethyl Acetate (DEP) | Ethyl Alcohol | Ethylene Glycol Monomethyl Ether (vapour) | Heptane | Hexamethylene Diisocyanate (HDI) (vapour) | n-Hexane (GHP) | Isobutanol | Isooctyl Acetate | Isopentane (Isopentane Polymer) | Isopropyl Alcohol (IPA) | Kaolin (particulate) | Magnesium Laurate | Methanol | 1-Methoxy-2-Propanol Acetate | Methyl Acetate | Methyl Ethyl Ketone | Methyl Ethyl Ketone (TMG-1123) | Methyl Isobutyl Ketone | Methyl Isobutyl Ketone (TMG-1122) | Methyl Propyl Ketone | Methylene Dichloride (DCM-VP) | Mica (particulate) | Naphthalene (VOP) | PCB77 | Phosphoric Acid Aqueous Soln | Polyether Polyols | Propanol | Propanol Vapour Concentrated | Silica Amorphous (particulate) | Silica Amorphous (particulate) | Silica Volcanic (particulate) | Stabilized Carbon Black (Lot 1) | 1,2,3-Trichloropropane (Vapour) | Whole Peptides |
| Mean | 7.42 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 4.71 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Standard Deviation (SoM) | | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +01 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00 | 0.00 +00

## Coating: BASF Bases and Colors

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Methyl Amyl Ketone | Methyl Isobutyl Ketone (MIBK)(HAP) | Silica Amorphous (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| HD10 | | | | | 50.00% | 5.00% | 3.40% | 60.00% | | 10.00% | 5.00% | | 5% | 13.73% |
| HD17 | | | | | | | 1.50% | | | | | | 7.10% | 6.20% |
| HD18 | | | | | | | 1.80% | | | | | | 6.70% | 7.10% |
| HD45 | | | | | | | | | | | | | 5.90% | |
| HD60 | | | | | | | 0.50% | | | | | | | 2.00% |
| HD81 | | | | | | | 0.70% | | | | | | | 2.80% |
| HD85 | | | | | | | 1.00% | | | | | | | 4.10% |
| HD87 | | | | | | | 1.00% | | | | | | | 3.80% |
| SC00 | | | | | | | 0.40% | | | | | | | 1.50% |
| SC01 | | | | | | | 1.30% | | | | | | 1.70% | 5.30% |
| SC03 | | | | | | | | | | | | 2.30% | 1.90% | |
| SC10 | | | | | | | 0.10% | | 4.00% | | | | 7.90% | |
| SC20 | | | | | | | | | 4.50% | | | | 7.10% | |
| SC25 | | | | | | | 0.20% | | 2.70% | | | | 6.90% | 1.30% |
| SC29 | | | | | | | | | 5.20% | | | | 7.30% | |
| SC30 | | | | | | | 0.10% | | 2.00% | | | | 6.80% | |
| SC40 | | | | | | | | | 5.50% | | | | 6.70% | |
| SC403 | | | | | | | 0.40% | | 2.00% | | | | 6% | 2.10% |
| SC44 | | | | | | | | | 4.80% | | | | 6.60% | |
| SC46 | | | | | | | 0.10% | | 7.60% | | | | 6.60% | |
| SC54 | | | | | | | 0.10% | | 5.60% | | | | 6.40% | |
| SC56 | | | | | | | 0.10% | | 4.90% | | | | 6.60% | |
| SC59 | | | | | | | | | 6.00% | | | | 7.30% | |
| SC61 | | | | | | | | | 4.00% | | | | 4.50% | |
| SC62 | | | | | | | 0.40% | | 1.70% | | | | 5.80% | 2.00% |
| SC66 | | | | | | | 0.10% | | 2.70% | | | | 4.60% | |
| SC67 | | | | | | | 0.40% | | 3.20% | | | | 6.40% | |
| SC69 | | | | | | | | | 3.50% | | | | 7.20% | |
| SC74 | | | | | | | | | 3.00% | | | | 4.90% | |
| SC77 | | | | | | | | | 3.30% | | | | 6.10% | |
| SC79 | | | | | | | | | 6.80% | | | | 7.30% | |
| SC804 | | | | | | | 1.30% | | 4.20% | | | | 7.00% | 7.30% |
| SC82 | | | | | | | | | 5.40% | | | | 5.50% | |
| SC85 | | | | | | | | | 1.10% | | | | 5.00% | |
| SC86 | | | | | | | | | 1.10% | | | | 5.90% | |
| SC88 | | | | | | | | | 5.00% | | | | 6.20% | |
| SC90 | | | | | | | 0.70% | | | | | | | 2.80% |
| SC99 | | | | | | | | | 2.60% | | | | 7.00% | |

## Coating: BASF Bases and Colors

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Butyl Acetate | Carbon Black (particulate) | Ethyl Benzene (HAP) | Methyl Amyl Ketone | Methyl Isobutyl Ketone (MIBK)(HAP) | Silica Amorphous (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| HD10 | 11.9 | 0.00 | 2.04 | 1.63 | 5.95 | 0.60 | 0.40 | 7.14 | 0.00 | 1.19 | 0.60 | 0.00 | 0.54 | 1.63 |
| HD17 | 11.9 | 0.00 | 0.92 | 0.74 | 0.00 | 0.00 | 0.18 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.84 | 0.74 |
| HD18 | 11.9 | 0.00 | 1.06 | 0.84 | 0.00 | 0.00 | 0.21 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.80 | 0.84 |
| HD45 | 11.9 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.70 | 0.00 |
| HD60 | 11.9 | 0.00 | 0.30 | 0.24 | 0.00 | 0.00 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.24 |
| HD81 | 11.9 | 0.00 | 0.42 | 0.33 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.33 |
| HD85 | 11.9 | 0.00 | 0.61 | 0.49 | 0.00 | 0.00 | 0.12 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.49 |
| HD87 | 11.9 | 0.00 | 0.57 | 0.45 | 0.00 | 0.00 | 0.12 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.45 |
| SC00 | 11.9 | 0.00 | 0.23 | 0.18 | 0.00 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.18 |
| SC01 | 11.9 | 0.00 | 0.79 | 0.63 | 0.00 | 0.00 | 0.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.20 | 0.63 |
| SC03 | 11.9 | 0.00 | 0.27 | 0.27 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.27 | 0.23 | 0.00 |
| SC10 | 11.9 | 0.00 | 0.49 | 0.48 | 0.00 | 0.00 | 0.01 | 0.00 | 0.48 | 0.00 | 0.00 | 0.00 | 0.94 | 0.00 |
| SC20 | 11.9 | 0.00 | 0.54 | 0.54 | 0.00 | 0.00 | 0.00 | 0.00 | 0.54 | 0.00 | 0.00 | 0.00 | 0.84 | 0.00 |
| SC25 | 11.9 | 0.00 | 0.50 | 0.32 | 0.00 | 0.00 | 0.02 | 0.00 | 0.32 | 0.00 | 0.00 | 0.00 | 0.82 | 0.15 |
| SC29 | 11.9 | 0.00 | 0.62 | 0.62 | 0.00 | 0.00 | 0.00 | 0.00 | 0.62 | 0.00 | 0.00 | 0.00 | 0.87 | 0.00 |
| SC30 | 11.9 | 0.00 | 0.25 | 0.24 | 0.00 | 0.00 | 0.01 | 0.00 | 0.24 | 0.00 | 0.00 | 0.00 | 0.81 | 0.00 |
| SC40 | 11.9 | 0.00 | 0.65 | 0.65 | 0.00 | 0.00 | 0.00 | 0.00 | 0.65 | 0.00 | 0.00 | 0.00 | 0.80 | 0.00 |
| SC403 | 11.9 | 0.00 | 0.54 | 0.25 | 0.00 | 0.00 | 0.05 | 0.00 | 0.24 | 0.00 | 0.00 | 0.00 | 0.71 | 0.25 |
| SC44 | 11.9 | 0.00 | 0.57 | 0.57 | 0.00 | 0.00 | 0.00 | 0.00 | 0.57 | 0.00 | 0.00 | 0.00 | 0.79 | 0.00 |
| SC46 | 11.9 | 0.00 | 0.92 | 0.90 | 0.00 | 0.00 | 0.01 | 0.00 | 0.90 | 0.00 | 0.00 | 0.00 | 0.79 | 0.00 |
| SC54 | 11.9 | 0.00 | 0.68 | 0.67 | 0.00 | 0.00 | 0.01 | 0.00 | 0.67 | 0.00 | 0.00 | 0.00 | 0.76 | 0.00 |
| SC56 | 11.9 | 0.00 | 0.60 | 0.58 | 0.00 | 0.00 | 0.01 | 0.00 | 0.58 | 0.00 | 0.00 | 0.00 | 0.79 | 0.00 |
| SC59 | 11.9 | 0.00 | 0.71 | 0.71 | 0.00 | 0.00 | 0.00 | 0.00 | 0.71 | 0.00 | 0.00 | 0.00 | 0.87 | 0.00 |
| SC61 | 11.9 | 0.00 | 0.48 | 0.48 | 0.00 | 0.00 | 0.00 | 0.00 | 0.48 | 0.00 | 0.00 | 0.00 | 0.54 | 0.00 |
| SC62 | 11.9 | 0.00 | 0.49 | 0.24 | 0.00 | 0.00 | 0.05 | 0.00 | 0.20 | 0.00 | 0.00 | 0.00 | 0.69 | 0.24 |
| SC66 | 11.9 | 0.00 | 0.33 | 0.32 | 0.00 | 0.00 | 0.01 | 0.00 | 0.32 | 0.00 | 0.00 | 0.00 | 0.55 | 0.00 |
| SC67 | 11.9 | 0.00 | 0.43 | 0.38 | 0.00 | 0.00 | 0.05 | 0.00 | 0.38 | 0.00 | 0.00 | 0.00 | 0.76 | 0.00 |
| SC69 | 11.9 | 0.00 | 0.42 | 0.42 | 0.00 | 0.00 | 0.00 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.86 | 0.00 |
| SC74 | 11.9 | 0.00 | 0.36 | 0.36 | 0.00 | 0.00 | 0.00 | 0.00 | 0.36 | 0.00 | 0.00 | 0.00 | 0.58 | 0.00 |
| SC77 | 11.9 | 0.00 | 0.39 | 0.39 | 0.00 | 0.00 | 0.00 | 0.00 | 0.39 | 0.00 | 0.00 | 0.00 | 0.73 | 0.00 |
| SC79 | 11.9 | 0.00 | 0.81 | 0.81 | 0.00 | 0.00 | 0.00 | 0.00 | 0.81 | 0.00 | 0.00 | 0.00 | 0.87 | 0.00 |
| SC804 | 11.9 | 0.00 | 1.52 | 0.87 | 0.00 | 0.00 | 0.15 | 0.00 | 0.50 | 0.00 | 0.00 | 0.00 | 0.83 | 0.87 |
| SC82 | 11.9 | 0.00 | 0.64 | 0.64 | 0.00 | 0.00 | 0.00 | 0.00 | 0.64 | 0.00 | 0.00 | 0.00 | 0.65 | 0.00 |
| SC85 | 11.9 | 0.00 | 0.13 | 0.13 | 0.00 | 0.00 | 0.00 | 0.00 | 0.13 | 0.00 | 0.00 | 0.00 | 0.60 | 0.00 |
| SC86 | 11.9 | 0.00 | 0.13 | 0.13 | 0.00 | 0.00 | 0.00 | 0.00 | 0.13 | 0.00 | 0.00 | 0.00 | 0.70 | 0.00 |
| SC88 | 11.9 | 0.00 | 0.60 | 0.60 | 0.00 | 0.00 | 0.00 | 0.00 | 0.60 | 0.00 | 0.00 | 0.00 | 0.74 | 0.00 |
| SC90 | 11.9 | 0.00 | 0.42 | 0.33 | 0.00 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.33 |
| SC99 | 11.9 | 0.00 | 0.31 | 0.31 | 0.00 | 0.00 | 0.00 | 0.00 | 0.31 | 0.00 | 0.00 | 0.00 | 0.83 | 0.00 |
| Maximum (lb/gal) | 11.90 | 0.00 | 2.04 | 1.63 | 5.95 | 0.60 | 0.40 | 7.14 | 0.90 | 1.19 | 0.60 | 0.27 | 0.94 | 1.63 |
| Emission Rate (lb/hr) | | 0.0E+00 | 4.1E-01 | 3.3E-01 | 1.2E+00 | 8.3E-04 | 8.1E-02 | 1.4E+00 | 1.8E-01 | 1.7E-03 | 1.2E-01 | 5.5E-02 | 1.9E-01 | 3.3E-01 |
| IDAPA TAP EL (lb/hr) | | | | | 4.73E+01 | 2.3E-01 | 2.90E+01 | 1.57E+01 | 1.37E+01 | 6.67E-01 | 3.50E+01 | 2.50E+01 | 8.20E+00 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: BASF Hardeners

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Aromatic Hydrocarbon | Butyl Acetate | Carbon Black (particulate) | Diisobutyl Ketone | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Proplonate | Ethyl Acetate | Hexamethylene Diisocyanate (HDI)(HAP) | Isophorone Diisocyanate Polymer | Methyl Acetate | 2-Heptanone, Methyl Amyl Ketone | Toluene (HAP) | 1,2,4 Trimethyl Benzene |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DH-16 | 8.5 | 56% | | | 1.00% | 25.00% | 0.60% | | | 1.00% | | 0.45% | 0.20% | | | | 3% |
| DH-18 | 8.5 | 56% | | | | 20.00% | | | | | | 0.45% | 0.20% | | | | |
| DH-42 | 8.87 | 72% | | | | 20.00% | | | | | | 0.75% | | | | 13.50% | |
| DH-55 | 8.16 | 38% | | | | 20.00% | | 5.00% | | | 15.00% | 0.40% | 0.10% | 20.00% | 5.00% | 10.00% | |
| DH-57 | 8.25 | 38% | | | | 15.00% | | 5.00% | 0.10% | | | 0.40% | 0.10% | 20.00% | | | 6.30% |
| DH-59 | 8.3 | 38% | | | | 5.00% | | 5.00% | | | | 0.40% | 0.10% | 20.00% | | | 10.00% |
| DH-62 | 8.44 | 55% | | | | 35.00% | | | 0.20% | | | 0.60% | | | | 13.40% | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Aromatic Hydrocarbon | Butyl Acetate | Carbon Black (particulate) | Diisobutyl Ketone | Ethyl Benzene (HAP) | Ethyl 3-Ethoxy Proplonate | Ethyl Acetate | Hexamethylene Diisocyanate (HDI)(HAP) | Isophorone Diisocyanate Polymer | Methyl Acetate | Methyl Amyl Ketone | Toluene (HAP) | 1,2,4 Trimethyl Benzene |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DH-16 | 8.5 | 4.76 | 0.04 | 0.04 | 0.09 | 2.13 | 0.05 | 0.00 | 0.00 | 0.09 | 0.00 | 0.04 | 0.02 | 0.00 | 0.00 | 0.00 | 0.21 |
| DH-18 | 8.5 | 4.76 | 0.04 | 0.04 | 0.00 | 1.70 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.04 | 0.02 | 0.00 | 0.00 | 0.00 | 0.00 |
| DH-42 | 8.87 | 6.39 | 1.26 | 1.20 | 0.00 | 1.77 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 1.20 | 0.00 |
| DH-55 | 8.16 | 3.10 | 0.85 | 0.82 | 0.00 | 1.63 | 0.00 | 0.41 | 0.00 | 0.00 | 1.22 | 0.03 | 0.01 | 1.63 | 0.41 | 0.82 | 0.00 |
| DH-57 | 8.25 | 3.14 | 0.04 | 0.03 | 0.00 | 1.24 | 0.00 | 0.41 | 0.01 | 0.00 | 0.00 | 0.03 | 0.01 | 1.65 | 0.00 | 0.00 | 0.52 |
| DH-59 | 8.3 | 3.15 | 0.03 | 0.03 | 0.00 | 0.42 | 0.00 | 0.42 | 0.00 | 0.00 | 0.00 | 0.03 | 0.01 | 1.66 | 0.00 | 0.00 | 0.83 |
| DH-62 | 8.44 | 4.64 | 1.20 | 1.13 | 0.00 | 2.95 | 0.00 | 0.00 | 0.02 | 0.00 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 1.13 | 0.00 |
| Maximum (lb/gal) | 8.87 | 6.39 | 1.26 | 1.20 | 0.09 | 2.95 | 0.05 | 0.42 | 0.02 | 0.09 | 1.22 | 0.07 | 0.02 | 1.66 | 0.41 | 1.20 | 0.83 |
| Emission Rate (lb/hr) | | 8.9E-03 | 2.5E-01 | 2.4E-01 | 1.7E-02 | 5.9E-01 | 7.1E-05 | 8.3E-02 | 3.4E-03 | 1.7E-02 | 2.4E-01 | 2.0E-03 | 5.1E-04 | 3.3E-01 | 8.2E-02 | 2.4E-01 | 1.7E-01 |
| IDAPA TAP EL (lb/hr) | | | | | | 4.73E+01 | 2.3E-01 | 9.67E+00 | 2.90E+01 | | 9.33E+01 | 2.0E-03 | 6.0E-03 | 4.1E+01 | 1.57E+01 | 2.50E+01 | 8.20E+00 |
| Below EL? | | | | | | Yes | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: BASF Surface Prep

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | n-Butyl Alcohol | Dipropylene Glycol Methyl Ether | Ethyl Benzene (HAP) | Isobutanol | Isopropyl Alcohol (IPA) | 1-Methoxy-2-Propanol Acetate | Methyl Amyl Ketone | Methyl Isobutyl Ketone (MIBK)(HAP) | Stoddard Solvent Mineral Spirits | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DE17 | | 55% | | | 10% | 6.80% | | 5.50% | 10.00% | | 10.00% | | | | | 24.60% |
| DE18 | | 18% | | | | | | | 24.10% | 45.00% | | | 19.50% | | | |
| 902 | | 0% | | | | 36.00% | 15.00% | | | | | 10.00% | | 50.00% | 2.00% | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | n-Butyl Alcohol | Dipropylene Glycol Methyl Ether | Ethyl Benzene (HAP) | Isobutanol | Isopropyl Alcohol (IPA) | 1-Methoxy-2-Propanol Acetate | Methyl Amyl Ketone | Methyl Isobutyl Ketone (MIBK)(HAP) | Stoddard Solvent Mineral Spirits | 1,2,4 Trimethyl Benzene | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DE17 | 9.17 | 5.04 | 2.76 | 2.26 | 0.92 | 0.62 | 0.00 | 0.50 | 0.92 | 0.00 | 0.92 | 0.00 | 0.00 | 0.00 | 0.00 | 2.26 |
| DE18 | 7.37 | 1.33 | 1.44 | 1.44 | 0.00 | 0.00 | 0.00 | 0.00 | 1.78 | 3.32 | 0.00 | 0.00 | 1.44 | 0.00 | 0.00 | 0.00 |
| 902 | 6.74 | 0.00 | 0.00 | 0.00 | 0.00 | 2.43 | 1.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.67 | 0.00 | 3.37 | 0.13 | 0.00 |
| **Maximum (lb/gal)** | **9.17** | **5.04** | **2.76** | **2.26** | **0.92** | **2.43** | **1.01** | **0.50** | **1.78** | **3.32** | **0.92** | **0.67** | **1.44** | **3.37** | **0.13** | **2.26** |
| **Emission Rate (lb/hr)** | | **7.1E-03** | **5.5E-01** | **4.5E-01** | **1.8E-01** | **4.9E-01** | **2.0E-01** | **1.0E-01** | **3.6E-01** | **6.6E-01** | **1.8E-01** | **1.3E-01** | **2.9E-01** | **6.7E-01** | **2.7E-02** | **4.5E-01** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 1.00E+01 | | 2.90E+01 | 1.0E+01 | 6.53E+01 | 2.40E+01 | 1.57E+01 | 1.37E+01 | 3.50E+01 | 8.20E+00 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: BASF Clearcoat

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Butyl Acetate | Ethyl Benzene (HAP) | Ethyl Acetate | Isobutyl Acetate | Isopropyl Alcohol (IPA) | Methyl Acetate | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isoamyl Ketone | Methyl Isobutyl Ketone (MIBK)(HAP) | Methyl Propyl Ketone | Naphthalene (HAP) | Propylene Glycol Monomethyl Ether Acetate |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DC76NR | | 35% | | | 25% | | 1.10% | | | | | 35.00% | | | 5.70% | | | |
| DC92 | | 48% | | | 10.00% | | 0.60% | | | | | 40.00% | | | | | | |
| DC98 | | 35% | | | | | 1.10% | | | 11.40% | | | | | | | | |
| DC100Z | | 14% | | | 10.00% | 5.00% | | | 5.00% | | | | 10.00% | | | | | 15.00% |
| DC5100 | | 40% | | | 20.00% | | 0.90% | | | | | 35.00% | | | 2.60% | | | |
| DC5120 | | 32% | | | 25.00% | | 0.10% | | | | | 20.00% | | | 1.90% | | | |
| DC5300 | | 56% | | | 5.00% | 10.00% | | | | | | 15.00% | | | | | 0.20% | |
| DC5335 | | 43% | | | 20.00% | | | | | | 10.00% | 30.00% | | 5.00% | 1.20% | | | |
| DC5600 | | 46% | | | 20.00% | 15.00% | 0.40% | 10.00% | | | 10.00% | 15.00% | | | 1.20% | 10.00% | | |
| DC5750 | | 38% | | | | 40.00% | 2.10% | | | | | | | | 3.10% | | | |
| DC5775 | | 38% | | | 15.00% | 10.00% | 0.30% | | | | 10.00% | | | | | | | |
| DC5800 | | 37% | | | 10.00% | | | | | | | 10.00% | | | | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Butyl Acetate | Ethyl Benzene (HAP) | Ethyl Acetate | Isobutyl Acetate | Isopropyl Alcohol (IPA) | Methyl Acetate | Methyl Amyl Ketone | Methyl Ethyl Ketone (MEK)(HAP) | Methyl Isoamyl Ketone | Methyl Isobutyl Ketone (MIBK)(HAP) | Methyl Propyl Ketone | Naphthalene (HAP) | Propylene Glycol Monomethyl Ether Acetate |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DC76NR | 7.58 | 2.65 | 0.98 | 0.46 | 1.90 | 0.00 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 2.65 | 0.00 | 0.00 | 0.43 | 0.00 | 0.00 | 0.00 |
| DC92 | 8 | 3.84 | 0.43 | 0.38 | 0.80 | 0.00 | 0.05 | 0.00 | 0.00 | 0.00 | 0.00 | 3.20 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DC98 | 10.06 | 3.52 | 0.11 | 0.11 | 0.00 | 0.00 | 0.11 | 0.00 | 0.00 | 1.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DC100Z | 7.33 | 1.03 | 3.14 | 2.08 | 0.73 | 0.37 | 0.00 | 0.00 | 0.37 | 0.00 | 0.00 | 0.00 | 0.73 | 0.00 | 0.00 | 0.00 | 0.00 | 1.10 |
| DC5100 | 7.78 | 3.11 | 0.71 | 0.44 | 1.56 | 0.00 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 2.72 | 0.00 | 0.00 | 0.20 | 0.00 | 0.00 | 0.00 |
| DC5120 | 8.51 | 2.72 | 0.28 | 0.16 | 2.13 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 1.70 | 0.00 | 0.00 | 0.16 | 0.00 | 0.00 | 0.00 |
| DC5300 | 8.2 | 4.59 | 0.02 | 0.02 | 0.41 | 0.82 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.23 | 0.00 | 0.00 | 0.00 | 0.00 | 0.02 | 0.00 |
| DC5335 | 7.85 | 3.38 | 0.24 | 0.15 | 1.57 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.79 | 2.36 | 0.00 | 0.39 | 0.09 | 0.00 | 0.00 | 0.00 |
| DC5600 | 7.88 | 3.62 | 0.25 | 0.13 | 1.58 | 1.18 | 0.03 | 0.79 | 0.00 | 0.00 | 0.79 | 1.18 | 0.00 | 0.00 | 0.09 | 0.79 | 0.00 | 0.00 |
| DC5750 | 8.07 | 3.07 | 1.37 | 0.95 | 0.00 | 3.23 | 0.17 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.25 | 0.00 | 0.00 | 0.00 |
| DC5775 | 9.26 | 3.52 | 0.16 | 0.13 | 1.39 | 0.93 | 0.03 | 0.00 | 0.00 | 0.00 | 0.93 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DC5800 | 9.48 | 3.51 | 0.00 | 0.00 | 0.95 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.95 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Maximum (lb/gal) | 10.06 | 4.59 | 3.14 | 2.08 | 2.13 | 3.23 | 0.17 | 0.79 | 0.37 | 1.15 | 0.93 | 3.20 | 0.73 | 0.39 | 0.43 | 0.79 | 0.02 | 1.10 |
| Emission Rate (lb/hr) | | 6.4E-03 | 6.3E-01 | 4.2E-01 | 4.3E-01 | 6.5E-01 | 3.4E-02 | 1.6E-01 | 1.1E-02 | 2.3E-01 | 1.9E-01 | 6.4E-01 | 1.5E-01 | 7.9E-02 | 8.6E-02 | 1.6E-01 | 3.3E-03 | 2.2E-01 |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 4.73E+01 | 2.90E+01 | 9.33E+01 | 4.7E+01 | 6.53E+01 | 4.1E+01 | 1.57E+01 | 3.93E+01 | 1.60E+01 | 1.37E+01 | 4.67E+01 | 3.33E+00 | |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: BASF Clearcoat

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Amorphous (particulate) | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|
| DC76NR | | 35% | | | | | | | 6.10% |
| DC92 | | 48% | | | | | | | 4.80% |
| DC98 | | 35% | | | | | | | |
| DC100Z | | 14% | | | | 28.40% | | 15.00% | 4.40% |
| DC5100 | | 40% | | | | | | | 5.60% |
| DC5120 | | 32% | | | | | | | 1.30% |
| DC5300 | | 56% | | | | | 9.20% | | |
| DC5335 | | 43% | | | | | | | 1.90% |
| DC5600 | | 46% | | | | | | | 1.60% |
| DC5750 | | 38% | | | 10.00% | | | | 11.80% |
| DC5775 | | 38% | | | 10.00% | | | | 1.40% |
| DC5800 | | 37% | | | | | | | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Amorphous (particulate) | Toluene (HAP) | 1,2,4 Trimethyl Benzene | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|
| DC76NR | 7.58 | 2.65 | 0.98 | 0.46 | 0.00 | 0.00 | 0.00 | 0.00 | 0.46 |
| DC92 | 8 | 3.84 | 0.43 | 0.38 | 0.00 | 0.00 | 0.00 | 0.00 | 0.38 |
| DC98 | 10.06 | 3.52 | 0.11 | 0.11 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DC100Z | 7.33 | 1.03 | 3.14 | 2.08 | 0.00 | 2.08 | 0.00 | 1.10 | 0.32 |
| DC5100 | 7.78 | 3.11 | 0.71 | 0.44 | 0.00 | 0.00 | 0.00 | 0.00 | 0.44 |
| DC5120 | 8.51 | 2.72 | 0.28 | 0.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.11 |
| DC5300 | 8.2 | 4.59 | 0.02 | 0.02 | 0.00 | 0.00 | 0.75 | 0.00 | 0.00 |
| DC5335 | 7.85 | 3.38 | 0.24 | 0.15 | 0.00 | 0.00 | 0.00 | 0.00 | 0.15 |
| DC5600 | 7.88 | 3.62 | 0.25 | 0.13 | 0.00 | 0.00 | 0.00 | 0.00 | 0.13 |
| DC5750 | 8.07 | 3.07 | 1.37 | 0.95 | 0.81 | 0.00 | 0.00 | 0.00 | 0.95 |
| DC5775 | 9.26 | 3.52 | 0.16 | 0.13 | 0.93 | 0.00 | 0.00 | 0.00 | 0.13 |
| DC5800 | 9.48 | 3.51 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **10.06** | **4.59** | **3.14** | **2.08** | **0.93** | **2.08** | **0.75** | **1.10** | **0.95** |
| **Emission Rate (lb/hr)** | | **6.4E-03** | **6.3E-01** | **4.2E-01** | **1.3E-03** | **4.2E-01** | **1.5E-01** | **2.2E-01** | **1.9E-01** |
| IDAPA TAP EL (lb/hr) | | | | | 6.67E-01 | 2.50E+01 | 8.20E+00 | 9.13E+01 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Rubberized Undercoating

Content
Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Calcium Carbonate (particulate) | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl Alcohol | Ethylene Glycol Monobutyl Ether | Heptane | Hexamethylene Diisocyanate (HDI)(HAP) | n-Hexane (HAP) | Kaolin (particulate) | Methanol |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Dupont 492-01 | | | | | | | | | | | | | | 1.00% | |
| Dupont 492-51 | | | | | | 1.00% | 0.70% | | | | | | 13.00% | 1.00% | |
| 3M Body Schutz | | | | | | 1.00% | | | 5.00% | | | | 30.00% | | |
| SW DUPLI-COLOR Undercoat | | | | | | 12.00% | | 0.50% | | | | | | 19.00% | 2.00% |
| DURO KOTE Undercoat | | | | | | | | | | | | | | | |
| Quick Dry Rubberized | | | | | 30.00% | 10.00% | 5.00% | 1.00% | | | 5.00% | | 13.00% | | 2.00% |
| Transtar 4363-F | | | | | 30.00% | 2.33% | 5.00% | 1.00% | | | | | | | |

Content
lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Calcium Carbonate (particulate) | Carbon Black (particulate) | Ethyl Benzene (HAP) | Ethyl Alcohol | Ethylene Glycol Monobutyl Ether | Heptane | Hexamethylene Diisocyanate (HDI)(HAP) | n-Hexane (HAP) | Kaolin (particulate) | Methanol |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Dupont 492-01 | 9.52 | 0.00 | 1.71 | 1.71 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.10 | 0.00 |
| Dupont 492-51 | 8.68 | 0.00 | 2.26 | 1.13 | 0.00 | 0.09 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.13 | 0.09 | 0.00 |
| 3M Body Schutz | 6.66 | 0.00 | 2.00 | 2.00 | 0.00 | 0.07 | 0.00 | 0.00 | 0.33 | 0.00 | 0.00 | 0.00 | 2.00 | 0.00 | 0.00 |
| SW DUPLI-COLO | 7.38 | 0.00 | 0.26 | 0.22 | 0.00 | 0.89 | 0.00 | 0.04 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.40 | 0.15 |
| DURO KOTE Und | 8.16 | 0.00 | 1.22 | 1.22 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Quick Dry Rubber | 9.30 | 0.00 | 1.95 | 1.21 | 2.79 | 0.93 | 0.46 | 0.09 | 0.00 | 0.00 | 0.46 | 0.00 | 1.21 | 0.00 | 0.19 |
| Transtar 4363-F | 7.53 | 0.00 | 1.70 | 1.51 | 2.26 | 0.18 | 0.38 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| **Maximum (lb/gal)** | **9.52** | **0.00** | **2.26** | **2.00** | **2.79** | **0.93** | **0.46** | **0.09** | **0.33** | **0.00** | **0.46** | **0.00** | **2.00** | **1.40** | **0.19** |
| **Emission Rate (lb/hr)** | | **0.0E+00** | **4.5E-01** | **4.0E-01** | **5.6E-01** | **1.3E-03** | **6.5E-04** | **1.9E-02** | **6.7E-02** | **0.0E+00** | **9.3E-02** | **0.0E+00** | **4.0E-01** | **2.0E-03** | **3.7E-02** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 6.7E-01 | 2.3E-01 | 2.90E+01 | 1.25E+02 | | 1.09E+02 | 2.0E-03 | 1.20E+01 | 1.3E-01 | 1.73E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Rubberized Undercoating

Content
Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Silicon Dioxide (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|
| Dupont 492-01 | | | | | | 1.00% | 18.00% | 1.00% | |
| Dupont 492-51 | | | | | 0.10% | 1.00% | 13.00% | | |
| 3M Body Schutz | | | | | | 5.00% | 0.00% | | |
| SW DUPLI-COLOR Undercoat | | | | | | 10.00% | | | 3.00% |
| DURO KOTE Undercoat | | | | | | 15.00% | 15.00% | 15.00% | |
| Quick Dry Rubberized | | | | | 1.00% | | 5.00% | 5.00% | 2.00% |
| Transtar 4363-F | | | | | 1.00% | | 20.00% | 2.85% | 1.57% |

Content
lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Silica Silicon Dioxide (particulate) | Stoddard Solvent Mineral Spirits | Toluene (HAP) | VM&P Naphtha | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|
| Dupont 492-01 | 9.52 | 0.00 | 1.71 | 1.71 | 0.00 | 0.10 | 1.71 | 0.10 | 0.00 |
| Dupont 492-51 | 8.68 | 0.00 | 2.26 | 1.13 | 0.01 | 0.09 | 1.13 | 0.00 | 0.00 |
| 3M Body Schutz | 6.66 | 0.00 | 2.00 | 2.00 | 0.00 | 0.33 | 0.00 | 0.00 | 0.00 |
| SW DUPLI-COLO | 7.38 | 0.00 | 0.26 | 0.22 | 0.00 | 0.74 | 0.00 | 0.00 | 0.22 |
| DURO KOTE Und | 8.16 | 0.00 | 1.22 | 1.22 | 0.00 | 1.22 | 1.22 | 1.22 | 0.00 |
| Quick Dry Rubber | 9.30 | 0.00 | 1.95 | 1.21 | 0.09 | 0.00 | 0.46 | 0.46 | 0.19 |
| Transtar 4363-F | 7.53 | 0.00 | 1.70 | 1.51 | 0.08 | 0.00 | 1.51 | 0.21 | 0.12 |
| **Maximum (lb/gal)** | **9.52** | **0.00** | **2.26** | **2.00** | **0.09** | **1.22** | **1.71** | **1.22** | **0.22** |
| **Emission Rate (lb/hr)** | | **0.0E+00** | **4.5E-01** | **4.0E-01** | **1.3E-04** | **2.4E-01** | **3.4E-01** | **2.4E-01** | **4.4E-02** |
| IDAPA TAP EL (lb/hr) | | | | | 6.70E-03 | 3.50E+01 | 2.50E+01 | 9.13E+01 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Bed Liner Components

Content Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Hexamethylene Diisocyanate (HDI)(HAP) | Methylene Diisocyanate (MDI)(HAP) |
|---|---|---|---|---|---|---|
| BASF XS-310 | | | | | | 39.00% |
| Vortex | | | | | | 60.00% |
| Rhino 2170 A | | | | | | 60.00% |
| Monstaliner | | | | | 0.10% | |
| Morton 999623 | | | | | 0.35% | |
| Speedliner 1000 | | | | | | 9.66% |
| Speedliner Primer 450 & 460 | | | | | | 11.09% |
| Langeman 700 A | | | | | | 15.00% |
| Pro-Tex Black | | | | | 0.32% | |

Content lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Hexamethylene Diisocyanate (HDI)(HAP) | Methylene Diisocyanate (MDI)(HAP) |
|---|---|---|---|---|---|---|
| BASF XS-310 | 9.80 | 0.00 | 3.82 | 3.82 | 0.00 | 3.82 |
| Vortex | 8.12 | 0.00 | 4.87 | 4.87 | 0.00 | 4.87 |
| Rhino 2170 A | 10.33 | 0.00 | 6.20 | 6.20 | 0.00 | 6.20 |
| Monstaliner | 9.77 | 0.00 | 0.01 | 0.01 | 0.01 | 0.00 |
| Morton 999623 | 9.58 | 0.00 | 0.03 | 0.03 | 0.03 | 0.00 |
| Speedliner 1000 | 8.33 | 0.00 | 0.80 | 0.80 | 0.00 | 0.80 |
| Speedliner Primer | 8.33 | 0.00 | 0.92 | 0.92 | 0.00 | 0.92 |
| Langeman 700 A | 9.10 | 0.00 | 1.37 | 1.37 | 0.00 | 1.37 |
| Pro-Tex Black | 9.50 | 0.00 | 0.03 | 0.03 | 0.03 | 0.00 |
| **Maximum (lb/gal)** | **10.33** | **0.00** | **6.20** | **6.20** | **0.03** | **6.20** |
| **Emission Rate (lb/hr)** | | **0.0E+00** | **1.2E+00** | **1.2E+00** | **1.0E-03** | |
| IDAPA TAP EL (lb/hr) | | | | | 2.0E-03 | see "iso" MDI sheet |
| Below EL? | | | | | Yes | |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

## Coating: Bed Liner "Iso" Component (MDI-Based)

$L_{sp} = (V_{air}/359) * (273.15/T_{sp}) * 60 * (C_{MDI}/1000000) * MW * k_{MDI} * t_{sp}$

where:

| | | |
|---|---|---|
| $L_{sp}$ = the annual emissions for spray coating operations | 24.77 | lb/yr[1] |
| $V_{air}$ = the exhaust airflow rate | 10,000 | $ft^3$/min |
| 359 = the molar volume of an ideal gas | 359 | $ft^3$/lbmol @ 0°C and 1-atm |
| $T_{sp}$ = the spray temperature | 308.15 | K |
| $C_{MDI} = (VP_{MDI}/760) \times 10^6$ = the MDI concentration in the exhaust air | 0.0458 | ppmv |
| $VP_{MDI}$ = MDI vapor pressure at exhaust temperature | 3.48E-05 | mmHg[2] |
| MW = the molecular weight of MDI (250.26) | 250.26 | lb/lbmol |
| $k_{MDI}$ = the adjustment factor to the vapor pressure that is a function of MDI concentration i | 1.00 | |
| $t_{sp}$ = hr/day x 365 day/yr = is the total time in hours/year that spray coating is occurring | 1460 | hr/yr |
| $t_{hr}$ = is the total time in hours/day that spray coating is occurring | 4.00 | hr/day |
| T = the spray temperature | 95 | °F |
| **Emission Rate (lb/hr, 24-hr average)** | **2.83E-03** | |
| **IDAPA TAP EL (lb/hr)** | 3.00E-03 | |
| **Below EL?** | Yes | |

## Coating: Bed Liner Components

Content
Weight %

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Butyl Acetate | Carbon Black (particulate) | Diethyl toluene diamine (DETA) | Dipropylene Glycol Methyl Ether | Methyl Amyl Ketone | Polyether Polyols | Silica Silicon Dioxide (particulate) | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| BASF XS-350 Resin | | | | | | | | 25.00% | | | 70.00% | | |
| Rhino 2170 B | | | | | | | | 5.00% | 60.00% | | | | |
| Rhino Duraspray B | | | | | | | | | | | | | |
| Langeman Reflex Colorant | | | | | | | | 20.00% | | | 80.00% | | |
| Langeman 700 B | | | | | | | | 20.00% | | | 80.00% | | |
| Langeman Reflex 700RA | | | | | | | | | | | 100.00% | | |
| Pro-Tex Black | | 73.80% | | | 10.00% | 7.00% | 1.50% | | | 5.00% | | 1.50% | 1.50% |

Content
lb/gal

| Coating Material | Density | Solids (particulate) | $HAP_{TOT}$ | $HAP_{MAX}$ | Acetone | Butyl Acetate | Carbon Black (particulate) | Diethyl toluene diamine (DETA) | Dipropylene Glycol Methyl Ether | Methyl Amyl Ketone | Polyether Polyols | Silica Silicon Dioxide (particulate) | Xylene (HAP) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| BASF XS-350 Re: | 8.39 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 2.10 | 0.00 | 0.00 | 5.87 | 0.00 | 0.00 |
| Rhino 2170 B | 8.83 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.44 | 5.30 | 0.00 | 0.00 | 0.00 | 0.00 |
| Rhino Duraspray I | 8.66 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Langeman Reflex | 8.58 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.72 | 0.00 | 0.00 | 6.86 | 0.00 | 0.00 |
| Langeman 700 B | 8.58 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.72 | 0.00 | 0.00 | 6.86 | 0.00 | 0.00 |
| Langeman Reflex | 8.41 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 8.41 | 0.00 | 0.00 |
| Pro-Tex Black | 10.24 | 7.56 | 0.15 | 0.15 | 1.02 | 0.72 | 0.15 | 0.00 | 0.00 | 0.51 | 0.00 | 0.15 | 0.15 |
| **Maximum (lb/gal)** | **10.24** | **7.56** | **0.15** | **0.15** | **1.02** | **0.72** | **0.15** | **2.10** | **5.30** | **0.51** | **8.41** | **0.15** | **0.15** |
| **Emission Rate (lb/hr)** | | **1.1E-02** | **3.1E-02** | **3.1E-02** | **2.0E-01** | **1.4E-01** | **2.2E-04** | **4.2E-01** | **1.1E+00** | **1.0E-01** | **1.7E+00** | **2.2E-04** | **3.1E-02** |
| IDAPA TAP EL (lb/hr) | | | | | 1.19E+02 | 4.73E+01 | 2.3E-01 | | | 1.57E+01 | | 6.70E-03 | 2.90E+01 |
| Below EL? | | | | | Yes | Yes | Yes | | | Yes | | Yes | Yes |

| Daily Use Rates (gal/day) | Averaging Period (hr/day) | Transfer Efficiency (%) | Filter Control Efficiency (%) |
|---|---|---|---|
| 4.00 | 24 | 65.00% | 98.00% |

| Isocyanate Reaction Factor (ratio) | Annual Usage Rate (gal/yr) | Safety Factor (ratio) |
|---|---|---|
| 85.00% | 1,460.0 | 1.20 |

**General PTC**
**Automotive Coating**
**Emission Inventory - spray booth heater emissions for natural gas combustion, AP-42 Section 1.4 (7/98)**

Heat Input Capacity: 10.00 MMBtu/hr

Operating Assumptions: 24 hr/day; 2,080 hr/yr; 1,020 MMBtu/MMscf

Fuel Use: 9.80E-03 MMscf/hr; 0.235 MMscf/day; 20.39 MMscf/yr

| Criteria Air Pollutants | Emission Factor | Emissions | | Modeling Threshold | | Below Threshold? | Modeling Threshold | | Below Threshold? |
|---|---|---|---|---|---|---|---|---|---|
| | lb/MMscf | lb/hr | T/yr | 2002 Guidance | | | Case-by-Case | | |
| $NO_2$ | 94 | 9.22E-01 | 9.58E-01 | 1 | T/yr | Yes | 7 | T/yr | Yes |
| CO | 40 | 3.92E-01 | 4.08E-01 | 14 | lb/hr | Yes | 70 | lb/hr | Yes |
| $PM_{10}$ | 7.6 | 7.45E-02 | 7.75E-02 | 0.2 | lb/hr | Yes | 0.9 | lb/hr | Yes |
| | | | | 1 | T/yr | Yes | 7 | T/yr | Yes |
| $SO_X$ | 0.6 | 5.88E-03 | 6.12E-03 | 0.2 | lb/hr | Yes | 0.9 | lb/hr | Yes |
| | | | | 4.00 | T/yr | Yes | 7 | T/yr | Yes |
| VOC | 5.5 | 5.39E-02 | 5.61E-02 | 40 | T/yr | Yes | | | |
| Lead | 0.0005 | 4.90E-06 | 5.10E-06 | 0.6 | T/yr | Yes | | | |
| | | | lb/mo | | | | | | |
| | | | 3.65E-03 | 10 | lb/mo | Yes | | | |

Note: 100 lb/mo Pb in guidance reduced by factor of 10 based on latest Pb NAAQS (reduced in 2008 from 1.5 ug/m3 to 0.15 ug/m3)

| Hazardous Air Pollutants (HAP) and Toxic Air Pollutants (TAP) | | | | Modeling Threshold | Below Threshold? |
|---|---|---|---|---|---|
| | lb/MMscf | lb/hr | T/yr | EL (lb/hr) | |
| **Organic HAP PAH** | | | | | |
| 2-Methylnaphthalene | 2.40E-05 | **5.59E-08** | **5.81E-08** | 9.10E-05 | Yes |
| 3-Methylchloranthrene | 1.80E-06 | **4.19E-09** | **4.36E-09** | 2.50E-06 | Yes |
| Acenaphthene | 1.80E-06 | **4.19E-09** | **4.36E-09** | 9.10E-05 | Yes |
| Acenaphthylene | 1.80E-06 | **4.19E-09** | **4.36E-09** | 9.10E-05 | Yes |
| Anthracene | 2.40E-06 | **5.59E-09** | **5.81E-09** | 9.10E-05 | Yes |
| Benzo(a)anthracene | 1.80E-06 | **4.19E-09** | **4.36E-09** | 9.10E-05 | See POM |
| Benzo(a)pyrene | 1.20E-06 | **2.79E-09** | **2.91E-09** | 2.00E-06 | See POM |
| Benzo(b)fluoranthene | 1.80E-06 | **4.19E-09** | **4.36E-09** | | See POM |
| Benzo(g,h,i)perylene | 1.20E-06 | **2.79E-09** | **2.91E-09** | 9.10E-05 | Yes |
| Benzo(k)fluoranthene | 1.80E-06 | **4.19E-09** | **4.36E-09** | | See POM |
| Chrysene | 1.80E-06 | **4.19E-09** | **4.36E-09** | | See POM |
| Dibenzo(a,h)anthracene | 1.20E-06 | **2.79E-09** | **2.91E-09** | | See POM |
| Dichlorobenzene | 1.20E-03 | **2.79E-06** | **2.91E-06** | 9.10E-05 | Yes |
| Fluoranthene | 3.00E-06 | **6.98E-09** | **7.26E-09** | 9.10E-05 | Yes |
| Fluorene | 2.80E-06 | **6.52E-09** | **6.78E-09** | 9.10E-05 | Yes |
| Indeno(1,2,3-cd)pyrene | 1.80E-06 | **4.19E-09** | **4.36E-09** | | See POM |
| Naphthalene | 6.10E-04 | **1.42E-06** | **1.48E-06** | 3.33 | Yes |
| Naphthalene | 6.10E-04 | **1.42E-06** | **1.48E-06** | 9.10E-05 | Yes |
| Phenanathrene | 1.70E-05 | **3.96E-08** | **4.12E-08** | 9.10E-05 | Yes |
| Pyrene | 5.00E-06 | **1.16E-08** | **1.21E-08** | 9.10E-05 | Yes |
| Polycyclic Organic Matter (POM, 7-PAH Group) | | **2.65E-08** | **2.76E-08** | 2.00E-06 | Yes |
| **Organic HAP Non-PAH** | | | | | |
| Benzene | 2.10E-03 | **4.89E-06** | **5.08E-06** | 8.00E-04 | Yes |
| Formaldehyde | 7.50E-02 | **1.75E-04** | **4.15E-05** | 5.10E-04 | Yes |
| Hexane | 1.80E+00 | 1.76E-02 | **4.19E-03** | 12 | Yes |
| Toluene | 3.40E-03 | 3.33E-05 | **7.91E-06** | 25 | Yes |
| **Organic Non-HAP** | | | | | |
| 7,12-Dimethylbenz(a)anthracene | 1.60E-05 | 1.57E-07 | **3.72E-08** | | |
| Butane | 2.10E+00 | 2.06E-02 | **4.89E-03** | | |
| Ethane | 3.10E+00 | 3.04E-02 | **7.22E-03** | | |
| Pentane | 2.60E+00 | 2.55E-02 | **6.05E-03** | 118 | Yes |
| Propane | 1.60E+00 | 1.57E-02 | **3.72E-03** | | |
| **Metal HAP** | | | | | |
| Arsenic | 2.00E-04 | **4.66E-07** | **1.11E-07** | 1.50E-06 | Yes |
| Barium | 4.40E-03 | 4.31E-05 | **1.02E-05** | 0.033 | Yes |
| Beryllium | 1.20E-05 | **2.79E-08** | **6.63E-09** | 2.80E-05 | Yes |
| Cadmium | 1.10E-03 | **2.56E-06** | **6.08E-07** | 3.70E-06 | Yes |
| Chromium | 1.40E-03 | 1.37E-05 | **3.26E-06** | 0.033 | Yes |
| Cobalt | 8.40E-05 | 8.24E-07 | **1.96E-07** | 0.0033 | Yes |
| Copper | 8.50E-04 | 8.33E-06 | **1.98E-06** | 0.013 | Yes |
| Manganese | 3.80E-04 | 3.73E-06 | **8.85E-07** | 0.067 | Yes |
| Mercury | 2.60E-04 | 2.55E-06 | **6.05E-07** | 0.003 | Yes |
| Molybdenum | 1.10E-03 | 1.08E-05 | **2.56E-06** | 0.333 | Yes |
| Nickel | 2.10E-03 | **4.89E-06** | **1.16E-06** | 2.70E-05 | Yes |
| Selenium | 2.40E-05 | 2.35E-07 | **5.59E-08** | 0.013 | Yes |
| Vanadium | 2.30E-03 | 2.25E-05 | **5.35E-06** | 0.003 | Yes |
| Zinc | 2.90E-02 | 2.84E-04 | **6.75E-05** | 0.667 | Yes |

NOTE: TAP emissions are based on 24-hour averages unless shown in **bold**, which are based on annual averages.

**General PTC**
**Automotive Coating**
***Emission Inventories - maximum emission estimates of all coatings analyzed and including booth heater emissions***

| Criteria Air Pollutants | Booth Emissions | Heater Emissions | Combined Emissions | Booth Emissions | Heater Emissions | Combined Emissions | Modeling Threshold | | Below Threshold? | Modeling Threshold | | Below Threshold? |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | lb/hr | lb/hr | lb/hr | T/yr | T/yr | T/yr | 2002 Guidance | | | Case-by-Case | | |
| $NO_2$ | 0.000 | 0.922 | 0.922 | 0.000 | 0.96 | 0.96 | 1 | T/yr | Yes | 7 | T/yr | Yes |
| CO | 0.000 | 0.393 | 0.393 | 0.000 | 0.41 | 0.41 | 14 | lb/hr | Yes | 70 | lb/hr | Yes |
| $PM_{10}$ | 0.031 | 0.075 | 0.106 | 0.136 | 0.08 | 0.22 | 0.2 | lb/hr | Yes | 0.9 | lb/hr | Yes |
| | | | | | | | 1 | T/yr | Yes | 7 | T/yr | Yes |
| $SO_X$ | 0.000 | 0.006 | 0.006 | 0.000 | 0.030 | 0.03 | 0.2 | lb/hr | Yes | 0.9 | lb/hr | Yes |
| | | | | | | | 1 | T/yr | Yes | 7 | T/yr | Yes |
| VOC | 4.560 | 0.054 | 4.614 | 19.973 | 0.06 | 20.04 | 40 | T/yr | Yes | | | |
| Lead | 0.E+00 | 5.E-06 | 5.E-06 | 0.E+00 | 6.E-06 | 6.E-06 | 0.6 | T/yr | Yes | | | |
| | lb/mo | lb/mo | lb/mo | | | | | | | | | |
| | 0.000 | 0.004 | 0.004 | | | | 10 | lb/mo | Yes | | | |
| $PM_{10}$ (uncontrolled) | 1.550 | 0.075 | 1.625 | 6.789 | 0.08 | 6.87 | | | | | | |

| Hazardous Air Pollutants (HAP) and Toxic Air Pollutants (TAP) | | | | | | |
|---|---|---|---|---|---|---|
| | Booth Emissions | Heater Emissions | Combined Emissions | Combined Emissions | Modeling Threshold | Below Threshold? |
| | lb/hr | lb/hr | lb/hr | T/yr | EL (lb/hr) | |
| **Organic HAP PAH** | | | | | | |
| 2-Methylnaphthalene | 0.00E+00 | 5.59E-08 | 5.59E-08 | 5.81E-08 | 9.10E-05 | Yes |
| 3-Methylchloranthrene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | 2.50E-06 | Yes |
| Acenaphthene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | 9.10E-05 | Yes |
| Acenaphthylene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | 9.10E-05 | Yes |
| Anthracene | 0.00E+00 | 5.59E-09 | 5.59E-09 | 5.81E-09 | 9.10E-05 | Yes |
| Benzo(a)anthracene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | 9.10E-05 | See POM |
| Benzo(a)pyrene | 0.00E+00 | 2.79E-09 | 2.79E-09 | 2.91E-09 | 2.00E-06 | See POM |
| Benzo(b)fluoranthene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | | See POM |
| Benzo(g,h,i)perylene | 0.00E+00 | 2.79E-09 | 2.79E-09 | 2.91E-09 | 9.10E-05 | Yes |
| Benzo(k)fluoranthene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | | See POM |
| Chrysene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | | See POM |
| Dibenzo(a,h)anthracene | 0.00E+00 | 2.79E-09 | 2.79E-09 | 2.91E-09 | | See POM |
| Dichlorobenzene | 0.00E+00 | 2.79E-06 | 2.79E-06 | 2.91E-06 | 9.10E-05 | Yes |
| 7,12-Dimethylbenz(a)anthracene | 0.00E+00 | 1.57E-07 | 1.57E-07 | 1.63E-07 | 9.10E-05 | Yes |
| Fluoranthene | 0.00E+00 | 6.98E-09 | 6.98E-09 | 7.26E-09 | 9.10E-05 | Yes |
| Fluorene | 0.00E+00 | 6.52E-09 | 6.52E-09 | 6.78E-09 | 9.10E-05 | Yes |
| Indeno(1,2,3-cd)pyrene | 0.00E+00 | 4.19E-09 | 4.19E-09 | 4.36E-09 | | See POM |
| Phenanathrene | 0.00E+00 | 3.96E-08 | 3.96E-08 | 4.12E-08 | 9.10E-05 | Yes |
| Pyrene | 0.00E+00 | 1.16E-08 | 1.16E-08 | 1.21E-08 | 9.10E-05 | Yes |
| Polycyclic Organic Matter (POM, 7-P | 0.00E+00 | 2.65E-08 | 2.65E-08 | 2.76E-08 | 2.00E-06 | Yes |
| **Organic HAP Non-PAH** | | | | | | |
| Benzene | 0.00E+00 | 4.89E-06 | 4.89E-06 | 5.08E-06 | 8.00E-04 | Yes |
| Ethyl Benzene | 1.40E-01 | 0.00E+00 | 1.40E-01 | 6.14E-01 | 2.90E+01 | Yes |
| Formaldehyde | 0.00E+00 | 1.75E-04 | 1.75E-04 | 1.82E-04 | 5.10E-04 | Yes |
| Hexamethylene Diisocyanate (HDI) | 2.00E-03 | 0.00E+00 | 2.00E-03 | 8.74E-03 | 2.00E-03 | Yes |
| n-Hexane | 4.00E-01 | 1.76E-02 | 4.17E-01 | 1.77E+00 | 1.20E+01 | Yes |
| Methanol | 3.72E-02 | 0.00E+00 | 3.72E-02 | 1.63E-01 | 1.73E+01 | Yes |
| Methyl Ethyl Ketone (MEK) | 2.76E-01 | 0.00E+00 | 2.76E-01 | 1.21E+00 | 3.93E+01 | Yes |
| Methyl Isobutyl Ketone (MIBK) | 2.87E-01 | 0.00E+00 | 2.87E-01 | 1.26E+00 | 1.37E+01 | Yes |
| Methylene Diisocyanate (MDI) | 2.83E-03 | 0.00E+00 | 2.83E-03 | 1.24E-02 | 3.00E-03 | Yes |
| Naphthalene | 5.34E-01 | 1.42E-06 | 5.34E-01 | 2.34E+00 | 3.33E+00 | Yes |
| Styrene | 5.73E-01 | 0.00E+00 | 5.73E-01 | 2.51E+00 | 6.67E+00 | Yes |
| Toluene | 4.38E-01 | 3.33E-05 | 4.38E-01 | 1.92E+00 | 2.50E+01 | Yes |
| Xylene | 5.38E-01 | 0.00E+00 | 5.38E-01 | 2.36E+00 | 2.90E+01 | Yes |
| **Organic Non-HAP** | | | | | | |
| Acetone | 1.76E+00 | 0.00E+00 | 1.76E+00 | 7.73E+00 | 1.19E+02 | Yes |
| Butyl Acetate | 1.33E+00 | 0.00E+00 | 1.33E+00 | 5.84E+00 | 4.73E+01 | Yes |
| n-Butyl Alcohol | 1.10E+00 | 0.00E+00 | 1.10E+00 | 4.81E+00 | 1.00E+01 | Yes |
| Carbon Black | 1.05E-03 | 0.00E+00 | 1.05E-03 | 4.59E-03 | 2.30E-01 | Yes |
| Cyclohexane | 1.29E-02 | 0.00E+00 | 1.29E-02 | 5.64E-02 | 7.00E+01 | Yes |
| Diisobutyl Ketone | 8.30E-02 | 0.00E+00 | 8.30E-02 | 3.64E-01 | 9.67E+00 | Yes |
| Ethyl Acetate | 2.45E-01 | 0.00E+00 | 2.45E-01 | 1.07E+00 | 9.33E+01 | Yes |
| Ethyl Alcohol | 6.66E-02 | 0.00E+00 | 6.66E-02 | 2.92E-01 | 1.25E+02 | Yes |
| Heptane | 9.30E-02 | 0.00E+00 | 9.30E-02 | 4.07E-01 | 1.09E+02 | Yes |
| Isobutanol | 3.55E-01 | 3.33E-05 | 3.55E-01 | 1.56E+00 | 1.00E+01 | Yes |
| Isobutyl Acetate | 1.10E-02 | 0.00E+00 | 1.10E-02 | 4.82E-02 | 4.67E+01 | Yes |
| Isophorone Diisocyanate Polymer | 2.50E-03 | 1.57E-07 | 2.50E-03 | 1.10E-02 | 6.00E-03 | Yes |
| Isopropyl Alcohol (IPA) | 6.63E-01 | 2.06E-02 | 6.84E-01 | 2.93E+00 | 6.53E+01 | Yes |
| 1-Methoxy-2-Propanol Acetate | 3.21E-01 | 2.55E-02 | 3.46E-01 | 1.43E+00 | 2.40E+01 | Yes |
| Methyl Acetate | 3.32E-01 | 1.57E-02 | 3.48E-01 | 1.47E+00 | 4.07E+01 | Yes |
| Methyl Amyl Ketone | 1.53E+00 | 0.00E+00 | 1.53E+00 | 6.70E+00 | 1.57E+01 | Yes |
| Methyl Isoamyl Ketone | 7.85E-02 | 4.31E-05 | 7.85E-02 | 3.44E-01 | 1.60E+01 | Yes |
| Methyl Propyl Ketone | 1.58E-01 | 2.56E-06 | 1.58E-01 | 6.90E-01 | 4.67E+01 | Yes |
| Pentane | 0.00E+00 | 2.55E-02 | 2.55E-02 | 2.65E-02 | 1.18E+02 | Yes |
| Propionic Acid | 1.51E-02 | 2.55E-06 | 1.51E-02 | 6.61E-02 | 2.00E+00 | Yes |
| Stoddard Solvent Mineral Spirits | 6.74E-01 | 2.25E-05 | 6.74E-01 | 2.95E+00 | 3.50E+01 | Yes |
| 1,2,4 Trimethyl Benzene | 1.88E-01 | 0.00E+00 | 1.88E-01 | 8.24E-01 | 8.20E+00 | Yes |
| VM&P Naphtha | 2.45E-01 | 0.00E+00 | 2.45E-01 | 1.07E+00 | 9.13E+01 | Yes |
| **Metal HAP** | | | | | | |
| Antimony | 1.86E-03 | 0.00E+00 | 1.86E-03 | 8.17E-03 | 3.30E-02 | Yes |
| Arsenic | 0.00E+00 | 4.66E-07 | 4.66E-07 | 4.84E-07 | 1.50E-06 | Yes |
| Beryllium | 0.00E+00 | 2.79E-08 | 2.79E-08 | 2.91E-08 | 2.80E-05 | Yes |
| Cadmium | 0.00E+00 | 2.56E-06 | 2.56E-06 | 2.66E-06 | 3.70E-06 | Yes |
| Chromium III | 5.63E-04 | 1.37E-05 | 5.77E-04 | 2.48E-03 | 3.30E-02 | Yes |
| Cobalt | 0.00E+00 | 8.24E-07 | 8.24E-07 | 8.56E-07 | 3.30E-03 | Yes |
| Copper | 0.00E+00 | 8.33E-06 | 8.33E-06 | 8.67E-06 | 1.30E-02 | Yes |
| Manganese | 0.00E+00 | 3.73E-06 | 3.73E-06 | 3.87E-06 | 6.70E-02 | Yes |
| Mercury | 0.00E+00 | 2.55E-06 | 2.55E-06 | 2.65E-06 | 3.00E-03 | Yes |
| Molybdenum | 0.00E+00 | 1.08E-05 | 1.08E-05 | 1.12E-05 | 3.33E-01 | Yes |
| Nickel | 0.00E+00 | 4.89E-06 | 4.89E-06 | 5.08E-06 | 2.70E-05 | Yes |
| Selenium | 0.00E+00 | 2.35E-07 | 2.35E-07 | 2.45E-07 | 1.30E-02 | Yes |
| Vanadium | 0.00E+00 | 2.25E-05 | 2.25E-05 | 2.35E-05 | 3.00E-03 | Yes |
| Zinc | 0.00E+00 | 2.84E-04 | 2.84E-04 | 2.96E-04 | 6.67E-01 | Yes |
| **Metal Non-HAP** | | | | | | |
| Aluminum | 4.66E-01 | 0.00E+00 | 4.66E-01 | 2.04E+00 | 6.67E-01 | Yes |
| Barium | 2.60E-04 | 4.31E-05 | 3.03E-04 | 1.18E-03 | 3.30E-02 | Yes |
| **Inorganic Non-HAP** | | | | | | |
| Calcium Carbonate | 1.30E-03 | 0.00E+00 | 1.30E-03 | 5.70E-03 | 6.67E-01 | Yes |
| Kaolin | 3.93E-03 | 3.04E-02 | 3.43E-02 | 4.88E-02 | 1.33E-01 | Yes |
| Mica | 1.09E-04 | 8.24E-07 | 1.10E-04 | 4.80E-04 | 2.00E-01 | Yes |
| Silica Amorphous | 1.67E-03 | 1.08E-05 | 1.68E-03 | 7.31E-03 | 6.67E-01 | Yes |
| Silica Gel | 1.12E-03 | 4.89E-06 | 1.13E-03 | 4.92E-03 | 6.67E-01 | Yes |
| Silica Silicon Dioxide | 2.56E-03 | 2.35E-07 | 2.56E-03 | 1.12E-02 | 6.70E-03 | Yes |
| | | $HAP_{TOT}$ | 3.250 | 14.24 | | |
| | | $HAP_{MAX}$ | 0.574 | 2.52 | | |

**Assumptions when estimating spray booth heater emissions:**
- Maximum heater size 10.00 MMBtu/hr
- Annual heater operation 2,080 hr/yr
- Fuel type natural gas only

**Assumptions when estimating spray booth emissions:**
- Maximum coating use rates 4.00 gal/day for all coatings (excluding "B" component)
- Averaging period 24 hr/day average
- Annual booth operation 8,760 hr/yr
- Safety factor 1.20 allowance for coatings not analyzed
- Transfer efficiency 65% control for particulates
- Filter removal efficiency 98% control for particulates
- Isocyanate reaction factor 85% control for isocyanates (not applied to MDI)
- Maximum coating density 16.76 lb/gal
- % of monomer in mixture 1% for diisocyanates in hardener mixture
- If no % of TAP was listed in the MSDS, then 1.0% was assumed

**Assumptions when estimating spray booth MDI emissions from truck bed lining:**
- Spray booth emissions were estimated referencing the equation and assumptions from Section 19.0 of the MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry, Alliance for the Polyurethanes Industry (API), 2004.
- 100% of isocyanate content was MDI ($k_{MDI}$ = 1.0).
- Spray booth filtration does not reduce or remove MDI (0% control efficiency).
- The combined spray and dry time to apply 4 gal of "iso" component is 4 hr or less.
- Spray coatings are applied 365 days per year.
- Spray coatings are applied at less than 95°F.

**Assumptions when estimating additional VOC emissions from truck bed liner "B" component** (VOC from the "iso" component were accounted for within the analysis for the 4 gal/day limit):
- Maximum "B" use rate ###### gal/day (1:1 by volume A:B mixture)
- Safety factor ###### allowance for coatings not analyzed
- Maximum coating density ###### lb/gal (from "Bed Liner B" sheet)
- Averaging period 24 hr/day average
- VOC emissions ###### lb/hr
- B component does not contain HAP or TAP substances

| | | | | | | | PM Emissions | | | PM2.5/10 Emissions | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Equipment | Volume Metal Removed by the Cut [a] ($in^3$/hr) | Total Weight of Metal Removed by Cut [a] (lbs/hr) | Control Method | Control Efficiency (%)[c] | Hour/ Day | Hours/ Year | Weight PM Emissions [b] (lbs/hr) | PM Hourly Emissions [b] (lb/hr) | PM Annual Emissions (tons/yr) | Weight PM2.5/10 Emissions[a] (lbs/hr) | PM2.5/10 Hourly Emissions[a] (lb/hr) | PM2.5/10 Annual Emissions (tons/yr) | Chromium (lb/hr) | Chromium (tons/yr) | Hexavalent Chromium (lb/hr) | Hexavalent Chromium (tons/yr) |
| Laser Cutting Machine | 30.00 | 8.35 | Robovent Plaser 3 | 99.9% | 8 | 2024 | 1.00144 | 0.00100 | 0.00101 | 0.50 | 0.0005 | 0.00051 | 6.01E-06 | 6.08E-06 | 1.32E-09 | 1.34E-09 |
| Plasma Cutting Table | 24.95 | 7.06 | Robovent Plaser 3 (to be installed) | 99.9% | 8 | 1250 | 0.84664 | 0.00085 | 0.00053 | 0.42 | 0.21 | 0.13229 | 5.08E-06 | 3.17E-06 | 1.12E-09 | 6.98E-10 |
| Abrasive Cutting (chop saw) | 24.95 | 7.06 | None | 0% | 0.5 | 50 | 0.84664 | 0.84664 | 0.02117 | 0.42 | 0.21 | 0.00529 | 5.08E-03 | 1.27E-04 | 1.12E-06 | 2.79E-08 |
| Total Emissions | | | | | | | | | 2.27E-02 | | | 1.38E-01 | | 1.36E-04 | | 3.00E-08 |
| 24-hr or Annual Avg (lb/hr) | | | | | | | | | | | | | 1.10E-04 | | | 6.84E-09 |

**Calculations:**

(a) Average 250"/minute Laser and 105"/min plasma and chop, width of cut 0.004" Laser, 0.1" plasma and chop, stainless steel = 0.5"; galvanized gauge 20 = 0.0396" and total weight of the metal removed by the cut = density * volume (PM10Emissions = 50% PM Emissions);

(b) Total Weight Removed by Cut X 0.12 lb/lb (PM Emission Factor for plasma/laser are cutting 0.12 lb/lb (PM10=0.5lb/lb) Cut Source test data, Appendix B, 4-24-90, P/C report, A/N 184446)

(c) MERV 16 99.9% control per manufacturer email.

References: https://yosemite.epa.gov/r9/air/epss.nsf/6924c72e5ea10d5e882561b100685e04/a5169187cd5c065508257790005d840b/$FILE/Evaluation.pdf

Additional References: http://www.npi.gov.au/sites/www.npi.gov.au/files/resources/15095a24-5fb6-9014-3942-fbceb1c39047/files/fstfamet.pdf

Additional References: http://www.dep.wv.gov/daq/Documents/January%202015/3149-Eval.pdf

Appendix B, 4-24-90, P/C report, A/N 184446

Chromium => 0.008 lb/lb

Hex. Chromium => 0.00022 lb/lb

Ni => 0.005 lb/lb

Mn => 0.0181 lb/lb

Fe => 0.69 lb/lb

Zn => 0.1 lb/lb

**YMC**

| Pollutant | Flux | Gas | Units | Flux Cored Arc Daily[a],[c] (lb/day) | Flux Cored Arc Annual[b],[c] (tons/yr) | Gas Metal Arc Daily[a],[c] (lb/day) | Gas Metal Arc Annual[b],[c] (tons/yr) | Totals Pollutant (tpy) | 24-hr or Annual Average (lb/hr)[3] |
|---|---|---|---|---|---|---|---|---|---|
| | Emission Factor | | | | | | | | |
| **Criteria Pollutants [1]** | | | | | | | | | |
| $PM_{2.5}/_{10}$ | 12.2 | 5.2 | lb/10$^3$ lb | 9.52E-03 | 5.24E-04 | 5.87E-03 | 7.34E-04 | 1.26E-03 | |
| **Hazardous Air Pollutants [2]** | | | | | | | | | |
| Chromium | 0.02 | 0.01 | lb/10$^3$ lb | 1.56E-05 | 2.00E-06 | 1.12E-05 | 1.40E-06 | 3.40E-06 | 1.12E-06 |
| Cobalt | 0.01 | 0.01 | lb/10$^3$ lb | 7.80E-06 | 1.00E-06 | 1.12E-05 | 1.40E-06 | 2.40E-06 | 7.92E-07 |
| Manangese | 6.62 | 3.2 | lb/10$^3$ lb | 5.16E-03 | 6.62E-04 | 3.56E-03 | 4.45E-04 | 1.11E-03 | 3.64E-04 |
| Nickel | 0.04 | 0.01 | lb/10$^3$ lb | 3.12E-05 | 4.00E-06 | 1.12E-05 | 1.40E-06 | 5.40E-06 | 1.23E-06 |
| | | | | | | | | | |

**Calculations:**

(a) Daily Emissions (lb/day) = [Daily Throughput (tons/day)] x [Emission Factor (lbs/10$^3$ lb)] / [1,000 lbs]

(b) Annual Emissions (tons/yr) = [Annual Throughput (lb/yr) x [Emission Factor (lbs/10$^3$ lb)] / (2,000 lb/ton)

Daily Throughput Flux (lb/day) = 7.80 Annual Througput Flux (lb/yr) = 2,000

Daily Throughput Gas Metal (lb/day) = 11.20 Annual Througput Gas Metal (lb/yr) = 2,800

(c) All welding is controlled via a Donaldson Torit prota trunk which is a MERV 15; 90% http://www.allergyclean.com/understanding-merv-or-the-minimum-efficiency-reporting-value/

**Notes:**

(1) AP-42 Table 12.19-1 PM-10 Emission Factors for Welding Operations.

(2) AP-42 Table 12.19-2 HAP Emission Factors for Welding Operations.

**Natural Gas Heaters**

| | | Daily | Annual | Heat Input | | Emission Factors [1][2] (lb/MMBtu) | | | | | PM2.5/10 | | NOx | | CO | | VOC | | SO2 | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Equipment | Hours | Hours | (MMBTU/hr) | PM (Total) | PM10 | NOx | CO | VOC | SO2 | (lb/hr) | (tpy) | (lb/hr) | (tpy) | (lb/hr) | (tpy) | (lb/hr) | (tpy) | (lb/hr) | (tpy) |
| UH1 | Infrared Radiant Tube Heater | 24 | 8760 | 0.075 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 5.59E-04 | 2.45E-03 | 7.35E-03 | 3.22E-02 | 6.18E-03 | 2.71E-02 | 4.04E-04 | 1.77E-03 | 4.41E-05 | 1.93E-04 |
| UH2 | Infrared Radiant Tube Heater | 24 | 8760 | 0.100 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 7.45E-04 | 3.26E-03 | 9.80E-03 | 4.29E-02 | 8.24E-03 | 3.61E-02 | 5.39E-04 | 2.36E-03 | 5.88E-05 | 2.58E-04 |
| UH3 | Unit Heater | 24 | 8760 | 0.144 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 1.07E-03 | 4.69E-03 | 1.41E-02 | 6.17E-02 | 1.18E-02 | 5.19E-02 | 7.75E-04 | 3.40E-03 | 8.46E-05 | 3.70E-04 |
| UH4 | Infrared Radiant Tube Heater | 24 | 8760 | 0.100 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 7.45E-04 | 3.26E-03 | 9.80E-03 | 4.29E-02 | 8.24E-03 | 3.61E-02 | 5.39E-04 | 2.36E-03 | 5.88E-05 | 2.58E-04 |
| UH5 | Infrared Radiant Tube Heater | 24 | 8760 | 0.100 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 7.45E-04 | 3.26E-03 | 9.80E-03 | 4.29E-02 | 8.24E-03 | 3.61E-02 | 5.39E-04 | 2.36E-03 | 5.88E-05 | 2.58E-04 |
| UH6 | Infrared Radiant Tube Heater | 24 | 8760 | 0.075 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 5.59E-04 | 2.45E-03 | 7.35E-03 | 3.22E-02 | 6.18E-03 | 2.71E-02 | 4.04E-04 | 1.77E-03 | 4.41E-05 | 1.93E-04 |
| UH7 | Unit Heater | 24 | 8760 | 0.150 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 1.12E-03 | 4.90E-03 | 1.47E-02 | 6.44E-02 | 1.24E-02 | 5.41E-02 | 8.09E-04 | 3.54E-03 | 8.82E-05 | 3.86E-04 |
| UH8 | Unit Heater | 24 | 8760 | 0.150 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 1.12E-03 | 4.90E-03 | 1.47E-02 | 6.44E-02 | 1.24E-02 | 5.41E-02 | 8.09E-04 | 3.54E-03 | 8.82E-05 | 3.86E-04 |
| UH9 | Unit Heater | 24 | 8760 | 0.150 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 1.12E-03 | 4.90E-03 | 1.47E-02 | 6.44E-02 | 1.24E-02 | 5.41E-02 | 8.09E-04 | 3.54E-03 | 8.82E-05 | 3.86E-04 |
| UH10 | Unit Heater | 24 | 8760 | 0.150 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 1.12E-03 | 4.90E-03 | 1.47E-02 | 6.44E-02 | 1.24E-02 | 5.41E-02 | 8.09E-04 | 3.54E-03 | 8.82E-05 | 3.86E-04 |
| UH11 | Radiant Heater | 24 | 8760 | 0.066 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 4.92E-04 | 2.15E-03 | 6.47E-03 | 2.83E-02 | 5.44E-03 | 2.38E-02 | 3.56E-04 | 1.56E-03 | 3.88E-05 | 1.70E-04 |
| UH12 | Radiant Heater | 24 | 8760 | 0.066 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 4.92E-04 | 2.15E-03 | 6.47E-03 | 2.83E-02 | 5.44E-03 | 2.38E-02 | 3.56E-04 | 1.56E-03 | 3.88E-05 | 1.70E-04 |
| UH13 | Radiant Heater | 24 | 8760 | 0.066 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 4.92E-04 | 2.15E-03 | 6.47E-03 | 2.83E-02 | 5.44E-03 | 2.38E-02 | 3.56E-04 | 1.56E-03 | 3.88E-05 | 1.70E-04 |
| RTU1 | RTU Package Unit | 24 | 8760 | 0.100 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 7.45E-04 | 3.26E-03 | 9.80E-03 | 4.29E-02 | 8.24E-03 | 3.61E-02 | 5.39E-04 | 2.36E-03 | 5.88E-05 | 2.58E-04 |
| RTU2 | RTU Package Unit | 24 | 8760 | 0.045 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 3.38E-04 | 1.48E-03 | 4.45E-03 | 1.95E-02 | 3.74E-03 | 1.64E-02 | 2.45E-04 | 1.07E-03 | 2.67E-05 | 1.17E-04 |
| RTU3 | RTU Package Unit | 24 | 8760 | 0.045 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 3.38E-04 | 1.48E-03 | 4.45E-03 | 1.95E-02 | 3.74E-03 | 1.64E-02 | 2.45E-04 | 1.07E-03 | 2.67E-05 | 1.17E-04 |
| RTU4 | RTU Package Unit | 24 | 8760 | 0.045 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 3.38E-04 | 1.48E-03 | 4.45E-03 | 1.95E-02 | 3.74E-03 | 1.64E-02 | 2.45E-04 | 1.07E-03 | 2.67E-05 | 1.17E-04 |
| RTU5 | RTU Package Unit | 24 | 8760 | 0.061 | 7.45E-03 | 7.45E-03 | 9.80E-02 | 8.24E-02 | 5.39E-03 | 5.88E-04 | 4.53E-04 | 1.98E-03 | 5.96E-03 | 2.61E-02 | 5.01E-03 | 2.19E-02 | 3.28E-04 | 1.44E-03 | 3.58E-05 | 1.57E-04 |
| | | | | | | | | | | | **Totals** | **5.51E-02** | | **7.25E-01** | | **6.09E-01** | | **3.99E-02** | | **4.35E-03** |

[1] Emission factor from AP-42 Section 1.4 Natural Gas Combustion, Table 1.4-1& 1.4-2

[2] To convert from lb/$10^6$ scf to lb/MMBtu, the lb/$10^6$ scf emission factor is divided by the average heating value of 1,020 Btu/scf.

| GHG Emission Factors | |
|---|---|
| Natural Gas | kg/MMBtu |
| CO2 | 53.06 |
| CH4 | 1 |
| N2O | 0.1 |

* 40 CFR part 98 Subpart C

https://www.epa.gov/sites/production/files/2015-12/documents/emission-factors_nov_2015.pdf

| | GHG PTE metric tons per year | | | | GHG Actuals metric tons per year | | | |
|---|---|---|---|---|---|---|---|---|
| | CO2 | CH4 | N2O | CO2e* | CO2 | CH4 | N2O | CO2e* |
| UH1 | 34.79 | 0.66 | 6.6E-02 | 71 | 34.79 | 0.66 | 6.6E-02 | 71 |
| UH2 | 46.38 | 0.87 | 8.7E-02 | 94 | 46.38 | 0.87 | 8.7E-02 | 94 |
| UH3 | 66.68 | 1.26 | 1.3E-01 | 136 | 66.68 | 1.26 | 1.3E-01 | 136 |
| UH4 | 46.38 | 0.87 | 8.7E-02 | 94 | 46.38 | 0.87 | 8.7E-02 | 94 |
| UH5 | 46.38 | 0.87 | 8.7E-02 | 94 | 46.38 | 0.87 | 8.7E-02 | 94 |
| UH6 | 34.79 | 0.66 | 6.6E-02 | 71 | 34.79 | 0.66 | 6.6E-02 | 71 |
| UH7 | 69.57 | 1.31 | 1.3E-01 | 141 | 69.57 | 1.31 | 1.3E-01 | 141 |
| UH8 | 69.57 | 1.31 | 1.3E-01 | 141 | 69.57 | 1.31 | 1.3E-01 | 141 |
| UH9 | 69.57 | 1.31 | 1.3E-01 | 141 | 69.57 | 1.31 | 1.3E-01 | 141 |
| UH10 | 69.57 | 1.31 | 1.3E-01 | 141 | 69.57 | 1.31 | 1.3E-01 | 141 |
| UH11 | 30.61 | 0.58 | 5.8E-02 | 62 | 30.61 | 0.58 | 5.8E-02 | 62 |
| UH12 | 30.61 | 0.58 | 5.8E-02 | 62 | 30.61 | 0.58 | 5.8E-02 | 62 |
| UH13 | 30.61 | 0.58 | 5.8E-02 | 62 | 30.61 | 0.58 | 5.8E-02 | 62 |
| RTU1 | 46.38 | 0.87 | 8.7E-02 | 94 | 46.38 | 0.87 | 8.7E-02 | 94 |
| RTU2 | 21.06 | 0.40 | 4.0E-02 | 43 | 21.06 | 0.40 | 4.0E-02 | 43 |
| RTU3 | 21.06 | 0.40 | 4.0E-02 | 43 | 21.06 | 0.40 | 4.0E-02 | 43 |
| RTU4 | 21.06 | 0.40 | 4.0E-02 | 43 | 21.06 | 0.40 | 4.0E-02 | 43 |
| RTU5 | 28.20 | 0.53 | 5.3E-02 | 57 | 28.20 | 0.53 | 5.3E-02 | 57 |
| Total | 783 | 14.8 | 1.5 | 1,592 | 783 | 14.8 | 1.5 | 1,592 |

* Applies GWP values of 1, 25 and 298 as defined in Appendix C of Part 98.